



# Lifestyle Colours

## DATA SHEET STONE COAT FLOOR SYSTEM

This cementitious flooring system is designed to give a thin coat smooth surface. Ideal for recoating old screed painted floors etc. Provided the substrate is sound. Can also be applied over wood floated or steel troweled new cement screeds.

### METHOD OF APPLICATION

- 1 . Make sure surface is free of powdering, flaking etc.
- 2 . High porosity screeds should be soaked with clean water prior to application to reduce suction.
- 3 . Add 1L of water plus 10 L of Flexi floor liquid to metal container. (Do not use plastic bucket, as pieces of plastic will result in scratch marks when using a mechanical stirrer).
- 4 . Add 30kg bag of Stone coat flooring system.
- 5 . Mix to a smooth consistency.
- 6 . Allow to stand and gel for 15 minutes.
- 7 . Pour enough material to be able to trowel at arms length.
- 8 . Using a round edge trowel, trowel as smooth as possible not more than 1mm thickness.
- 9 . Complete entire application in one operation.
10. Allow drying for 24 hours.
11. Sand off any high spots using a 100 grit sand paper.
12. Apply second coat in same manner as first coat, troweling hard in an even motion - to produce an even mottled effect.
13. If necessary sand entire floor with 220g sand paper.
14. Allow drying for at least 24 hours.
15. Apply appropriate sealer for a durable finish.

Packaging:	30kg bag
Colours:	24 Awesome colours. See cement paint colour chart
Coverage:	Approximately 50m <sup>2</sup> per bag
Shelf Life:	6 Months
Cleaning of Tools:	clean tap water

### HEALTH AND SAFETY

STONE COAT FLOORING SYSTEM contains fine aggregated so inhalation of dust while mixing should be avoided. Contact with sensitive skin may cause irritation. Wear suitable protective clothing, gloves and eye protection.

### DISCLAIMER ADVICE

The information given in this product information sheet is based on controlled laboratory tests and many years of experience. It is given in good faith but no guarantee of any performance characteristic is given or implied. Lifestyle Colours cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Lifestyle Colours product. Paint technology is continually being developed and Lifestyle Colours reserves the right to update product specifications without prior notice. Contact Lifestyle Colours for details.

**TECHNICAL: 083 446 6754**

**Email: [info@lifestylecolours.co.za](mailto:info@lifestylecolours.co.za) Website: [www.lifestylecolours.co.za](http://www.lifestylecolours.co.za)**