

TECHNICAL DATA SHEET

AUTOCOTE THINNERS (DI022)

DESCRIPTION:

- **AUTOCOTE THINNERS** is a wide cut, slow evaporating, mainly aliphatic solvent.
- **AUTOCOTE THINNERS** is used for dilution of autocote paints and for the cleaning of equipment.

FEATURES:

- | | |
|--------------------------|-------------------|
| • APPEARANCE | Water like liquid |
| • S G @ 25°C (g/ml) | 0.77 |
| • VISCOSITY @ 25°C (sec) | 10 – 12 |
| • FLASH POINT (°C) | 49 |
| • FLAMMABILITY | Flammable |

STORAGE STABILITY:

- Flammable materials should be stored in a separate safety storage cabinet or room.
- Keep away from heat.
- Keep away from sources of ignition.
- Keep container tightly closed.
- Keep in a cool, well ventilated place.
- Ground all equipment containing material.
- Store away from strong oxidizing agents or combustible material

PRODUCT PACKAGING:

- 5 LT
- 25 LT
- 200 LT

COLOURS:

- Colourless



5 Wakefield Road, Founders View South, Edenvale (opposite Modderfontein golf Course) | P.O. Box 303, Edenvale, 1610, South Africa
Tel: 011 452-5221 | Fax: 011 452-2313 | orders@durapaints.co.za | www.durapaints.co.za | Director M Lloyd



Dura Paints (PTY) Ltd. - CK 2012/184075/07

SAFETY PRECAUTIONS:

- Keep out of reach of children.
- Keep away from food, drink and animal feeding stuffs
- Keep away from sources of ignition - No smoking
- Avoid contact with skin
- Wear suitable protective clothing and gloves
- In case of fire use foam/dry powder/carbon dioxide
- If swallowed, do not induce vomiting: Seek medical advice immediately and show this container or label where possible

DISCLAIMER:

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user.

They are based on results gained from our experiences and tests and are believed to be reliable.

No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

Technology may change with time necessitating changes to this Technical Data Sheet (TDS)/MSDS. It is the responsibility of the user to ensure that the latest TDS is being used. See www.durapaints.co.za for the latest version.



5 Wakefield Road, Founders View South, Edenvale (opposite Modderfontein golf Course) | P.O. Box 303, Edenvale, 1610, South Africa
Tel: 011 452-5221 | Fax: 011 452-2313 | orders@durapaints.co.za | www.durapaints.co.za | Director M Lloyd



Dura Paints (PTY) Ltd. - CK 2012/184075/07