

WEDGEWOOD CONTRACTORS.

WD 002

PRODUCT CODE:	White (Wedgewood Plastic Containers)	:CON (05) (20)
	White (Bulk minimum qty. 105 x 5lt –White containers)	:CON (05_BULK (05)
	White (Bulk minimum qty. 48 x 20lt –Blue containers)	:CON (20_BULK(SPECIAL) (20)
	Peach(Bulk minimum qty. 48 x 20lt –Blue containers)	:CONPCH (20)
	Infinity Cream (Bulk minimum qty. 48 x 20lt –Blue containers)	:CONINFC (20)

PRODUCT DESCRIPTION: *Contractors* is an economical, smooth, white acrylic coating.

INTENDED USES: Economical filler coat for interior use on dry, cement plastered walls, porous brick or as an obliteration coat to cover existing dark colours. (TIP: Consider using *Wedgewood Opulent Cover Coat* for the same application. Better overall performance-opacity, coverage, whiteness)

FEATURES: Economical coating suitable for interior use. Low odour. Lead free.

PRODUCT INFORMATION:	• APPEARANCE	Smooth matt finish.
	• COLOUR	White/Peach/Infinity Cream.
	• VOLUME SOLIDS	49% by mass 28% by volume
	• S G @ 25°C	1.42 (typical)
	• RECOMMENDED DFT	MIN : 25µm MAX: 35µm
	• PRACTICAL SPREADING RATE	6 to 8 m ² . (dependant on substrate and application thickness (DFT)
	• VISCOSITY @ 25°C (WHITE)	100-105 KU (typical)

APPLICATION DETAILS:

- MIXING Stir thoroughly with a flat paddle until homogeneous
- METHOD Brush, roller or airless spray
- THINNING Not recommended.
- CLEANING Water
- SUBSTRATE Cement plaster.
- APPLICATION ENVIRONMENT

Surface Temp	Ambient Temp	Relative Humidity
Min 10°C or 2°C above dew point	Min 10°C or 2°C above dew point	Min: 10%
Max : 40°C	Max : 40°C	Max : 85%

- DRYING TIME

Touch dry	30 Min @ 25°C
Dry to handle	1 hour @ 25°C
Overcoating	1 hour @ 25°C

STORAGE AND PACKAGING:

- Store away from direct sun, heat and severe cold. Do not exceed 50°C.
- Keep containers tightly closed.
- Packaging 5lt & 20lt
- Shelf life. 12 months from date of manufacture when correctly stored and unopened.

WEDGEWOOD OPULENT CONTRACTORS (contd.)

TRANSPORTATION:

SHIPPING NAME:	Not classified
PACKAGING GROUP:	Not classified
HAZARD CLASS:	4-H-C
S.I.N/UN NUMBER:	Not classified dangerous for transport

SURFACE PREPARATION:

Ensure all surfaces are dry, less than 12% moisture content, and free from dirt, dust, chalking, oil, grease and other contaminants before painting.

Unpainted Substrate:

Cement plaster.

- Apply one or two coats **Wedgewood Contractors**, then overcoat with appropriate **Wedgewood product**.

Previously painted substrate

- Remove all loose and flaking paint by scrapping, sanding or hydro blasting - allow to dry. Clean with **ProLong ProSoap** or **ProLong ProSoap Liquid** to remove all contaminants. Rinse off **ProLong ProSoap/ProSoap Liquid** with water.
- Apply one or two coats **Wedgewood Contractors**, then overcoat with appropriate **Wedgewood product**.
- If the surface is chalky and cannot be thoroughly cleaned, apply one coat of **Opulent Bonding Liquid**, allow to dry overnight, then apply one or two coats **Wedgewood Contractors**.
- Fill defects with **ProLong Crackfill** or **ProLong Profill**, as part of the preparation.
- Mould/Algae. Remove by scrubbing with a solution of 4:1 Water/Bleach or Water/Chlorine. Saturate affected areas and allow to stand for a minimum of 4 hours. Rinse off thoroughly with clean water and allow to dry before painting.

APPLICATION:

Apply one or two coats un-thinned to prepared surfaces so as to achieve complete obliteration. For airless spraying thinning is not normally required.

CAUTIONS:

- Avoid painting during inclement weather or if temperature is below 10°C.
- For optimum performance a practical recommended spreading rate of 6 m² / l should not be exceeded.
 - Do not apply to plaster with a moisture content of more than 12%. Allow new plaster to dry for seven days before painting.

SAFETY PRECAUTIONS:

- Keep out of reach of children.
- Ensure good ventilation during application and drying.
- In case of skin contact, wash with soap and water or a recognized skin cleaner. Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist. If ingested give plenty of water / milk. Do not induce vomiting. Seek medical attention.
- Refer to Material Safety Data Sheet for complete information. See www.durapaints.co.za.

WEDGEWOOD OPULENT CONTRACTORS (contd.)

DISCLAIMER:

- *The recommendations contained herein are given in good faith and are meant to guide the specifier or the user.*
- *They are based on results gained from our experiences and tests and are believed to be reliable.*
- *No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.*
- *Technology may change necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used. See www.durapaints.co.za.*