

WEDGEWOOD OPULENT MATTE WD 006

PRODUCT CODE: White/Pastel (Wedgewood Plastic Containers) : opmatw (01) (05) (20)
 Deep (Wedgewood Plastic Containers) : opmatde (01) (05) (20)
 Transparent (Wedgewood Plastic Containers) : opmattr (01) (05) (20)

PRODUCT DESCRIPTION: *Opulent Matte* is a long lasting premium coating with a matt finish, excellent wash ability and opacity. It is ideal for high traffic areas such as passages, bedrooms and stairwells. It is also ideal as a premium coating for exterior use. *Opulent Matte* is water-based, non-flammable and lead free.

INTENDED USES: Suitable for previously primed or painted areas such as cement plaster, gypsum plaster, concrete, fibre cement, ceiling boards, unglazed brick and steel, provided that appropriate preparation is carried out.

FEATURES: A pure acrylic suitable for interior and exterior use. Hides imperfections. Stain resistant. Low odour. Washable. Excellent coverage. This product comes with a 7 year quality guarantee. (Subject to Terms and Conditions-see www.durapaints.co.za)

PRODUCT INFORMATION:

- APPEARANCE Matte finish.
- COLOUR White, can be tinted
- VOLUME SOLIDS 48% by mass (Varies by colour/base)
34% by volume (Varies by colour/base)
- S G @ 25°C 1.30 (Varies by colour/base)
- RECOMMENDED DFT MIN : 25µm MAX: 35µm
- PRACTICAL SPREADING RATE 10 - 12 m². (dependant on substrate and application thickness (DFT))
- VISCOSITY @ 25°C (WHITE) 100-105 KU (varies by colour/base.)

APPLICATION DETAILS:

- MIXING Stir thoroughly with a flat paddle until homogeneous
- METHOD Brush, roller or airless spray
- THINNING Not recommended.
- CLEANING Water
- SUBSTRATE Cement plaster, concrete, fibre-cement, ceiling boards, gypsum plaster.
- APPLICATION ENVIRONMENT

Surface Temp	Ambient Temp	Relative Humidity
Min 10°C or 2°C above dew point	Min 10°C or 2°C above dew point	Min: 10%
Max : 40°C	Max : 40°C	Max : 85%

- DRYING TIME Touch dry 30 Min @ 25°C
 Dry to handle 2 hours @ 25°C
 Overcoating 2 hours @ 25°C

STORAGE AND PACKAGING:

- Store away from direct sun, heat and severe cold. Do not exceed 50°C.
- Keep containers tightly closed.
- Packaging 1lt, 5lt & 20lt
- Shelf life. 12 months from date of manufacture when correctly stored and unopened.

WEDGEWOOD OPULENT MATTE (cont.)

TRANSPORTATION:

SHIPPING NAME:	Not classified
PACKAGING GROUP:	Not classified
HAZARD CLASS:	4-H-C
S.I.N/UN NUMBER:	Not classified dangerous for transport

SURFACE PREPARATION:

Ensure all surfaces are dry, less than 12% moisture content, and free from rust, dirt, dust, chalking, oil, grease and any other contamination before painting.

Unpainted Substrate:

Cement plaster, concrete, ceiling boards, fibre cement, gypsum board.

- Prime with one coat **Wedgewood Opulent 2 in 1** water based primer/topcoat.
- Apply two or three coats **Wedgewood Opulent Matte**, depending on colour.

Mild Steel.

- Degrease with **ProLong Grease Devil** and rinse thoroughly with water. Allow to dry.
- Prime with one coat **Dura Hydro Prime**. (water based steel primer).
- Apply two or three coats **Wedgewood Opulent Matte**, depending on colour.

Previously painted substrate

- Remove all loose and flaking paint by scraping, sanding or hydro blasting - allow to dry. Clean with **ProLong ProSoap or ProLong ProSoap Liquid** to remove all contaminants. Rinse off **ProLong ProSoap/ProSoap Liquid** with water.
- Apply two or three coats **Wedgewood Opulent Matte**, depending on colour.
- If the surface is chalky and cannot be thoroughly cleaned, apply one coat of **Opulent Bonding Liquid**, allow to dry overnight, then apply two or three coats **Wedgewood Opulent Matte**, depending on colour.
- Fill defects with ProLong **Crackfill** or **ProLong Profill**, as part of the preparation. Fill defects in wood with **ProLong Timberfill**.
- Mould/Algae. Remove by scrubbing with a solution of 4:1 Water/Bleach or Water/Chlorine. Saturate affected areas and allow to stand for a minimum of 4 hours. Rinse off thoroughly with clean water and allow to dry before painting.

APPLICATION:

Apply two (three coats for some low hiding colours) un-thinned to prepared surfaces so as to achieve complete obliteration. Thin with a minimum amount of water for conventional spray application. For airless spraying thinning is not normally required

CAUTIONS:

- Avoid painting during inclement weather or if temperature is below 10°C.
- For optimum performance a practical recommended spreading rate of 10 m² / l should not be exceeded.
- It is very important to purchase sufficient paint to complete the project. Different batches may result in slight variations in colour that are beyond the control of the manufacturer.

WEDGEWOOD OPULENT MATTE (cont.)

SAFETY PRECAUTIONS:

- Keep out of reach of children.
 - Ensure good ventilation during application and drying.
 - In case of skin contact, wash with soap and water or a recognized skin cleaner. Avoid contact with eyes – In case of contact with eyes rinse immediately with plenty of water and seek medical advice if symptoms persist. If ingested give plenty of water / milk. Do not induce vomiting. Seek medical attention.
 - Refer to Material Safety Data Sheet for complete information. See www.durapaints.co.za.
-

DISCLAIMER:

- *The recommendations contained herein are given in good faith and are meant to guide the specifier or the user.*
- *They are based on results gained from our experiences and tests and are believed to be reliable.*
- *No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.*
- *Technology may change necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used. See www.durapaints.co.za.*