

WEDGEWOOD OPULENT SUPER ACRYLIC

WD 010

| | | |
|----------------------|---|---------------------|
| PRODUCT CODE: | White/Pastel (Wedgewood Plastic Containers) | : opsupw (05) (20) |
| | Deep (Wedgewood Plastic Containers) | : opsupde (05) (20) |
| | Transparent (Wedgewood Plastic Containers) | : opsuptr (05) (20) |

PRODUCT DESCRIPTION: *Opulent Super Acrylic* is a durable coating with a matt finish and good washability. It is ideal for interior and exterior use. *Opulent Super Acrylic* is water-based, non-flammable and lead free.

INTENDED USES: Suitable for previously primed or painted areas such as cement plaster, gypsum plaster, concrete, fibre cement, ceiling boards, unglazed brick, provided that appropriate preparation is carried out.

FEATURES: *Opulent Super Acrylic* is smooth matt coating ideal for interior and exterior use. Low odour. Washable. Lead Free.

| | |
|-----------------------------|---|
| PRODUCT INFORMATION: | <ul style="list-style-type: none"> • APPEARANCE Matt finish. • COLOUR White, can be tinted • SOLIDS % 57% by mass (Varies by colour/base) 37% by volume (Varies by colour/base) • S G @ 25°C 1.49 (Varies by colour/base) • RECOMMENDED DFT MIN : 20µm MAX: 35µm • PRACTICAL SPREADING RATE 8 to 10 m². (dependant on substrate and application thickness (DFT)) • VISCOSITY @ 25°C (WHITE) 100-105 KU (varies by colour/base.) |
|-----------------------------|---|

| | |
|-----------------------------|---|
| APPLICATION DETAILS: | <ul style="list-style-type: none"> • MIXING Stir thoroughly with a flat paddle until homogeneous • METHOD Brush, roller or airless spray • THINNING Not recommended. • CLEANING Water • SUBSTRATE Cement plaster, concrete, fibre-cement, ceiling boards, gypsum plaster. • APPLICATION ENVIRONMENT |
|-----------------------------|---|

| Surface Temp | Ambient Temp | Relative Humidity |
|---------------------------------|---------------------------------|-------------------|
| Min 10°C or 2°C above dew point | Min 10°C or 2°C above dew point | Min: 10% |
| Max : 40°C | Max : 40°C | Max : 85% |

| | | |
|---------------|---------------|----------------|
| • DRYING TIME | Touch dry | 30 Min @ 25°C |
| | Dry to handle | 2 hours @ 25°C |
| | Overcoating | 2 hours @ 25°C |

STORAGE AND PACKAGING:

- Store away from direct sun, heat and severe cold. Do not exceed 50°C.
- Keep containers tightly closed.
- Packaging. 5lt & 20lt
- Shelf life. 12 months from date of manufacture when correctly stored and unopened.

WEDGEWOOD SUPER ACRYLIC (contd.)

TRANSPORTATION:

| | |
|------------------|--|
| SHIPPING NAME: | Not classified |
| PACKAGING GROUP: | Not classified |
| HAZARD CLASS: | 4-H-C |
| S.I.N/UN NUMBER: | Not classified dangerous for transport |

SURFACE PREPARATION:

Ensure all surfaces are dry, less than 12% moisture content, and free from dirt, dust, chalking, oil, grease and any other contamination before painting.

Unpainted Substrate:

Cement plaster, concrete, ceiling boards, fibre cement, gypsum board.

- Prime with one coat *Wedgewood Opulent 2 in 1* water based primer/topcoat.
- Apply two or three coats *Wedgewood Opulent Super Acrylic*, depending on colour.

Previously painted substrate

- Remove all loose and flaking paint by scrapping, sanding or hydro blasting - allow to dry. Clean with *ProLong ProSoap or ProLong ProSoap Liquid* to remove all contaminants. Rinse off *ProLong ProSoap/ProSoap Liquid* with water.
- Apply two or three coats *Wedgewood Opulent Super Acrylic*, depending on colour.
- If the surface is chalky and cannot be thoroughly cleaned, apply one coat of *Opulent Bonding Liquid*, allow to dry overnight, then apply two or three coats of *Wedgewood Opulent Super Acrylic*, depending on colour.
- Fill defects with ProLong *Crackfill* or *ProLong Profill*, as part of the preparation. Fill defects in wood with *ProLong Timberfill*
- Mould/Algae. Remove by scrubbing with a solution of 4:1 Water/Bleach or Water/Chlorine. Saturate affected areas and allow to stand for a minimum of 4 hours. Rinse off thoroughly with clean water and allow to dry before painting.

APPLICATION:

Apply two (three coats for some low hiding colours) un-thinned to prepared surfaces so as to achieve complete obliteration. When applying with Airless spraying equipment thinning is not normally required.

CAUTIONS:

- Avoid painting during inclement weather or if temperature is below 10°C.
- For optimum performance a practical recommended spreading rate of 8 m² / l should not be exceeded.
- It is very important to purchase sufficient paint to complete the project. Different batches may result in slight variations in colour that are beyond the control of the manufacturer.

WEDGEWOOD OPULENT SUPER ACRYLIC (contd.)

SAFETY PRECAUTIONS:

- Keep out of reach of children.
- Ensure good ventilation during application and drying.
- In case of skin contact, wash with soap and water or a recognized skin cleaner. Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist. If ingested give plenty of water / milk. Do not induce vomiting. Seek medical attention.
- Refer to Material Safety Data Sheet for complete information. See www.durapaints.co.za.

DISCLAIMER:

- *The recommendations contained herein are given in good faith and are meant to guide the specifier or the user.*
- *They are based on results gained from our experiences and tests and are believed to be reliable.*
- *No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.*
- *Technology may change necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used. See www.durapaints.co.za.*