

1. PRODUCT AND COMPANY IDENTIFICATION

Trade Name	WEDGEWOOD OPULENT UNIVERSAL UNDERCOAT (WD015)
Synonyms	Alkyd based paint.
Description	A blend of pigments in a solvent based alkyd binder.
Dura Paints (PTY) Ltd	5 Wakefield Road, Founders View South, Edenvale, 1610, South Africa.
Contact us on	+27 11 452-5221

2. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Class	Alkyd based paint.
EC Classification	Flammable
Comment	Liquid Form
R-Phrases:	R10, 20/21, 65
S-Phrases:	S2, 13, 43, 62

3. HAZARDS IDENTIFICATION

SAPMA Health Rating	2- Moderate – Temporary or minor injury possible even if treatment given.
Flammable	Flammable with toxic fumes.
Harmful	Ensure sufficient ventilation, avoid inhalation of vapours. Avoid contact with skin or eyes.
Ingestion	Irritating and nauseating. May cause lung damaged if swallowed.
Skin contact	Irritating. Direct contact to be avoided may cause dermatitis.
Inhalation	Avoid exposures to vapours, fumes and mist.
Eye contact	Irritating. Avoid contact. May cause irreversible damage.

4. FIRST AID MEASURE

Ingestion	Wash mouth with plenty of water. Do not induce vomiting. Seek medical attention.
Skin	Wash with soap and water or a recognised skin cleaner. Avoid use of solvents.
Inhalation	Move to fresh air. In case of discomfort seek medical attention.
Eyes	In case of contact immediately flush eyes with clean water for at least 15 minutes. Obtain medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Extinguishing media	Use foam, CO ₂ , dry powder. Use fog to cool-do not use water jets.
Special Hazards	Can form explosive vapour/air mixture.
Protective Equipment	In case of fire, wear respiratory protection.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:	Surface may be slippery. Wear protective equipment to prevent skin and eye contact and breathing vapours.
Environmental Precautions:	Do not allow product to enter sewage drains, soil or watercourses.
Clean up method:	Contain & collect spillage with non-combustible absorbent material and dispose of according to local regulations. Do not allow product to enter drains and sewers.

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage:

Technical measures:	Precautions to be taken in handling and storage as per packaging instructions.
Safe handling:	Avoid contact with eyes.
Packaging materials:	Keep in original container.
Storage conditions:	Store in a cool, dry, well ventilated area away from direct sun, sources of heat, and severe cold.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

SAPMA Rating	2-H-E PPE – Eye Protection
Inhalation	In case of insufficient ventilation use suitable respiratory protection.
Skin	Avoid contact as far as possible. Observe the rules of hygiene. Wash before eating, drinking or smoking. Use barrier cream and gloves.
Eyes	Avoid direct contact. Never touch eyes with dirty hands or gloves. Use safety glasses.
Ingestion	Observe the rules of hygiene. Wash hands before eating, drinking or smoking.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance :	White Liquid	Odour	Solvent
Specific Gravity (g/ml)	1.33 (typical)	Viscosity @ 25 C	75 TO 80 KU (typical)
Solubility	Soluble in solvent, insoluble in water.		

10. STABILITY AND REACTIVITY

Stable under normal conditions.	
No reaction with fire-fighting water.	Avoid contact with strong oxidising agents.
Conditions to avoid	Avoid contact with acids and alkalis. Potential for spontaneous combustion.

11. TOXICOLOGICAL INFORMATION

No records of chronic effects found.

12. ECOLOGICAL INFORMATION

May have short term environmental effects. Contain, monitor & remove. Do not discharge into drains, lakes, streams, ponds, etc.

13. DISPOSAL CONSIDERATIONS

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Exercise caution in disposal of used containers

14. TRANSPORT INFORMATION

SHIPPING NAME:	Paint
PACKAGING GROUP:	111
HAZARD CLASS:	3
UN / S.I.N NUMBER:	1263.

15. REGULATORY INFORMATION

Classification: Flammable

S-Phases: S2 - Keep out of reach of children.
S13- Keep away from food, drink and animal feed.
S24/25 – Avoid contact with eyes and skin
S43- In case of fire, use water fog, foam or powder. Do not use water jets.
S62- If swallowed do not induce vomiting. See medical advice immediately.

R-Phases: R10- Flammable.
R20/21- Harmful by inhalation and skin contact
R65- May cause lung damage if swallowed.

16. OTHER INFORMATION

This data is offered in good faith as typical values and not as a product specification. No warranty, whether expressed or implied is made. All information is given in good faith, but without guarantee in respect of accuracy and no responsibility is accepted for errors or omissions or the consequences thereof. The current version of this Material Safety Data Sheet (MSDS) and Technical Data Sheet (TDS) are available from Dura Paints website - www.durapaints.co.za.

C	=	Ceiling limit	NEGL	=	Negligible
EST	=	Estimated	NF	=	None found
NA	=	Not applicable	UNKN	=	Unknown
NE	=	None established	REC	=	Recommended
ND	=	None determined	V	=	Recommended by vendor
TS	=	Trade secret	SKN	=	Skin
R	=	Recommended	MST	=	Mist

END OF MSDS