

WEDGEWOOD OPULENT RIPPLE COAT

WD 016

PRODUCT CODE: White (Wedgewood Plastic Containers) : opripw (05) (20)

PRODUCT DESCRIPTION: *Opulent Ripple Coat* is a long lasting coating with a smooth stipple texture. It is ideal for hiding hairline cracks, blemishes in plasterwork and painting correctly prepared concrete ceilings. *Opulent Ripple Coat* is water-based, non- flammable and lead free.

INTENDED USES: Suitable for previously primed or painted areas such as cement plaster, gypsum plaster , concrete, fibre cement, ceiling boards and unglazed brick, provided that appropriate preparation is carried out.

FEATURES: Suitable for interior and exterior use. Hides imperfections and hairline cracks. Stain resistant. Low odour. Excellent coverage.

PRODUCT INFORMATION:

- APPEARANCE Matt stipple finish.
- COLOUR White
- VOLUME SOLIDS 47% by mass (Typical)
36% by volume (Typical)
- S G @ 25°C 1.34 (Typical)
- RECOMMENDED DFT MIN : 20µm MAX: 35µm
- PRACTICAL SPREADING RATE 4 -6 m². (dependant on substrate and application thickness (DFT)
- VISCOSITY @ 25°C (WHITE) 150 to 155 KU

APPLICATION DETAILS:

- MIXING Stir thoroughly with a flat paddle until homogeneous
- METHOD TEXTURE Roller only.
- THINNING Not recommended.
- CLEANING Water
- SUBSTRATE Cement plaster, concrete, fibre-cement, ceiling boards, gypsum plaster.
- APPLICATION ENVIRONMENT

Surface Temp	Ambient Temp	Relative Humidity
Min 10°C or 2°C above dew point	Min 10°C or 2°C above dew point	Min: 10%
Max : 40°C	Max : 40°C	Max : 85%

- DRYING TIME Touch dry 30 Min @ 25°C
Dry to handle 2 hours @ 25°C
Overcoating 2 hours @ 25°

STORAGE AND PACKAGING:

- Store away from direct sun, heat and severe cold. Do not exceed 50°C.
- Keep containers tightly closed.
- Packaging 5lt & 20lt
- Shelf life. 12 months from date of manufacture when correctly stored and unopened.

WEDGEWOOD OPULENT RIPPLE COAT (contd.)

TRANSPORTATION:

SHIPPING NAME:	Not classified
PACKAGING GROUP:	Not classified
HAZARD CLASS:	4-H-C
S.I.N/UN NUMBER:	Not classified dangerous for transport

SURFACE PREPARATION:

Ensure all surfaces are dry, less than 12% moisture content, and free from rust, dirt, dust, chalking, oil, grease and any other contamination before painting.

Unpainted Substrate:

Cement plaster, concrete, ceiling boards, fibre cement, gypsum board.

- Prime with one coat **Wedgewood Opulent 2 in 1** water based primer/topcoat or Opulent Bonding Liquid.
- Apply one or two coats **Wedgewood Opulent Ripple Coat**.

Previously painted substrate

- Remove all loose and flaking paint by scrapping, sanding or hydro blasting - allow to dry. Clean with **ProLong ProSoap or ProLong ProSoap Liquid** to remove all contaminants. Rinse off **ProLong ProSoap/ProSoap Liquid** with water.
- Apply one or two coats **Wedgewood Opulent Ripple Coat**.
- If the surface is chalky and cannot be thoroughly cleaned, apply one coat of **Opulent Bonding Liquid**, allow to dry overnight, then apply two or three coats **Wedgewood Ripple Coat**.
- Fill defects with ProLong **Crackfill** or **ProLong Profill**, as part of the preparation.
- Mould/Algae. Remove by scrubbing with a solution of 4:1 Water/Bleach or Water/Chlorine. Saturate affected areas and allow to stand for a minimum of 4 hours. Rinse off thoroughly with clean water and allow to dry before painting.

APPLICATION:

Apply one or two coats un-thinned to prepared surfaces so as to achieve complete obliteration and required finish.

CAUTIONS:

- Avoid painting during inclement weather or if temperature is below 10°C.
- For optimum performance a practical recommended spreading rate of 4m² / l should not be exceeded.
- Some technique is required to achieve the desired finish. Use a TEXTURE ROLLER only

SAFETY PRECAUTIONS:

- Keep out of reach of children.
- Ensure good ventilation during application and drying.
- In case of skin contact, wash with soap and water or a recognized skin cleaner. Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist. If ingested give plenty of water / milk. Do not induce vomiting. Seek medical attention.
- Refer to Material Safety Data Sheet for complete information. See www.durapaints.co.za.

WEDGEWOOD OPULENT RIPPLE COAT (contd.)

DISCLAIMER:

- *The recommendations contained herein are given in good faith and are meant to guide the specifier or the user.*
- *They are based on results gained from our experiences and tests and are believed to be reliable.*
- *No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.*
- *Technology may change necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used. See www.durapaints.co.za.*