

WEDGEWOOD OPULENT PLASTER PRIMER

WD 020

PRODUCT CODE: White (Wedgewood plastic containers) : OPPLAP (01) (05) (20)

PRODUCT DESCRIPTION: *Opulent Plaster Primer* is a top quality, Nano particle copolymer. *Opulent Plaster Primer* is water-based, non- flammable and lead free.

INTENDED USES: Suitable for priming cement plaster, concrete, fibre cement, ceiling boards and unglazed brick, provided that appropriate preparation is carried out.

FEATURES: A deep penetrating acrylic suitable for interior and exterior use. Water based. Ammonia and Formaldehyde free. Very low odour. Alkali resistant. Low VOCs. APEO free. Fast drying and short over coating cycle. Can be over coated with any **Wedgewood Opulent** water based product. Tintable, in pastel colours only. Excellent penetration and binding on porous, friable or chalky substrates.

PRODUCT INFORMATION:

- APPEARANCE Matt finish.
- COLOUR White. Can be tinted to light pastel colours.
- VOLUME SOLIDS 34% by mass.
23% by volume.
- S G @ 25°C 1.19
- RECOMMENDED DFT First coat -penetrating.
- PRACTICAL SPREADING RATE 4 to 6 m². (dependant on substrate and application thickness (DFT)
- VISCOSITY @ 25°C (WHITE) 70 TO 75 KU.

APPLICATION DETAILS:

- MIXING Stir thoroughly with a flat paddle until homogeneous
- METHOD Brush, roller or airless spray
- THINNING Not recommended.
- CLEANING Water
- SUBSTRATE Cement plaster, concrete, fibre-cement, ceiling boards.
- APPLICATION ENVIRONMENT

Surface Temp	Ambient Temp	Relative Humidity
Min 10°C or 2°C above dew point	Min 10°C or 2°C above dew point	Min: 10%
Max : 40°C	Max : 40°C	Max : 85%

- DRYING TIME

Touch dry	30 Min @ 25°C
Dry to handle	1 hour @ 25°C
Overcoating	3 hours @ 25°C

STORAGE AND PACKAGING:

- Store away from direct sun, heat and severe cold. Do not exceed 50°C.
- Keep containers tightly closed.
- Packaging 1lt, 5lt & 20lt
- Shelf life. 12 months from date of manufacture when correctly stored and unopened.

TRANSPORTATION:

SHIPPING NAME: Not classified
PACKAGING GROUP: Not classified
HAZARD CLASS: 4-H-C
S.I.N/UN NUMBER: Not classified dangerous for transport

SURFACE PREPARATION:

Ensure all surfaces are dry, less than 12% moisture content, and free from rust, dirt, dust, chalking, oil, grease and any other contamination before painting.

Unpainted Substrate:

Cement plaster, concrete, ceiling boards, fibre cement, gypsum board.

WEDGEWOOD OPULENT PLASTER PRIMER (cont.)

SURFACE PREPARATION (cont.):

- Prime with one or two coats **Wedgewood Plaster Primer**. **NB: This product has been developed with a lower viscosity than normal decorative coatings to ensure optimal penetration and adhesion.**
- After priming apply two or three coats from the **Wedgewood Opulent** range, depending on colour.
- Fill defects with **ProLong Crackfill** or **ProLong Profill**, as part of the preparation.
- Mould/Algae. Remove by scrubbing with a solution of 4:1 Water/Bleach or Water/Chlorine. Saturate affected areas and allow to stand for a minimum of 4 hours. Rinse off thoroughly with clean water and allow to dry before painting.

APPLICATION:

Apply one or two coats, un-thinned to prepared surfaces.

CAUTIONS:

- Avoid painting during inclement weather or if temperature is below 10°C.
- For optimum performance a practical recommended spreading rate of 4 m² / l should not be exceeded.
- Do not tint to deep or very deep colours as this will affect coating performance.
- If tinted it is very important to purchase sufficient paint to complete the project. Different batches may result in slight variations in colour that are beyond the control of the manufacturer.
- Do not apply to concrete or plaster substrates that contain more than 12% moisture.
- It is recommended that solvent based **Opulent Bonding Liquid** is used as a primer on Rhinolite.

SAFETY PRECAUTIONS:

- Keep out of reach of children.
- Ensure good ventilation during application and drying.
- In case of skin contact, wash with soap and water or a recognized skin cleaner. Avoid contact with eyes. In case of contact with eyes rinse immediately with plenty of water and seek medical advice if symptoms persist. If ingested give plenty of water / milk. Do not induce vomiting. Seek medical attention.
- Refer to Material Safety Data Sheet for complete information. See www.durapaints.co.za.

DISCLAIMER:

- *The recommendations contained herein are given in good faith and are meant to guide the specifier or the user.*
- *They are based on results gained from our experiences and tests and are believed to be reliable.*
- *No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.*
- *Technology may change necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used. See www.durapaints.co.za.*