

**1. PRODUCT AND COMPANY IDENTIFICATION**

Trade Name	WEDGEWOOD OPULENT SB PLASTER PRIMER (WD022)
Synonyms	Acrylic co-polymer resin based paint.
Description	A blend of pigments in a solvent based binder.
Dura Paints (PTY) Ltd	5 Wakefield Road, Founders View South, Edenvale, 1610, South Africa.
Contact us on	+27 11 452-5221

**2. COMPOSITION / INFORMATION ON INGREDIENTS**

<b>Chemical Class</b>	Acrylic co-polymer resin based paint.
<b>EC Classification</b>	Harmful, Xn, N.
<b>Comment</b>	Liquid Form
<b>Chemical Name:</b>	Petroleum Spirits (White Spirits). CAS No 64475-85-0. Weight% < 33.
<b>R-Phrases:</b>	R10, 20/21, 65
<b>S-Phrases:</b>	S2,13,24/25,43,62

**3. HAZARDS IDENTIFICATION**

SAPMA Health Rating	2- Moderate – Temporary or minor injury possible even if treatment given.
Flammable	Flammable with toxic fumes.
Harmful	Ensure sufficient ventilation, avoid inhalation of vapours. Avoid contact with skin or eyes.
Ingestion	Irritating and nauseating. May cause lung damaged if swallowed.
Skin contact	Irritating. Direct contact to be avoided may cause dermatitis.
Inhalation	Avoid exposures to vapours, fumes and mist.
Eye contact	Irritating. Avoid contact. May cause irreversible damage.

**4. FIRST AID MEASURE**

Ingestion	Wash mouth with plenty of water. Do not induce vomiting. Seek medical attention.
Skin	Wash with soap and water or a recognised skin cleaner. Avoid use of solvents.
Inhalation	Move to fresh air. In case of discomfort seek medical attention.
Eyes	In case of contact immediately flush eyes with clean water for at least 15 minutes. Obtain medical attention if irritation persists.

**5. FIRE FIGHTING MEASURES**

Extinguishing media	Use foam, CO <sub>2</sub> , dry powder. Use fog to cool-do not use water jets.
Special Hazards	Can form explosive vapour/air mixture.
Protective Equipment	In case of fire, wear respiratory protection.

**6. ACCIDENTAL RELEASE MEASURES**

Personal precautions:	Surface may be slippery. Wear protective equipment to prevent skin and eye contact and breathing vapours.
Environmental Precautions:	Do not allow product to enter sewage drains, soil or watercourses.
Clean up method:	Contain & collect spillage with non-combustible absorbent material and dispose of according to local regulations. Do not allow product to enter drains and sewers.

**7. HANDLING AND STORAGE**

Precautions to be taken in handling and storage:

Technical measures:	Precautions to be taken in handling and storage as per packaging instructions.
Safe handling:	Avoid contact with eyes.
Packaging materials:	Keep in original container.
Storage conditions:	Store in an approved Fire Store and keep cool, dry, well ventilated and away from direct sun, sources of heat and severe cold.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

SAPMA Rating	3-H-E PPE – Eye Protection
Inhalation	In case of insufficient ventilation use suitable respiratory protection.
Skin	Avoid contact as far as possible. Observe the rules of hygiene. Wash before eating, drinking or smoking. Use barrier cream and gloves.
Eyes	Avoid direct contact. Never touch eyes with dirty hands or gloves. Use safety glasses.
Ingestion	Observe the rules of hygiene. Wash hands before eating, drinking or smoking.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance :	White/Opaque Liquid	Odour	Solvent
Specific Gravity (g/ml)	1.39 (typical)	Viscosity @ 25 C	68 TO 72 KU
Solubility	Soluble in solvent, insoluble in water.		

**10. STABILITY AND REACTIVITY**

Stable under normal conditions.	
No reaction with fire-fighting water	Avoid contact with strong oxidising agents.
Conditions to avoid	Avoid contact with acids and alkalis, potential for spontaneous combustion.

**11. TOXICOLOGICAL INFORMATION**

No records of chronic effects found.

**12. ECOLOGICAL INFORMATION**

May have short term environmental effects. Contain, monitor & remove. Do not discharge into drains, lakes, streams, ponds, etc.

**13. DISPOSAL CONSIDERATIONS**

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Exercise caution in disposal of used containers

**14. TRANSPORT INFORMATION**

SHIPPING NAME:	Paint
PACKAGING GROUP:	111
HAZARD CLASS:	3
UN / S.I.N NUMBER:	1263

**15. REGULATORY INFORMATION**

Classification:	Harmful, Xn,N
S-Phases:	S2 - Keep out of reach of children. S13- Keep away from food, drink and animal feed. S24/25 – Avoid contact with eyes and skin S43- In case of fire, use water fog, foam or powder. Do not use water jets. S62- If swallowed do not induce vomiting. See medical advice immediately.
R-Phases:	R10- Flammable. R20/21- Harmful by inhalation and skin contact R65- May cause lung damage if swallowed.

**16. OTHER INFORMATION**

This data is offered in good faith as typical values and not as a product specification. No warranty, whether expressed or implied is made. All information is given in good faith, but without guarantee in respect of accuracy and no responsibility is accepted for errors or omissions or the consequences thereof. The current version of this Material Safety Data Sheet (MSDS) and Technical Data Sheet (TDS) are available from Dura Paints website - [www.durapaints.co.za](http://www.durapaints.co.za).

# MATERIAL SAFETY DATA SHEET

C	=	Ceiling limit	NEGL	=	Negligible
EST	=	Estimated	NF	=	None found
NA	=	Not applicable	UNKN	=	Unknown
NE	=	None established	REC	=	Recommended
ND	=	None determined	V	=	Recommended by vendor
TS	=	Trade secret	SKN	=	Skin
R	=	Recommended	MST	=	Mist

**END OF MSDS**