

WEDGEWOOD OPULENT SB PLASTER PRIMER

WD 022

PRODUCT CODE: White (Wedgewood metal can) : OPSBPLAP (05)
White (White metal can) : OPSBPLAP (20)

PRODUCT DESCRIPTION: *Opulent SB Plaster Primer* is a top quality, solvent based plaster primer. It is ideal as a primer for Rhinolite and plaster. *Opulent SB Plaster Primer* is lead free.

INTENDED USES: Suitable for priming Rhinolite, cement plaster, concrete, fibre cement, ceiling boards and unglazed brick, provided that appropriate preparation is carried out.

FEATURES: A deep penetrating acrylic copolymer suitable for interior and exterior use. Alkali resistant. Fast drying and short over coating cycle. Can be over coated with any **Wedgewood Opulent** water based product. Excellent penetration and binding on porous, friable or chalky substrates.

PRODUCT INFORMATION:

• APPEARANCE	Matt finish.
• COLOUR	White.
• VOLUME SOLIDS	55% by mass. 35% by volume.
S G @ 25°C	1.20 (typical)
• RECOMMENDED DFT	First coat -penetrating.
• PRACTICAL SPREADING RATE	4 to 6 m ² . (dependant on substrate and application thickness (DFT)
• VISCOSITY @ 25°C (WHITE)	68 TO 72 KU.

APPLICATION DETAILS:

• MIXING	Stir thoroughly with a flat paddle until homogeneous
• METHOD	Brush, roller or airless spray
• THINNING	Dura White Spirits/Mineral Turps. (minimum required to apply)
• CLEANING	Dura White Spirits/Mineral Turps or Dura Lacquer Thinners.
• SUBSTRATE	Rhinolite, Cement plaster, concrete, fibre-cement, ceiling boards.
• APPLICATION ENVIRONMENT	

Surface Temp	Ambient Temp	Relative Humidity
Min 10°C or 2°C above dew point	Min 10°C or 2°C above dew point	Min: 10%
Max : 40°C	Max : 40°C	Max : 85%

• DRYING TIME	Touch dry	30 Min @ 25°C
	Dry to handle	1 hour @ 25°C
	Overcoating	2 hours @ 25°C

STORAGE AND PACKAGING:

- Store away from direct sun, heat and severe cold. Do not exceed 50°C.
- Keep containers tightly closed.
- Packaging 5lt & 20lt metal containers
- Shelf life. 12 months from date of manufacture when correctly stored and unopened.
- Flammable. Store in an approved Fire Store.

TRANSPORTATION:

SHIPPING NAME: Paint
PACKAGING GROUP: 111
HAZARD CLASS: 3
UN NUMBER: 1263

SURFACE PREPARATION: Ensure all surfaces are dry, less than 12% moisture content, and free from rust, dirt, dust, chalking, oil, grease and any other contamination before painting.

Unpainted Substrate:

Cement plaster, concrete, ceiling boards, fibre cement, gypsum board.

WEDGEWOOD OPULENT SB PLASTER PRIMER (cont.)

SURFACE PREPARATION (cont.):

- Prime with one or two coats **Wedgewood SB Plaster Primer**. **NB: This product has been developed with a lower viscosity than normal decorative coatings to ensure optimal penetration and adhesion.**
- After priming apply two or three coats from the **Wedgewood Opulent** range, depending on colour.
- Fill defects with **ProLong Crackfill** or **ProLong Profill**, as part of the preparation.
- Mould/Algae. Remove by scrubbing with a solution of 4:1 Water/Bleach or Water/Chlorine. Saturate affected areas and allow to stand for a minimum of 4 hours. Rinse off thoroughly with clean water and allow to dry before painting.

APPLICATION:

Apply one or two coats to prepared surfaces.

CAUTIONS:

- Avoid painting during inclement weather or if temperature is below 10°C.
 - For optimum performance a practical recommended spreading rate of 6 m² / l should not be exceeded.
 - Do not apply to concrete or plaster substrates that contain more than 12% moisture.
-

SAFETY PRECAUTIONS:

- Keep out of reach of children.
 - Ensure good ventilation during application and drying.
 - In case of skin contact, wash with soap and water or a recognized skin cleaner. Avoid contact with eyes. In case of contact with eyes rinse immediately with plenty of water and seek medical advice if symptoms persist. If ingested give plenty of water / milk. Do not induce vomiting. Seek medical attention.
 - Refer to Material Safety Data Sheet for complete information. See www.durapaints.co.za.
-

DISCLAIMER:

- *The recommendations contained herein are given in good faith and are meant to guide the specifier or the user.*
- *They are based on results gained from our experiences and tests and are believed to be reliable.*
- *No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.*
- *Technology may change necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used. See www.durapaints.co.za.*