

PROLONG GREASE DEVIL

PL041

PRODUCT CODE: GREASE DEVIL : PLGREASEDEV (750) (01) (05) (25)

PRODUCT DESCRIPTION: *ProLong Grease Devil* is a super concentrated all purpose power cleaner.

INTENDED USES:

- *ProLong Grease Devil* combines with water to emulsify tough grease and dirt allowing for easy cleaning.
- *ProLong Grease Devil L* may be diluted up to 100 times with cold water for general purpose cleaning or used concentrated for stubborn grease and dirt.
- *ProLong Grease Devil* can be used in the home, office, or factory to lift and remove grease, grime, oil, grit, ink, coffee, wet paint, rubber marks, mud and dirt from ceramics, clay tiles, vinyl floors, corrugated iron, metal, copper, chrome, mag wheels, baths, grills plastic, concrete, timber, enamel, fabric, glass, etc.
- *ProLong Grease Devil* replaces the need to use most general purpose cleaners that have toxic chemicals as active ingredients. It is a general purpose cleaner, tile cleaner, dustbin degreaser, floor cleaner, window cleaner, white board cleaner, work top spray and wipe and braai degreaser.

FEATURES:

- Non Toxic
- Biodegradable
- Solvent Free
- *Dilution Ratios:*
- Light duty (all purpose spray and wipe) 1:100
- Medium Duty 1:40
- Heavy Duty 1:20 or less depending of degree of contamination.

PRODUCT INFORMATION:

- APPEARANCE Coloured liquid.
- COLOUR Pink / Red
- FRAGRANCE Ammonia Free
- S G @ 25°C 0.5 - 1
- PH 8.5 - 10

APPLICATION DETAILS:

- MIXING Dilute with water, stir properly or shake
- METHOD Brush with an electric floor cleaner, stiff broom, mop or cloth
- THINNING Recommended (Water)
- CLEANING Water
- SUBSTRATE Undercarriages, corrugated iron roofs, metal surfaces, tools, engine parts and other equipment. Cars, caravans, counter tops, furniture, tiled floors and vinyl surfaces.
- APPLICATION ENVIRONMENT

Surface Temp	Ambient Temp	Relative Humidity
Min 10°C or 2°C above dew point	Min 10°C or 2°C above dew point	Min: 10%
Max : 40°C	Max : 40°C	Max : 85%

STORAGE AND PACKAGING:

- Store away from direct sun, heat and severe cold. Do not exceed 50°C.
- Keep containers tightly closed.
- Packaging: 750ml, 1lt, 5lt & 25lt.
- Shelf life. 12 months from date of manufacture when correctly stored and unopened.

TRANSPORTATION:

SHIPPING NAME: Not classified
PACKAGING GROUP: Not classified
HAZARD CLASS: 3-H-C
S.I./UN NUMBER: Not classified dangerous for transport

PROLONG GREASE DEVIL (contd.)

SURFACE PREPARATION:

- Dilute with **1 part** water for general cleaning or undercarriages, corrugated iron roofs, metal surfaces, tools, engine parts and other equipment.
- Dilute with **20 parts** water for washing cars or caravans.
- Dilute with **40 parts** water for general purpose cleaning of counter tops, furniture, tiled floors and vinyl surfaces.
- Dilute with **100 parts** water for an excellent general purpose spray and wipe for windows and glass tops, etc.

APPLICATION:

Dilute as above.

- Apply diluted **ProLong Grease Devil** (as required) over area to be cleaned.
- Brush with an electric floor cleaner, stiff broom, mop or cloth.
- Wash down and rinse with clean water.

CAUTIONS:

- For optimum performance a practical recommended dilution ratio should not be exceeded.

SAFETY PRECAUTIONS:

- Keep out of reach of children.
- Ensure good ventilation during application and drying. Do not ingest or inhale.
- In case of skin contact, wash with soap and water or a recognized skin cleaner. Avoid contact with eyes – In case of contact with eyes rinse immediately with plenty of water and seek medical advice if symptoms persist. If ingested give plenty of water / milk. Do not induce vomiting. Seek medical attention.
- Refer to Material Safety Data Sheet for complete information. See www.durapaints.co.za.

DISCLAIMER:

- *The recommendations contained herein are given in good faith and are meant to guide the specifier or the user.*
- *They are based on results gained from our experiences and tests and are believed to be reliable.*
- *No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.*
- *Technology may change necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used. See www.durapaints.co.za.*