

UN NO	1263
Class/Division	3
Subsidiary risk	
Packaging Group	II
ERG No	.

SECTION 1: PROPER SHIPPING NAME:

PROPER SHIPPING NAME: LACQUER THINNERS
(Flammable liquid (flash point less than 23°C or boiling point not exceeding 35°C))

Manufacturer or supplier's details
Company
Address

Dura Paints (PTY) Ltd
5 Wakefield Road,
Founders View South,
Edenvale, 1610,
South Africa.
+27 11 452-5221
orders@durapaints.co.za
+27 11 452-5221

Telephone
E-mail address
Emergency telephone number

SECTION 2. APPEARANCE

APPEARANCE:

- Colourless liquid or paste.
- Usually with perceptible odour.
- Immiscible or partly miscible with water – Lighter than water.

SECTION 3. DANGER

DANGER:

- Highly flammable.
- May form explosive mixture with air, particularly in empty uncleaned receptacles.
- May evaporate quickly.
- Heating will cause pressure rise, severe risk or bursting and subsequent explosion.
- The vapour is heavier than air and spreads along ground.
- The vapour may be invisible.
- The vapour may have narcotic effect.
- The vapour may have irritant effect on eyes, skin and air passages.

SECTION 4. PERSONAL PROTECTIVE EQUIPMENT/ EMERGENCY RESPONSE EQUIPMENT

PERSONAL PROTECTIVE EQUIPMENT:

- Protective gloves.
- Protective footwear.
- Eyewash bottle with clean water.

EMERGENCY RESPONSE / INTERVENTION EQUIPMENT:

- Shovel.
- Broom.
- Sand or other absorbent.
- Alternatively, appropriate spill kit.

SECTION 5. DRIVER FIRST ACTIONS / DRIVER SPECIAL / ADDITIONAL ACTIONS

DRIVER FIRST ACTIONS

- Stop the engine.
- No Naked lights. No smoking.
- Mark the roads with self-standing warning signs and warn other road users or passers-by.
- Keep public away from the danger area. Keep upwind.
- Notify police and fire brigade as soon as possible.

DRIVER SPECIAL /ADITIONAL ACTIONS

- Any action / Spill containment only if without personal risk.
- Stop leaks without risk.
- Contain or absorb leaking liquid with sand or other suitable material.
- Avoid direct contact with substance.
- Vapour may create explosive atmosphere.
- Avoid making sparks.
- Prevent liquids entering water courses, sewers, basements and work pits.
- If substances have entered a water course or sewer or been spilt on soil or vegetation, inform the police.
- Warn everybody: Explosion hazard.

UN NO	1263
Class/Division	3
Subsidiary risk	
Packaging Group	II
ERG No	.

SECTION 6. DRIVER ACTION IN CASE OF FIRE

Do not attempt to deal with any fire involving the load.

SECTION 7. FIRST AID

- If substance has got into the eyes, immediately wash out with plenty of water. Continue treatment until medical assistance is provided.
- Remove contaminated clothing immediately and wash affected skin with soap and water.
- Seek medical treatment when anyone has symptoms apparently due to inhalation, swallowing or contact with skin or eyes.
- Persons who have inhaled the fumes produced in a fire may not show immediate symptoms.
- In case of burns immediately cool affected skin as long as possible with cold water.

SECTION 8. SPECIAL INFORMATION FOR EMERGENCY SERVICES

- Keep container(s) cool by spraying with water if exposed to fire.
- Extinguishing with water spray or preferably with foam or dry chemical.
- Do not use water jet.
- Sewers must be covered and basements and work pits evacuated.
- Use low-sparking hand tools and explosion-proof electrical equipment.

SECTION 9. ADDITIONAL INFORMATION

CONTACT REFERENCE:

DURA PAINTS (PTY) LTD

EMERGENCY TELEPHONE NUMBERS:

+27 (11) 452-5221

SECTION 10. SUBSTANCE / BRAND NAME

LACQUER THINNERS

SECTION 11. PREPARED BY

Prepared by Dura Paints (PTY) Ltd from the best knowledge available; no guarantee is provided that the information is sufficient or correct under all circumstances

PREPERATION DATE:
01/09/2020

EXPIRY DATE
01/09/2023

REFERENCE
DURA PAINTS (PTY) LTD

NOTES
MSDS – DI004

END OF TRANSPORT EMERGENCY CARD