

# Dura - Anchorbond colours containing PR104 Scarlet Chrome and/or PY34 Lemon/Middle Chrome

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8  
Issue date: 2/16/2023 Revision date: 2/16/2023 Supersedes: 2/16/2023 Version: 1.1

### SECTION 1: Identification of the substance/mixture and of the supplier/undertaking

#### 1.1. GHS product identifier

Product form	: Mixture
Trade name	: Dura - Anchorbond colours containing PR104 Scarlet Chrome and/or PY34 Lemon/Middle Chrome
Type of product	: Coatings
Product code	: ANCHORBOND
Product group	: Trade product

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended uses and restrictions : Light industrial coating applications

#### 1.4. Supplier's details

##### Manufacturer

Dura Paints (Pty) Ltd.  
5 Wakefield Road; Founders View South.  
P.O. Box 303  
1610 Edenvale; Johannesburg – South Africa  
T 011 452 5221  
Contact: Lizel Rosemann

#### 1.5. Emergency phone number

Emergency number : 079 494 2731 / 011 452 5221

### SECTION 2: Hazard identification

#### 2.1. GHS classification of the substance/mixture and any national or regional information

##### Classification according to the United Nations GHS

Flammable liquids, Category 2	H225
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Skin sensitisation, Category 1	H317
Germ cell mutagenicity, Category 1B	H340
Carcinogenicity, Category 1A	H350
Reproductive toxicity, Category 2	H361
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity – Repeated exposure, Category 2	H373
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Acute Hazard, Category 2	H401
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects : Highly flammable liquid and vapour,May cause cancer,May cause genetic defects,Suspected of damaging fertility or the unborn child,May cause damage to organs through prolonged or repeated exposure,May cause drowsiness or dizziness,Harmful if inhaled,Causes skin irritation,May cause an allergic skin reaction,May be fatal if swallowed and enters airways,Toxic to aquatic life,Toxic to aquatic life with long lasting effects.

# Dura - Anchorbond colours containing PR104 Scarlet Chrome and/or PY34 Lemon/Middle Chrome

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

### 2.2. GHS label elements, including precautionary statements

#### Labelling according to the United Nations GHS

Hazard pictograms (GHS ZA) :



Signal word (GHS-ZA) : Danger

Hazardous ingredients : Solvent naphtha (petroleum), light arom.; (Z)-octadec-9-en-1-aminium salts of tall-oil fatty acids; Fatty acids, C18-unsatd., trimers, compds. with oleylamine; hexane; Solvent naphtha (petroleum), light aliph.; benzene; Toluene; Lead sulphochromate yellow; Lead chromate molybdate sulfate red/scarlet

Hazard statements (GHS ZA) :

- H225 - Highly flammable liquid and vapour
- H304 - May be fatal if swallowed and enters airways
- H315 - Causes skin irritation
- H317 - May cause an allergic skin reaction
- H332 - Harmful if inhaled
- H336 - May cause drowsiness or dizziness
- H340 - May cause genetic defects (Dermal, Inhalation)
- H350 - May cause cancer (Dermal, Inhalation)
- H361 - Suspected of damaging the unborn child. (Dermal, Inhalation)
- H373 - May cause damage to organs (central nervous system, Skin) through prolonged or repeated exposure (Dermal, Inhalation)
- H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS ZA) :

- P102 - Keep out of reach of children.
- P103 - Read carefully and follow all instructions.
- P261 - Avoid breathing mist, spray.
- P273 - Avoid release to the environment.
- P314 - Get medical advice/attention if you feel unwell
- P331 - Do NOT induce vomiting.
- P501 - Dispose of container to Recycling.

### 2.3. Other hazards which do not result in classification or are not covered by the GHS

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification according to the United Nations GHS
Xylene	CAS-No.: 1330-20-7	12 – 33.019	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. Not classified (Inhalation:dust,mist) Skin Irrit. 2, H315 STOT RE Not classified Aquatic Chronic Not classified
Solvent naphtha (petroleum), light aliph.	CAS-No.: 64742-89-8	15.75 – 29.3	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304

# Dura - Anchorbond colours containing PR104 Scarlet Chrome and/or PY34 Lemon/Middle Chrome

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

Name	Product identifier	%	Classification according to the United Nations GHS
Toluene	CAS-No.: 108-88-3	9 – 28	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	-	7.5 – 13.3	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 4, H413
Lead sulphochromate yellow	CAS-No.: 1344-37-2	0.1 – 12	Acute Tox. Not classified (Oral) Carc. 1B, H350 STOT RE 2, H373 Aquatic Acute Not classified Aquatic Chronic 1, H410
Lead chromate molybdate sulfate red/scarlet	CAS-No.: 12656-85-8	0.1 – 12	Carc. 1B, H350 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS-No.: 64742-48-9	7.5 – 11.4	Flam. Liq. 3, H226 Asp. Tox. 1, H304
hexane	CAS-No.: 110-54-3	2.55 – 5.9	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
benzene	CAS-No.: 71-43-2	0.03 – 0.4	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Muta. 1B, H340 Carc. 1A, H350 STOT RE 1, H372 Asp. Tox. 1, H304
Solvent naphtha (petroleum), light arom.	CAS-No.: 64742-95-6	0.06 – 0.25	Flam. Liq. 3, H226 Muta. 1B, H340 Carc. 1B, H350 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Fatty acids, C18-unsatd., trimers, compds. with oleylamine	CAS-No.: 147900-93-4	0.06 – 0.25	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317 STOT RE 2, H373 Aquatic Chronic 2, H411
(Z)-octadec-9-en-1-aminium salts of tall-oil fatty acids	CAS-No.: 85711-55-3	0.04 – 0.125	Eye Dam. 1, H318 Skin Sens. 1A, H317 STOT RE 2, H373

# Dura - Anchorbond colours containing PR104 Scarlet Chrome and/or PY34 Lemon/Middle Chrome

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

### SECTION 4: First aid measures

#### 4.1. Description of necessary first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.

#### 4.2. Most important symptoms/effect, acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after ingestion	: Risk of lung oedema.

#### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

#### 5.3. Special protective actions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures	: No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapours/spray.
----------------------	---

##### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

#### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

#### 6.3. Methods and materials for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

# Dura - Anchorbond colours containing PR104 Scarlet Chrome and/or PY34 Lemon/Middle Chrome

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
Hygiene measures	: Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Xylene (1330-20-7)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Xylene, o-, m-, p- or mixed isomers
OEL eight hour TWA [ppm]	300 ppm
RHCA - STEL/C [ppm]	200 ppm
Remark	SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Xylene, o-, m-, p- or mixed isomers
OEL TWA	218 mg/m <sup>3</sup>
OEL TWA [ppm]	50 ppm
OEL STEL	435 mg/m <sup>3</sup>
OEL STEL [ppm]	100 ppm
Remark	Sk (Danger of cutaneous absorption)
Regulatory reference	Government Notice No. R 904
South Africa - Biological limit values	
Local name	Xylenes
BEI	1.5 g/g creatinine Parameter: Methylhippuric acids - Medium: urine - Sampling time: End of shift
Regulatory reference	Government Notice No. R. 280, 2021

# Dura - Anchorbond colours containing PR104 Scarlet Chrome and/or PY34 Lemon/Middle Chrome

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

<b>hexane (110-54-3)</b>	
<b>South Africa - Occupational Exposure Limits (Restricted Limits)</b>	
Local name	n-Hexane
RHCA - STEL/C [ppm]	100 ppm
Remark	SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021
<b>South Africa - Occupational Exposure Limits (Airborne Pollutants)</b>	
Local name	n-Hexane
OEL TWA	70 mg/m <sup>3</sup>
OEL TWA [ppm]	20 ppm
Regulatory reference	Government Notice No. R 904
<b>South Africa - Biological limit values</b>	
Local name	n-Hexane
BEI	0.4 mg/l Parameter: 2,5-Hexanedione - Medium: urine - Sampling time: End of shift at end of workweek
Regulatory reference	Government Notice No. R. 280, 2021
<b>benzene (71-43-2)</b>	
<b>South Africa - Occupational Exposure Limits (Airborne Pollutants)</b>	
Local name	Benzene
OEL TWA	3 mg/m <sup>3</sup>
OEL TWA [ppm]	1 ppm
Regulatory reference	Government Notice No. R 904
<b>Toluene (108-88-3)</b>	
<b>South Africa - Occupational Exposure Limits (Restricted Limits)</b>	
Local name	Toluene
OEL eight hour TWA [ppm]	150 ppm
OEL eight hour TWA	560 mg/m <sup>3</sup>
RHCA - STEL/C [ppm]	40 ppm 50 ppm
RHCA - STEL/C	188 mg/m <sup>3</sup>
Remark	SKIN (danger of cutaneous absorption) Sk
Regulatory reference	Government Notice No. R. 280, 2021 Government Notice. R: 1179
<b>South Africa - Occupational Exposure Limits (Airborne Pollutants)</b>	
Local name	Toluene
OEL TWA	188 mg/m <sup>3</sup>
OEL TWA [ppm]	50 ppm
OEL STEL	560 mg/m <sup>3</sup>
OEL STEL [ppm]	150 ppm
Remark	Sk (Danger of cutaneous absorption)

# Dura - Anchorbond colours containing PR104 Scarlet Chrome and/or PY34 Lemon/Middle Chrome

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

Toluene (108-88-3)	
Regulatory reference	Government Notice No. R 904
South Africa - Biological limit values	
Local name	Toluene
BEI	0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: Prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: End of shift 0.3 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: End of shift - Notations: B (background)
Regulatory reference	Government Notice No. R. 280, 2021

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment

Hand protection : Protective gloves  
Eye protection : Safety glasses  
Skin and body protection : Wear suitable protective clothing  
Respiratory protection : [In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s)



### 8.4. Exposure limit values for the other components

No additional information available

## SECTION 9: Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state : Liquid  
Appearance : Viscous liquid.  
Colour : Colourless to yellow liquid.  
Odour : Pungent.  
Odour threshold : No data available  
pH : No data available  
pH solution : No data available  
Relative evaporation rate (butylacetate=1) : No data available  
Relative evaporation rate (ether=1) : No data available  
Melting point : Not applicable  
Freezing point : No data available  
Boiling point : > 35 °C  
Flash point : < 23 °C  
Auto-ignition temperature : No data available  
Decomposition temperature : No data available  
Flammability : Highly flammable liquid and vapour.  
Vapour pressure : No data available  
Vapour pressure at 50°C : No data available  
Relative vapour density at 20°C : No data available  
Relative density : No data available  
Relative density of saturated gas/air mixture : No data available  
Density : No data available

# Dura - Anchorbond colours containing PR104 Scarlet Chrome and/or PY34 Lemon/Middle Chrome

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

Relative gas density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: < 7.5 mm <sup>2</sup> /s
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Physical state	: Liquid
Appearance	: Viscous liquid.

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10: Stability and Reactivity

### 10.1. Reactivity

Highly flammable liquid and vapour.

### 10.2. Chemical Stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Harmful if inhaled.

Dura - Anchorbond colours containing PR104 Scarlet Chrome and/or PY34 Lemon/Middle Chrome	
ATE ZA (dust, mist)	4.543 mg/l/4h
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	≥ 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)



# Dura - Anchorbond colours containing PR104 Scarlet Chrome and/or PY34 Lemon/Middle Chrome

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

<b>Hydrocarbons, C11-C12, isoalkanes, &lt;2% aromatics</b>	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	≥ 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
<b>Xylene (1330-20-7)</b>	
LD50 oral rat	≈ 3523 mg/kg bodyweight
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male, Remarks on results: other:
LC50 Inhalation - Rat	≈ 27.124 mg/l Source: ECHA
<b>Solvent naphtha (petroleum), light arom. (64742-95-6)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
<b>(Z)-octadec-9-en-1-aminium salts of tall-oil fatty acids (85711-55-3)</b>	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), Guideline: EU Method B.1 tris (Acute Oral Toxicity - Acute Toxic Class Method), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity), Guideline: other., Remarks on results: other:
<b>Solvent naphtha (petroleum), light aliph. (64742-89-8)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	≈ 5.61 mg/l Source: ECHA
<b>Toluene (108-88-3)</b>	
LD50 oral rat	5580 mg/kg Source: ECHA
LD50 dermal rabbit	> 5000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	> 20 mg/l Source: ECHA
<b>Lead sulphochromate yellow (1344-37-2)</b>	
LD50 oral rat	> 10000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Remarks on results: other:
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: May cause genetic defects (Dermal, Inhalation).
Carcinogenicity	: May cause cancer (Dermal, Inhalation).
Reproductive toxicity	: Suspected of damaging the unborn child. (Dermal, Inhalation).
STOT-single exposure	: May cause drowsiness or dizziness.
<b>Solvent naphtha (petroleum), light arom. (64742-95-6)</b>	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
<b>hexane (110-54-3)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>Toluene (108-88-3)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs (central nervous system, Skin) through prolonged or repeated exposure (Dermal, Inhalation).

# Dura - Anchorbond colours containing PR104 Scarlet Chrome and/or PY34 Lemon/Middle Chrome

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

<b>Xylene (1330-20-7)</b>	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
<b>(Z)-octadec-9-en-1-aminium salts of tall-oil fatty acids (85711-55-3)</b>	
NOAEL (oral, rat, 90 days)	7.1 – 21.9 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
<b>Fatty acids, C18-unsatd., trimers, compds. with oleylamine (147900-93-4)</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
<b>hexane (110-54-3)</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
<b>Solvent naphtha (petroleum), light aliph. (64742-89-8)</b>	
LOAEC (inhalation, rat, vapour, 90 days)	≈ 1.402 mg/l
NOAEC (inhalation, rat, gas, 90 days)	≈ 1402 mg/l Specimen: Rat - Source: ECHA
<b>benzene (71-43-2)</b>	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
<b>Toluene (108-88-3)</b>	
LOAEL (oral, rat, 90 days)	≈ 1250 mg/kg bodyweight/day Source: ECHA
LOAEC (inhalation, rat, gas, 90 days)	≈ 2.261 mg/l Source: ECHA
NOAEL (oral, rat, 90 days)	≈ 625 mg/kg bodyweight/day Rat
NOAEC (inhalation, rat, gas, 90 days)	1.131 – 2.355 mg/l Air, Source: ECHA
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
<b>Lead sulphochromate yellow (1344-37-2)</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
<b>Lead chromate molybdate sulfate red/scarlet (12656-85-8)</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
<b>Dura - Anchorbond colours containing PR104 Scarlet Chrome and/or PY34 Lemon/Middle Chrome</b>	
Viscosity, kinematic	< 7.5 mm <sup>2</sup> /s

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: Toxic to aquatic life. Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

<b>Hydrocarbons, C11-C12, isoalkanes, &lt;2% aromatics</b>	
NOEC (chronic)	0.011 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

# Dura - Anchorbond colours containing PR104 Scarlet Chrome and/or PY34 Lemon/Middle Chrome

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

<b>Xylene (1330-20-7)</b>	
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

<b>(Z)-octadec-9-en-1-aminium salts of tall-oil fatty acids (85711-55-3)</b>	
LOEC (chronic)	4.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

<b>Solvent naphtha (petroleum), light aliph. (64742-89-8)</b>	
EC50 - Crustacea [1]	≈ 4.5 mg/l EL50 value Source: ECHA
NOEC chronic fish	≈ 2.6 mg/l

<b>Toluene (108-88-3)</b>	
LC50 - Fish [1]	5.5 mg/l Source: ECHA
EC50 - Crustacea [1]	3.78 mg/l Source: ECHA
NOEC chronic crustacea	≈ 0.74 mg/l Source: ECHA

<b>Lead sulphochromate yellow (1344-37-2)</b>	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	0.7 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

### 12.2. Persistence and degradability

<b>Dura - Anchorbond colours containing PR104 Scarlet Chrome and/or PY34 Lemon/Middle Chrome</b>	
Persistence and degradability	No additional information available

### 12.3. Bioaccumulative potential

<b>Dura - Anchorbond colours containing PR104 Scarlet Chrome and/or PY34 Lemon/Middle Chrome</b>	
Bioaccumulative potential	No additional information available

<b>hexane (110-54-3)</b>	
Partition coefficient n-octanol/water (Log Kow)	≈ 4 20 °C and pH 7 - Source: ECHA

<b>benzene (71-43-2)</b>	
Partition coefficient n-octanol/water (Log Kow)	≈ 2.13 Temperature: 20°C Source: ECHA

<b>Toluene (108-88-3)</b>	
Partition coefficient n-octanol/water (Log Kow)	2.73 Source: HSDB

### 12.4. Mobility in soil

<b>Dura - Anchorbond colours containing PR104 Scarlet Chrome and/or PY34 Lemon/Middle Chrome</b>	
Mobility in soil	No additional information available

### 12.5. Other adverse effects

Ozone : Not classified

# Dura - Anchorbond colours containing PR104 Scarlet Chrome and/or PY34 Lemon/Middle Chrome

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

Other adverse effects : No additional information available




### SECTION 13: Disposal Considerations

#### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Additional information : Flammable vapours may accumulate in the container.

### SECTION 14: Transport information

In accordance with SANS / IMDG / IATA

SANS	IMDG	IATA
<b>14.1. UN number</b>		
1307	1307	1307
<b>14.2. UN Proper Shipping Name</b>		
XYLENES	XYLENES	Xylenes
<b>14.3. Transport hazard class(es)</b>		
3	3	3
		
<b>14.4. Packing group, if applicable</b>		
III	III	III
<b>14.5. Environmental hazards</b>		
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes
No supplementary information available		

#### 14.6. Special precautions for user

##### SANS

Special provisions (SANS) : 223  
Limited quantities (SANS) : 5 L  
Limited quantities (SANS) : 5 L  
Packagings, large packagings and IBCs Packing instructions (SANS) : P001, IBC03, LP01  
Portable tank and bulk containers instructions (SANS) : T2  
Portable tank and bulk container special provisions (SANS) : TP1

##### IMDG

Special provisions (IMDG) : 223  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E1  
Packing instructions (IMDG) : P001, LP01  
IBC packing instructions (IMDG) : IBC03  
Tank instructions (IMDG) : T2  
Tank special provisions (IMDG) : TP1  
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS

# Dura - Anchorbond colours containing PR104 Scarlet Chrome and/or PY34 Lemon/Middle Chrome

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS  
Stowage category (IMDG) : A  
Flash point (IMDG) : 23°C to 30°C c.c.  
Properties and observations (IMDG) : Colourless liquids. Flashpoint: 23°C to 30°C c.c. Explosive limits: 1.1% to 7% Immiscible with water.

### IATA

PCA Excepted quantities (IATA) : E1  
PCA Limited quantities (IATA) : Y344  
PCA limited quantity max net quantity (IATA) : 10L  
PCA packing instructions (IATA) : 355  
PCA max net quantity (IATA) : 60L  
CAO packing instructions (IATA) : 366  
CAO max net quantity (IATA) : 220L  
Special provisions (IATA) : A3  
ERG code (IATA) : 3L

### 14.7. Transport in bulk according to IMO instructions

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

## SECTION 16: Other information

Issue date : 16/02/2023  
Revision date : 16/02/2023  
Supersedes : 16/02/2023

### Full text of H-statements:

H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure

# Dura - Anchorbond colours containing PR104 Scarlet Chrome and/or PY34 Lemon/Middle Chrome

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

Full text of H-statements:	
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life

Safety Data Sheet (SDS), South Africa (HCA)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.