

### SECTION 1: Identification of the substance/mixture and of the supplier/undertaking

#### 1.1. GHS product identifier

Product form	: Mixture
Trade name	: Dura - 2K Enamel - White
Type of product	: Coatings
Product code	: 2KWHITE
Product group	: Trade product

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Light industrial coating applications

#### 1.4. Supplier's details

##### Manufacturer

Dura Paints (Pty) Ltd.  
5 Wakefield Road; Founders View South.  
P.O. Box 303  
1610 Edenvale; Johannesburg – South Africa  
T 011 452 5221  
Contact: Lizel Rosemann

#### 1.5. Emergency phone number

Emergency number : 079 494 2731 / 011 452 5221

### SECTION 2: Hazard identification

#### 2.1. GHS classification of the substance/mixture and any national or regional information

##### Classification according to the United Nations GHS

Flammable liquids, Category 2	H225
Acute toxicity (dermal), Category 4	H312
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Carcinogenicity, Category 1B	H350
Specific target organ toxicity – Repeated exposure, Category 2	H373
Hazardous to the aquatic environment – Acute Hazard, Category 2	H401

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects : Highly flammable liquid and vapour,May cause cancer,May cause damage to organs through prolonged or repeated exposure,Harmful in contact with skin,Harmful if inhaled,Causes skin irritation,Causes serious eye irritation,Toxic to aquatic life

#### 2.2. GHS label elements, including precautionary statements

##### Labelling according to the United Nations GHS

Hazard pictograms (GHS ZA) :



Signal word (GHS-ZA) : Danger

Hazardous ingredients : 2-butoxyethanol; Xylene; Cumene; ethylbenzene; 4-methylpentan-2-one

# Dura - 2K Enamel - White

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

Hazard statements (GHS ZA)	: H225 - Highly flammable liquid and vapour H312+H332 - Harmful in contact with skin or if inhaled H315 - Causes skin irritation H319 - Causes serious eye irritation H350 - May cause cancer (Inhalation) H373 - May cause damage to organs (hearing organs) through prolonged or repeated exposure (Inhalation) H401 - Toxic to aquatic life
Precautionary statements (GHS ZA)	: P102 - Keep out of reach of children. P103 - Read carefully and follow all instructions. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P242 - Use non-sparking tools. P261 - Avoid breathing dust, mist, spray, vapours. P273 - Avoid release to the environment. P280 - Wear eye protection, protective clothing, protective gloves. P319 - Get medical help if you feel unwell. P501 - Dispose of container to recycling.

### 2.3. Other hazards which do not result in classification or are not covered by the GHS

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification according to the United Nations GHS
Xylene	CAS-No.: 1330-20-7	23.337 – 55.311	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. Not classified (Inhalation:dust,mist) Skin Irrit. 2, H315 STOT RE Not classified Aquatic Chronic Not classified
Titanium dioxide	CAS-No.: 13463-67-7	15 – 22	Acute Tox. Not classified (Inhalation:dust,mist) Carc. 2, H351
1,3,5-trimethylbenzene; 1-ethyl-4-methylbenzene; prop-1-en-2-ylbenzene; propan-2-ylbenzene; propylbenzene	CAS-No.: 128601-23-0	1 – 8	Flam. Liq. 3, H226 Acute Tox. 3 (Inhalation:vapour), H331 STOT RE Not classified Aquatic Acute 1, H400
4-methylpentan-2-one	CAS-No.: 108-10-1	0.995 – 7.96	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H336
2-butoxyethanol	CAS-No.: 111-76-2	0.9 – 3	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319

# Dura - 2K Enamel - White

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

Name	Product identifier	%	Classification according to the United Nations GHS
ethylbenzene	CAS-No.: 100-41-4	0.11 – 1.633	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapour), H332 STOT RE 2, H373 Asp. Tox. 1, H304
Cumene	CAS-No.: 98-82-8	0.001 – 0.16	Flam. Liq. 3, H226 Carc. 1B, H350 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412

### SECTION 4: First aid measures

#### 4.1. Description of necessary first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

#### 4.2. Most important symptoms/effect, acute and delayed

Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.

#### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

#### 5.3. Special protective actions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures	: No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapours/spray.
----------------------	---

# Dura - 2K Enamel - White

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and materials for containment and cleaning up

For containment : Collect spillage.  
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing.  
Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.  
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

2-butoxyethanol (111-76-2)	
<b>South Africa - Occupational Exposure Limits (Maximum Limits)</b>	
Local name	2-Butoxyethanol [EGBE]
RHCA - STEL/C [ppm]	40 ppm
Regulatory reference	Government Notice No. R. 280, 2021
<b>South Africa - Occupational Exposure Limits (Airborne Pollutants)</b>	
Local name	2-Butoxyethanol (Ethylene glycol monobutyl ether [EGBE])
OEL TWA	120 mg/m <sup>3</sup>
OEL TWA [ppm]	25 ppm
Remark	Sk (Danger of cutaneous absorption)
Regulatory reference	Government Notice No. R 904
<b>South Africa - Biological limit values</b>	
Local name	2-Butoxyethanol

# Dura - 2K Enamel - White

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

<b>2-butoxyethanol (111-76-2)</b>	
BEI	200 mg/g creatinine Parameter: Butoxyacetic acid (BAA) - Medium: urine - Sampling time: End of shift
Regulatory reference	Government Notice No. R. 280, 2021
<b>Xylene (1330-20-7)</b>	
<b>South Africa - Occupational Exposure Limits (Restricted Limits)</b>	
Local name	Xylene, o-, m-, p- or mixed isomers
OEL eight hour TWA [ppm]	300 ppm
RHCA - STEL/C [ppm]	200 ppm
Remark	SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021
<b>South Africa - Occupational Exposure Limits (Airborne Pollutants)</b>	
Local name	Xylene, o-, m-, p- or mixed isomers
OEL TWA	218 mg/m <sup>3</sup>
OEL TWA [ppm]	50 ppm
OEL STEL	435 mg/m <sup>3</sup>
OEL STEL [ppm]	100 ppm
Remark	Sk (Danger of cutaneous absorption)
Regulatory reference	Government Notice No. R 904
<b>South Africa - Biological limit values</b>	
Local name	Xylenes
BEI	1.5 g/g creatinine Parameter: Methylhippuric acids - Medium: urine - Sampling time: End of shift
Regulatory reference	Government Notice No. R. 280, 2021
<b>Titanium dioxide (13463-67-7)</b>	
<b>South Africa - Occupational Exposure Limits (Restricted Limits)</b>	
Local name	Titanium dioxide
RHCA - STEL/C	10 mg/m <sup>3</sup> 10 mg/m <sup>3</sup> total inhalable dust 5 mg/m <sup>3</sup> respirable dust
Remark	CARC (denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B)
Regulatory reference	Government Notice No. R. 280, 2021 Government Notice. R: 1179
<b>South Africa - Occupational Exposure Limits (Airborne Pollutants)</b>	
Local name	Titanium dioxide
OEL TWA	10 mg/m <sup>3</sup> inhalable particulate 5 mg/m <sup>3</sup> respirable particulate
Regulatory reference	Government Notice No. R 904
<b>ethylbenzene (100-41-4)</b>	
<b>South Africa - Occupational Exposure Limits (Restricted Limits)</b>	
Local name	Ethyl benzene
RHCA - STEL/C [ppm]	40 ppm

# Dura - 2K Enamel - White

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

ethylbenzene (100-41-4)	
Remark	CARC (denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B), SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Ethyl benzene
OEL TWA	435 mg/m <sup>3</sup>
OEL TWA [ppm]	100 ppm
OEL STEL	545 mg/m <sup>3</sup>
OEL STEL [ppm]	125 ppm
Regulatory reference	Government Notice No. R 904
South Africa - Biological limit values	
Local name	Ethyl benzene
BEI	0.15 g/g creatinine Parameter: Sum of mandelic acid and phenylglyoxylic acid - Medium: urine - Sampling time: End of shift - Notations: Ns (non-specific)
Regulatory reference	Government Notice No. R. 280, 2021

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment

Hand protection : Protective gloves  
Eye protection : Safety glasses  
Skin and body protection : Wear suitable protective clothing  
Respiratory protection : [In case of inadequate ventilation] wear respiratory protection.  
Personal protective equipment symbol(s)



### 8.4. Exposure limit values for the other components

No additional information available

## SECTION 9: Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state : Liquid  
Appearance : Liquid.  
Colour : White.  
Odour : Aromatic solvent like odour.  
Odour threshold : No data available  
pH : No data available  
pH solution : No data available  
Relative evaporation rate (butylacetate=1) : No data available  
Relative evaporation rate (ether=1) : No data available  
Melting point : Not applicable  
Freezing point : No data available  
Boiling point : No data available  
Flash point : No data available

# Dura - 2K Enamel - White

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability	: Highly flammable liquid and vapour.
Vapour pressure	: No data available
Vapour pressure at 50°C	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: ≈ 1
Relative density of saturated gas/air mixture	: No data available
Density	: No data available
Relative gas density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: > 300 – < 550 cP
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Physical state	: Liquid
Appearance	: Liquid.

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10: Stability and Reactivity

### 10.1. Reactivity

Highly flammable liquid and vapour.

### 10.2. Chemical Stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Harmful in contact with skin.
Acute toxicity (inhalation)	: Harmful if inhaled.

Dura - 2K Enamel - White	
ATE ZA (Dermal)	1886.437 mg/kg bodyweight
ATE ZA (dust, mist)	2.371 mg/l/4h

# Dura - 2K Enamel - White

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

<b>2-butoxyethanol (111-76-2)</b>	
LD50 oral	1414 mg/kg bodyweight Animal: guinea pig, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1020 - 1961
<b>Xylene (1330-20-7)</b>	
LD50 oral rat	≈ 3523 mg/kg bodyweight
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male, Remarks on results: other:
LC50 Inhalation - Rat	≈ 27.124 mg/l Source: ECHA
<b>Titanium dioxide (13463-67-7)</b>	
LC50 Inhalation - Rat (Dust/Mist)	> 6.82 mg/l Source: ECHA
<b>1,3,5-trimethylbenzene; 1-ethyl-4-methylbenzene; prop-1-en-2-ylbenzene; propan-2-ylbenzene; propylbenzene (128601-23-0)</b>	
LD50 dermal rabbit	> 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal	≥
LC50 Inhalation - Rat	> 6.193 mg/l/4h Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
<b>Cumene (98-82-8)</b>	
LD50 dermal rabbit	> 3160 mg/kg bodyweight Animal: rabbit
<b>ethylbenzene (100-41-4)</b>	
LD50 oral rat	≈ 3500 mg/kg bodyweight Animal: rat
<b>4-methylpentan-2-one (108-10-1)</b>	
LD50 oral rat	≈ 4570 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer (Inhalation).
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
<b>Cumene (98-82-8)</b>	
STOT-single exposure	May cause respiratory irritation.
<b>4-methylpentan-2-one (108-10-1)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs (hearing organs) through prolonged or repeated exposure (Inhalation).
<b>2-butoxyethanol (111-76-2)</b>	
NOAEL (dermal, rat/rabbit, 90 days)	> 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study), Remarks on results: other:
<b>Xylene (1330-20-7)</b>	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)



# Dura - 2K Enamel - White

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

<b>1,3,5-trimethylbenzene; 1-ethyl-4-methylbenzene; prop-1-en-2-ylbenzene; propan-2-ylbenzene; propylbenzene (128601-23-0)</b>	
NOAEL (oral, rat, 90 days)	600 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
<b>ethylbenzene (100-41-4)</b>	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
<b>4-methylpentan-2-one (108-10-1)</b>	
LOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	4.106 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

Aspiration hazard : Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Toxic to aquatic life.  
Hazardous to the aquatic environment, short-term (acute) : Toxic to aquatic life.  
Hazardous to the aquatic environment, long-term (chronic) : Not classified

<b>2-butoxyethanol (111-76-2)</b>	
LC50 - Fish [1]	1474 mg/l Test organisms (species): <i>Oncorhynchus mykiss</i> (previous name: <i>Salmo gairdneri</i> )
EC50 - Crustacea [1]	≈ 1800 mg/l Test organisms (species): <i>Daphnia magna</i>
NOEC (chronic)	100 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d'
NOEC chronic fish	≥ 100 mg/l Test organisms (species): <i>Oryzias latipes</i> Duration: '14 d'

<b>Xylene (1330-20-7)</b>	
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): <i>Ceriodaphnia dubia</i>
LOEC (chronic)	3.16 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): <i>Oncorhynchus mykiss</i> (previous name: <i>Salmo gairdneri</i> ) Duration: '56 d'

<b>Titanium dioxide (13463-67-7)</b>	
LOEC (acute)	≈ 160 mg/l Fish, 4 Days; Source: ECHA
LOEC (chronic)	≈ 5 mg/l Crustacea, 21 Days; Source: ECHA
NOEC (acute)	0.004 – 0.08 mg/l 28 Dday, fish; Source: Echa

<b>1,3,5-trimethylbenzene; 1-ethyl-4-methylbenzene; prop-1-en-2-ylbenzene; propan-2-ylbenzene; propylbenzene (128601-23-0)</b>	
EC50 72h - Algae [1]	0.42 mg/l Test organisms (species): <i>Raphidocelis subcapitata</i> (previous names: <i>Pseudokirchneriella subcapitata</i> , <i>Selenastrum capricornutum</i> )
EC50 72h - Algae [2]	0.29 mg/l Test organisms (species): <i>Raphidocelis subcapitata</i> (previous names: <i>Pseudokirchneriella subcapitata</i> , <i>Selenastrum capricornutum</i> )

# Dura - 2K Enamel - White

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

<b>Cumene (98-82-8)</b>	
LC50 - Fish [1]	4.7 mg/l Test organisms (species): <i>Cyprinodon variegatus</i>
LC50 - Fish [2]	4.8 mg/l Test organisms (species): <i>Oncorhynchus mykiss</i> (previous name: <i>Salmo gairdneri</i> )
EC50 - Crustacea [1]	2.14 mg/l Test organisms (species): <i>Daphnia magna</i>
EC50 72h - Algae [1]	2.01 mg/l Test organisms (species): <i>Desmodesmus subspicatus</i> (previous name: <i>Scenedesmus subspicatus</i> )
EC50 72h - Algae [2]	1.29 mg/l Test organisms (species): <i>Desmodesmus subspicatus</i> (previous name: <i>Scenedesmus subspicatus</i> )
NOEC (chronic)	0.35 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d'
NOEC chronic fish	0.38 mg/l Test organisms (species): other: Duration: '28 d'
<b>ethylbenzene (100-41-4)</b>	
LC50 - Fish [1]	5.1 mg/l Test organisms (species): <i>Menidia menidia</i>
EC50 72h - Algae [1]	5.4 mg/l Test organisms (species): <i>Pseudokirchneriella subcapitata</i> (previous names: <i>Raphidocelis subcapitata</i> , <i>Selenastrum capricornutum</i> )
EC50 72h - Algae [2]	4.9 mg/l Test organisms (species): <i>Skeletonema costatum</i>
EC50 96h - Algae [1]	3.6 mg/l Test organisms (species): <i>Pseudokirchneriella subcapitata</i> (previous names: <i>Raphidocelis subcapitata</i> , <i>Selenastrum capricornutum</i> )
EC50 96h - Algae [2]	7.7 mg/l Test organisms (species): <i>Skeletonema costatum</i>
LOEC (chronic)	1.7 mg/l Test organisms (species): <i>Ceriodaphnia dubia</i> Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): <i>Ceriodaphnia dubia</i> Duration: '7 d'
<b>4-methylpentan-2-one (108-10-1)</b>	
LC50 - Fish [1]	> 179 mg/l Test organisms (species): <i>Danio rerio</i> (previous name: <i>Brachydanio rerio</i> )
EC50 - Crustacea [1]	> 200 mg/l Test organisms (species): <i>Daphnia magna</i>

### 12.2. Persistence and degradability

<b>Dura - 2K Enamel - White</b>	
Persistence and degradability	No additional information available

### 12.3. Bioaccumulative potential

<b>Dura - 2K Enamel - White</b>	
Bioaccumulative potential	No additional information available

### 12.4. Mobility in soil

<b>Dura - 2K Enamel - White</b>	
Mobility in soil	No additional information available

### 12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No additional information available

## SECTION 13: Disposal Considerations

### 13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
-------------------------	---

# Dura - 2K Enamel - White




## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

Additional information : Flammable vapours may accumulate in the container.

### SECTION 14: Transport information

In accordance with SANS / IMDG / IATA

SANS	IMDG	IATA
<b>14.1. UN number</b>		
1307	1307	1307
<b>14.2. UN Proper Shipping Name</b>		
XYLENES	XYLENES	Xylenes
<b>14.3. Transport hazard class(es)</b>		
3	3	3
		
<b>14.4. Packing group, if applicable</b>		
III	III	III
<b>14.5. Environmental hazards</b>		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available		

### 14.6. Special precautions for user

#### SANS

Special provisions (SANS) : 223  
Limited quantities (SANS) : 5 L  
Limited quantities (SANS) : 5 L  
Packagings, large packagings and IBCs Packing instructions (SANS) : P001, IBC03, LP01  
Portable tank and bulk containers instructions (SANS) : T2  
Portable tank and bulk container special provisions (SANS) : TP1

#### IMDG

Special provisions (IMDG) : 223  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E1  
Packing instructions (IMDG) : P001, LP01  
IBC packing instructions (IMDG) : IBC03  
Tank instructions (IMDG) : T2  
Tank special provisions (IMDG) : TP1  
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS  
EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS  
Stowage category (IMDG) : A  
Flash point (IMDG) : 23°C to 30°C c.c.  
Properties and observations (IMDG) : Colourless liquids. Flashpoint: 23°C to 30°C c.c. Explosive limits: 1.1% to 7% Immiscible with water.

#### IATA

PCA Excepted quantities (IATA) : E1  
PCA Limited quantities (IATA) : Y344  
PCA limited quantity max net quantity (IATA) : 10L

# Dura - 2K Enamel - White

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

### 14.7. Transport in bulk according to IMO instructions

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

## SECTION 16: Other information

Issue date : 11/07/2023

Full text of H-statements:	
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), South Africa (HCA)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.