

### SECTION 1: Identification of the substance/mixture and of the supplier/undertaking

#### 1.1. GHS product identifier

Product form : Mixture  
 Trade name : Dura - Epoxy Enamel - White  
 Type of product : Coatings  
 Product code : EPWH  
 Product group : Trade product

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Light industrial coating applications

#### 1.4. Supplier's details

##### Manufacturer

Dura Paints (Pty) Ltd.  
 5 Wakefield Road; Founders View South.  
 P.O. Box 303  
 1610 Edenvale; Johannesburg – South Africa  
 T 011 452 5221  
 Contact: Lizel Rosemann

#### 1.5. Emergency phone number

Emergency number : 079 494 2731 / 011 452 5221

### SECTION 2: Hazard identification

#### 2.1. GHS classification of the substance/mixture and any national or regional information

##### Classification according to the United Nations GHS

Flammable liquids, Category 2	H225
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Carcinogenicity, Category 2	H351
Specific target organ toxicity – Repeated exposure, Category 2	H373

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects : Highly flammable liquid and vapour, Suspected of causing cancer, May cause damage to organs through prolonged or repeated exposure, Harmful if inhaled, Causes skin irritation, Causes serious eye irritation.

#### 2.2. GHS label elements, including precautionary statements

##### Labelling according to the United Nations GHS

Hazard pictograms (GHS ZA) :



Signal word (GHS-ZA) : Danger  
 Hazardous ingredients : Titanium dioxide; Talc /Talc containing no asbestos fibers/; ethylbenzene  
 Hazard statements (GHS ZA) : H225 - Highly flammable liquid and vapour  
 H315 - Causes skin irritation

# Dura - Epoxy Enamel - White

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

Precautionary statements (GHS ZA)	H319 - Causes serious eye irritation H332 - Harmful if inhaled H351 - Suspected of causing cancer (Inhalation) H373 - May cause damage to organs (hearing organs, respiratory system) through prolonged or repeated exposure (Inhalation) : P102 - Keep out of reach of children. P103 - Read carefully and follow all instructions. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 - Avoid breathing dust, mist, spray, vapours. P280 - Wear eye protection, protective clothing, protective gloves. P319 - Get medical help if you feel unwell. P501 - Dispose of container to recycling.
-----------------------------------	---

### 2.3. Other hazards which do not result in classification or are not covered by the GHS

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification according to the United Nations GHS
Xylene	CAS-No.: 1330-20-7	17.963 – 32.472	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. Not classified (Inhalation:dust,mist) Skin Irrit. 2, H315 STOT RE Not classified Aquatic Chronic Not classified
Titanium dioxide	CAS-No.: 13463-67-7	6 – 12	Acute Tox. Not classified (Inhalation:dust,mist) Carc. 2, H351
Talc /Talc containing no asbestos fibers/	CAS-No.: 14807-96-6	6 – 12	Acute Tox. Not classified (Oral) Acute Tox. 4 (Inhalation:dust,mist), H332 STOT RE 2, H373 Aquatic Acute Not classified
Butanone	CAS-No.: 78-93-3	1.99 – 6.965	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 Aquatic Acute Not classified
ethylbenzene	CAS-No.: 100-41-4	0.99 – 3.266	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapour), H332 STOT RE 2, H373 Asp. Tox. 1, H304

# Dura - Epoxy Enamel - White

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

Name	Product identifier	%	Classification according to the United Nations GHS
n-Butyl alcohol	CAS-No.: 71-36-3	0.65 – 2.07	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336 STOT SE 3, H335 Aquatic Acute Not classified

### SECTION 4: First aid measures

#### 4.1. Description of necessary first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

#### 4.2. Most important symptoms/effect, acute and delayed

Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.

#### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

#### 5.3. Special protective actions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
----------------------	--

##### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

# Dura - Epoxy Enamel - White

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and materials for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Xylene (1330-20-7)	
<b>South Africa - Occupational Exposure Limits (Restricted Limits)</b>	
Local name	Xylene, o-, m-, p- or mixed isomers
OEL eight hour TWA [ppm]	300 ppm
RHCA - STEL/C [ppm]	200 ppm
Remark	SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021
<b>South Africa - Occupational Exposure Limits (Airborne Pollutants)</b>	
Local name	Xylene, o-, m-, p- or mixed isomers
OEL TWA	218 mg/m <sup>3</sup>
OEL TWA [ppm]	50 ppm
OEL STEL	435 mg/m <sup>3</sup>
OEL STEL [ppm]	100 ppm
Remark	Sk (Danger of cutaneous absorption)
Regulatory reference	Government Notice No. R 904
<b>South Africa - Biological limit values</b>	
Local name	Xylenes
BEI	1.5 g/g creatinine Parameter: Methylhippuric acids - Medium: urine - Sampling time: End of shift

# Dura - Epoxy Enamel - White

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

<b>Xylene (1330-20-7)</b>	
Regulatory reference	Government Notice No. R. 280, 2021
<b>Titanium dioxide (13463-67-7)</b>	
<b>South Africa - Occupational Exposure Limits (Restricted Limits)</b>	
Local name	Titanium dioxide
RHCA - STEL/C	10 mg/m <sup>3</sup> 10 mg/m <sup>3</sup> total inhalable dust 5 mg/m <sup>3</sup> respirable dust
Remark	CARC (denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B)
Regulatory reference	Government Notice No. R. 280, 2021 Government Notice. R: 1179
<b>South Africa - Occupational Exposure Limits (Airborne Pollutants)</b>	
Local name	Titanium dioxide
OEL TWA	10 mg/m <sup>3</sup> inhalable particulate 5 mg/m <sup>3</sup> respirable particulate
Regulatory reference	Government Notice No. R 904
<b>Talc /Talc containing no asbestos fibers/ (14807-96-6)</b>	
<b>South Africa - Occupational Exposure Limits (Maximum Limits)</b>	
Local name	Talc (containing asbestos fibres)
RHCA - OEL [ppm]	0.6 fibers/mL (measured over a continuous 10-minute period)
RHCA - STEL/C [ppm]	0.1 fibers/mL
Remark	CARC (denotes carcinogenicity, which is based on GHS categorisation, including category 1A and 1B)
Regulatory reference	Government Notice No. R. 280, 2021; Government Notice No. R. 11196, 2020
<b>South Africa - Occupational Exposure Limits (Restricted Limits)</b>	
Local name	Talc (containing no asbestos fibers)
RHCA - STEL/C	4 mg/m <sup>3</sup> (E: the value is for particulate matter containing no asbestos and ≤ 1% crystalline silica, R: respirable fraction) 10 mg/m <sup>3</sup> total inhalable dust 1 mg/m <sup>3</sup> respirable dust
Regulatory reference	Government Notice No. R. 280, 2021 Government Notice. R: 1179
<b>South Africa - Occupational Exposure Limits (Airborne Pollutants)</b>	
Local name	Talc
OEL TWA	10 mg/m <sup>3</sup> inhalable particulate 1 mg/m <sup>3</sup> respirable particulate
Regulatory reference	Government Notice No. R 904
<b>ethylbenzene (100-41-4)</b>	
<b>South Africa - Occupational Exposure Limits (Restricted Limits)</b>	
Local name	Ethyl benzene
RHCA - STEL/C [ppm]	40 ppm
Remark	CARC (denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B), SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021

# Dura - Epoxy Enamel - White

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

ethylbenzene (100-41-4)	
<b>South Africa - Occupational Exposure Limits (Airborne Pollutants)</b>	
Local name	Ethyl benzene
OEL TWA	435 mg/m <sup>3</sup>
OEL TWA [ppm]	100 ppm
OEL STEL	545 mg/m <sup>3</sup>
OEL STEL [ppm]	125 ppm
Regulatory reference	Government Notice No. R 904
<b>South Africa - Biological limit values</b>	
Local name	Ethyl benzene
BEI	0.15 g/g creatinine Parameter: Sum of mandelic acid and phenylglyoxylic acid - Medium: urine - Sampling time: End of shift - Notations: Ns (non-specific)
Regulatory reference	Government Notice No. R. 280, 2021
n-Butyl alcohol (71-36-3)	
<b>South Africa - Occupational Exposure Limits (Airborne Pollutants)</b>	
Local name	n-Butyl alcohol (Butan-1-ol)
OEL STEL	150 mg/m <sup>3</sup>
OEL STEL [ppm]	50 ppm
Remark	Sk (Danger of cutaneous absorption)
Regulatory reference	Government Notice No. R 904

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment

Hand protection : Protective gloves  
Eye protection : Safety glasses  
Skin and body protection : Wear suitable protective clothing  
Respiratory protection : [In case of inadequate ventilation] wear respiratory protection.  
Personal protective equipment symbol(s)



### 8.4. Exposure limit values for the other components

No additional information available

## SECTION 9: Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state : Liquid  
Appearance : Opaque.  
Colour : White.  
Odour : Aromatic.  
Odour threshold : No data available  
pH : No data available

# Dura - Epoxy Enamel - White

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability	: Highly flammable liquid and vapour.
Vapour pressure	: No data available
Vapour pressure at 50°C	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: > 1.15 – < 1.2
Relative density of saturated gas/air mixture	: No data available
Density	: No data available
Relative gas density	: No data available
Solubility	: immiscible.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: > 260 – < 380 cP
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Physical state	: Liquid
Appearance	: Opaque.

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10: Stability and Reactivity

### 10.1. Reactivity

Highly flammable liquid and vapour.

### 10.2. Chemical Stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

# Dura - Epoxy Enamel - White

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Harmful if inhaled.

<b>Dura - Epoxy Enamel - White</b>	
ATE ZA (dust, mist)	3.373 mg/l/4h
<b>Xylene (1330-20-7)</b>	
LD50 oral rat	≈ 3523 mg/kg bodyweight
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male, Remarks on results: other:
LC50 Inhalation - Rat	≈ 27.124 mg/l Source: ECHA
<b>Titanium dioxide (13463-67-7)</b>	
LC50 Inhalation - Rat (Dust/Mist)	> 6.82 mg/l Source: ECHA
<b>Talc /Talc containing no asbestos fibers/ (14807-96-6)</b>	
LD50 oral rat	> 5000 mg/l Animal: rat, Animal sex: male, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 2.1 mg/l Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
<b>ethylbenzene (100-41-4)</b>	
LD50 oral rat	≈ 3500 mg/kg bodyweight Animal: rat
<b>n-Butyl alcohol (71-36-3)</b>	
LD50 oral rat	2292 mg/kg Source: ECHA
LD50 dermal rabbit	3430 mg/kg Source: ECHA
LC50 Inhalation - Rat [ppm]	8000 ppm Source: ECHA
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer (Inhalation).
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
<b>n-Butyl alcohol (71-36-3)</b>	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
<b>Butanone (78-93-3)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs (hearing organs, respiratory system) through prolonged or repeated exposure (Inhalation).
<b>Xylene (1330-20-7)</b>	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
<b>Talc /Talc containing no asbestos fibers/ (14807-96-6)</b>	
NOAEL (oral, rat, 90 days)	100 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.



# Dura - Epoxy Enamel - White

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

<b>ethylbenzene (100-41-4)</b>	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

<b>Xylene (1330-20-7)</b>	
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

<b>Titanium dioxide (13463-67-7)</b>	
LOEC (acute)	≈ 160 mg/l Fish, 4 Days; Source: ECHA
LOEC (chronic)	≈ 5 mg/l Crustacea, 21 Days; Source: ECHA
NOEC (acute)	0.004 – 0.08 mg/l 28 Dday, fish; Source: Echa

<b>Talc /Talc containing no asbestos fibers/ (14807-96-6)</b>	
LC50 - Fish [1]	89581.02 mg/l Test organisms (species): other:
LC50 - Fish [2]	110000 mg/l Test organisms (species): other:
EC50 96h - Algae [1]	7202.7 mg/l Test organisms (species): other:
NOEC (chronic)	1459798 mg/l Test organisms (species): other: Duration: '30 d'

<b>ethylbenzene (100-41-4)</b>	
LC50 - Fish [1]	5.1 mg/l Test organisms (species): Menidia menidia
EC50 72h - Algae [1]	5.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	4.9 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [1]	3.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	7.7 mg/l Test organisms (species): Skeletonema costatum
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'

<b>n-Butyl alcohol (71-36-3)</b>	
LC50 - Fish [1]	1376 mg/l Source: ECHA
EC50 - Crustacea [1]	1983 mg/l Source: ECHA
EC50 96h - Algae [1]	225 mg/l Source: ECHA

# Dura - Epoxy Enamel - White

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

Butanone (78-93-3)	
LC50 - Fish [1]	2973 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	308 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	1220 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	1240 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

### 12.2. Persistence and degradability

Dura - Epoxy Enamel - White	
Persistence and degradability	No additional information available

### 12.3. Bioaccumulative potential

Dura - Epoxy Enamel - White	
Bioaccumulative potential	No additional information available

n-Butyl alcohol (71-36-3)	
Partition coefficient n-octanol/water (Log Kow)	1 Source: ECHA

### 12.4. Mobility in soil

Dura - Epoxy Enamel - White	
Mobility in soil	No additional information available

### 12.5. Other adverse effects

Ozone : Not classified  
Other adverse effects : No additional information available




## SECTION 13: Disposal Considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Additional information : Flammable vapours may accumulate in the container.

## SECTION 14: Transport information

In accordance with SANS / IMDG / IATA

SANS	IMDG	IATA
<b>14.1. UN number</b>		
1866	1866	1866
<b>14.2. UN Proper Shipping Name</b>		
RESIN SOLUTION	RESIN SOLUTION	Resin solution
<b>14.3. Transport hazard class(es)</b>		
3	3	3
		

# Dura - Epoxy Enamel - White

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

SANS	IMDG	IATA
<b>14.4. Packing group, if applicable</b>		
III	III	III
<b>14.5. Environmental hazards</b>		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available		

### 14.6. Special precautions for user

#### SANS

Special provisions (SANS)	: 223
Limited quantities (SANS)	: 5 L
Limited quantities (SANS)	: 5 L
Packagings, large packagings and IBCs Packing instructions (SANS)	: P001, IBC03, LP01
Packagings, large packagings and IBCs Special packing instructions (SANS)	: PP1
Portable tank and bulk containers instructions (SANS)	: T2
Portable tank and bulk container special provisions (SANS)	: TP1

#### IMDG

Special provisions (IMDG)	: 223, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

#### IATA

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

### 14.7. Transport in bulk according to IMO instructions

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

# Dura - Epoxy Enamel - White

## Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

### SECTION 16: Other information

Issue date : 31/07/2023

Full text of H-statements:	
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), South Africa (HCA)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.