

SECTION 1: Identification of the substance/mixture and of the supplier/undertaking

1.1. GHS product identifier

Product form : Mixture
Trade name : Wedgewood - Opulent Ripple Coat
Type of product : Coatings
Product code : OPRIPW
Product group : Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Water-based decorative coating

1.4. Supplier's details

Manufacturer

Dura Paints (Pty) Ltd.
5 Wakefield Road; Founders View South.
P.O. Box 303
1610 Edenvale; Johannesburg – South Africa
T 011 452 5221
Contact: Lizel Rosemann

1.5. Emergency phone number

Emergency number : 079 494 2731 / 011 452 5221

SECTION 2: Hazard identification


2.1. GHS classification of the substance/mixture and any national or regional information

Classification according to the United Nations GHS

Skin corrosion/irritation Not classified
Carcinogenicity, Category 2 H351
Specific target organ toxicity – Repeated exposure, Category 2 H373
Full text of H-statements: see section 16
Adverse physicochemical, human health and environmental effects : Suspected of causing cancer, May cause damage to organs through prolonged or repeated exposure.

2.2. GHS label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS ZA) : 

Signal word (GHS-ZA) : Warning

Hazardous ingredients : Titanium dioxide; Talc /Talc containing no asbestos fibers/; Ethylene Glycol (Regular)

Hazard statements (GHS ZA) : H351 - Suspected of causing cancer (Inhalation)
H373 - May cause damage to organs (respiratory system) through prolonged or repeated exposure (Inhalation)

Precautionary statements (GHS ZA) : P102 - Keep out of reach of children.
P103 - Read carefully and follow all instructions.
P260 - Do not breathe dust, mist, spray.
P501 - Dispose of container to recycling.

Wedgewood - Opulent Ripple Coat

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

2.3. Other hazards which do not result in classification or are not covered by the GHS

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to the United Nations GHS
Titanium dioxide	CAS-No.: 13463-67-7	2 – 10	Acute Tox. Not classified (Inhalation:dust,mist) Carc. 2, H351
Silicon dioxide	CAS-No.: 7631-86-9	1.97 – 9.85	Acute Tox. Not classified (Dermal) Acute Tox. Not classified (Inhalation:dust,mist) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Acute Not classified Aquatic Chronic Not classified
Talc /Talc containing no asbestos fibers/	CAS-No.: 14807-96-6	1 – 5	Acute Tox. Not classified (Oral) Acute Tox. 4 (Inhalation:dust,mist), H332 STOT RE 2, H373 Aquatic Acute Not classified
Ethelyne Glycol (Regular)	CAS-No.: 107-21-1	1 – 3	Acute Tox. 4 (Oral), H302 STOT RE 2, H373

SECTION 4: First aid measures

4.1. Description of necessary first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms/effect, acute and delayed

No additional information available

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

Wedgewood - Opulent Ripple Coat

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

5.3. Special protective actions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Titanium dioxide (13463-67-7)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Titanium dioxide
RHCA - STEL/C	10 mg/m ³ 10 mg/m ³ total inhalable dust 5 mg/m ³ respirable dust
Remark	CARC (denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B)
Regulatory reference	Government Notice No. R. 280, 2021 Government Notice. R: 1179
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Titanium dioxide

Wedgewood - Opulent Ripple Coat

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

Titanium dioxide (13463-67-7)	
OEL TWA	10 mg/m ³ inhalable particulate 5 mg/m ³ respirable particulate
Regulatory reference	Government Notice No. R 904
Talc /Talc containing no asbestos fibers/ (14807-96-6)	
South Africa - Occupational Exposure Limits (Maximum Limits)	
Local name	Talc (containing asbestos fibres)
RHCA - OEL [ppm]	0.6 fibers/mL (measured over a continuous 10-minute period)
RHCA - STEL/C [ppm]	0.1 fibers/mL
Remark	CARC (denotes carcinogenicity, which is based on GHS categorisation, including category 1A and 1B)
Regulatory reference	Government Notice No. R. 280, 2021; Government Notice No. R. 11196, 2020
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Talc (containing no asbestos fibers)
RHCA - STEL/C	4 mg/m ³ (E: the value is for particulate matter containing no asbestos and ≤ 1% crystalline silica, R: respirable fraction) 10 mg/m ³ total inhalable dust 1 mg/m ³ respirable dust
Regulatory reference	Government Notice No. R. 280, 2021 Government Notice. R: 1179
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Talc
OEL TWA	10 mg/m ³ inhalable particulate 1 mg/m ³ respirable particulate
Regulatory reference	Government Notice No. R 904
Silicon dioxide (7631-86-9)	
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Silica, amorphous
OEL TWA	6 mg/m ³ inhalable particulate 3 mg/m ³ respirable particulate
Regulatory reference	Government Notice No. R 904
Ethylene Glycol (Regular) (107-21-1)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Ethylene glycol
OEL eight hour TWA	20 mg/m ³ (H: aerosol only)
RHCA - STEL/C	50 mg/m ³ (V: vapour fraction) 100 mg/m ³ (V: vapour fraction)
Remark	SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Ethylene glycol (Ethane-1,2-diol; 1,2-Dihydroxyethane)
OEL TWA	20 mg/m ³
OEL STEL	40 mg/m ³
Regulatory reference	Government Notice No. R 904

Wedgewood - Opulent Ripple Coat

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection : Protective gloves
Eye protection : Safety glasses
Skin and body protection : Wear suitable protective clothing
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s)



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid
Appearance : No data available
Colour : White.
Odour : Slight odour.
Odour threshold : No data available
pH : > 8.8
pH solution : No data available
Relative evaporation rate (butylacetate=1) : No data available
Relative evaporation rate (ether=1) : No data available
Melting point : Not applicable
Freezing point : No data available
Boiling point : No data available
Flash point : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability : Non flammable.
Vapour pressure : No data available
Vapour pressure at 50°C : No data available
Relative vapour density at 20°C : No data available
Relative density : No data available
Relative density of saturated gas/air mixture : No data available
Density : No data available
Relative gas density : No data available
Solubility : No data available
Partition coefficient n-octanol/water (Log Pow) : No data available
Partition coefficient n-octanol/water (Log Kow) : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available
Explosive limits : No data available
Lower explosion limit : No data available
Upper explosion limit : No data available
Physical state : Liquid
Appearance : No data available

Wedgewood - Opulent Ripple Coat

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10: Stability and Reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical Stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Titanium dioxide (13463-67-7)	
LC50 Inhalation - Rat (Dust/Mist)	> 6.82 mg/l Source: ECHA
Talc /Talc containing no asbestos fibers/ (14807-96-6)	
LD50 oral rat	> 5000 mg/l Animal: rat, Animal sex: male, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 2.1 mg/l Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
Silicon dioxide (7631-86-9)	
LD50 oral rat	3160 mg/kg Source: TOMES; HAZARTEXT
LD50 dermal rabbit	> 5000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Dust/Mist)	5.01 mg/l Source: ECHA
Ethylene Glycol (Regular) (107-21-1)	
LD50 oral rat	6000 – 13000 mg/kg Source: Supplier SDS
LD50 dermal rabbit	> 2270 mg/kg Source: Supplier SDS
LC50 Inhalation - Rat	> 3.95 mg/l Source: Supplier SDS

Wedgewood - Opulent Ripple Coat

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

Skin corrosion/irritation	: Not classified. pH: > 8.8
Serious eye damage/irritation	: Not classified pH: > 8.8
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer (Inhalation).
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

Silicon dioxide (7631-86-9)

STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs (respiratory system) through prolonged or repeated exposure (Inhalation).

Talc /Talc containing no asbestos fibers/ (14807-96-6)

NOAEL (oral, rat, 90 days)	100 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Ethylene Glycol (Regular) (107-21-1)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Titanium dioxide (13463-67-7)

LOEC (acute)	≈ 160 mg/l Fish, 4 Days; Source: ECHA
LOEC (chronic)	≈ 5 mg/l Crustacea, 21 Days; Source: ECHA
NOEC (acute)	0.004 – 0.08 mg/l 28 Dday, fish; Source: Echa

Talc /Talc containing no asbestos fibers/ (14807-96-6)

LC50 - Fish [1]	89581.02 mg/l Test organisms (species): other:
LC50 - Fish [2]	110000 mg/l Test organisms (species): other:
EC50 96h - Algae [1]	7202.7 mg/l Test organisms (species): other:
NOEC (chronic)	1459798 mg/l Test organisms (species): other: Duration: '30 d'

Silicon dioxide (7631-86-9)

LC50 - Fish [1]	10000 mg/l Source: ECHA
EC50 - Crustacea [1]	> 5000 mg/l Source: ECHA
EC50 72h - Algae [1]	> 173.1 mg/l Source: ECHA
EC50 96h - Algae [1]	217.576 – 217.6 mg/l Source: ECHA
LOEC (chronic)	≈ 149.2 mg/l Source: ECHA
NOEC (chronic)	68 – 250 mg/l 21 days; Source: ECHA

Wedgewood - Opulent Ripple Coat

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

Silicon dioxide (7631-86-9)	
NOEC chronic fish	≈ 57.001 mg/l Source: ECHA
NOEC chronic algae	≈ 42.1 mg/l
Ethelyne Glycol (Regular) (107-21-1)	
LC50 - Fish [1]	≈ 51000 mg/l Source: Supplier SDS
LC50 - Fish [2]	≈ 27540 (≤ 0) mg/l Source: Supplier SDS
EC50 - Crustacea [1]	46300 – 51100 mg/l Source: Supplier SDS
EC50 72h - Algae [1]	9500 – 13000 mg/l Source: Supplier SDS
NOEC chronic fish	≈ 15.38 g/l Source: ECHA
NOEC chronic crustacea	7.5 – 15 g/l Period: 21 days; Source: ECHA
NOEC chronic algae	≈ 100 mg/l Period: 72 hours; Source: ECHA

12.2. Persistence and degradability

Wedgewood - Opulent Ripple Coat	
Persistence and degradability	No additional information available

12.3. Bioaccumulative potential

Wedgewood - Opulent Ripple Coat	
Bioaccumulative potential	No additional information available

Ethelyne Glycol (Regular) (107-21-1)	
Bioconcentration factor (BCF REACH)	< 100
Partition coefficient n-octanol/water (Log Kow)	≈ -1.36

12.4. Mobility in soil

Wedgewood - Opulent Ripple Coat	
Mobility in soil	No additional information available

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No additional information available

SECTION 13: Disposal Considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with SANS / IMDG / IATA

SANS	IMDG	IATA
14.1. UN number		
Not regulated for transport		
14.2. UN Proper Shipping Name		
Not applicable	Not applicable	Not applicable

Wedgewood - Opulent Ripple Coat

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

SANS	IMDG	IATA
14.3. Transport hazard class(es)		
Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable
14.4. Packing group, if applicable		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available		

14.6. Special precautions for user

SANS

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to IMO instructions

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

SECTION 16: Other information

Issue date : 21/06/2023

Full text of H-statements:	
H302	Harmful if swallowed
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

Safety Data Sheet (SDS), South Africa (HCA)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.