

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8 Issue date: 6/21/2023 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the supplier/undertaking

1.1. GHS product identifier		
Product form	: Mixture	
Trade name	: Wedgewood - Opulent Super Gloss - White & Deep	
Type of product	: Coatings	
Product code	: OPSGL W/DE	
Product group	: Trade product	

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture

: Decorative coating

1.4. Supplier's details

Manufacturer

Dura Paints (Pty) Ltd. 5 Wakefield Road; Founders View South. P.O. Box 303 1610 Edenvale; Johannesburg – South Africa T 011 452 5221 Contact: Lizel Rosemann

1.5. Emergency phone number

Emergency number

: 079 494 2731 / 011 452 5221

SECTION 2: Hazard identification

2.1. GHS classification of the substance/mixture and any national or regional information

Classification according to the United Nations GHS

Flammable liquids, Category 3	H226
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 1B	H350
Specific target organ toxicity - Repeated exposure, Category	1 H372
Aspiration hazard, Category 1	H304
Full text of H-statements: see section 16	
Adverse physicochemical, human health and : Flam	mable liquid and
environmental effects prolo	onged or repeated

Flammable liquid and vapour,May cause cancer,Causes damage to organs through prolonged or repeated exposure,May cause an allergic skin reaction,May be fatal if swallowed and enters airways.

2.2. GHS label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS ZA)

Signal word (GHS-ZA) Hazardous ingredients Hazard statements (GHS ZA) : Danger

: Solvent naphtha (petroleum), medium aliph.; Cobalt bis(2-ethylhexanoate); Butanone oxime : H226 - Flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

	H317 - May cause an allergic skin reaction
	H350 - May cause cancer (Inhalation)
	H372 - Causes damage to organs (central nervous system) through prolonged or repeated
	exposure (Inhalation)
Precautionary statements (GHS ZA)	: P102 - Keep out of reach of children.
	P103 - Read carefully and follow all instructions.
	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
	No smoking.
	P261 - Avoid breathing dust, mist, spray.
	P280 - Wear protective clothing, protective gloves.
	P319 - Get medical help if you feel unwell.
	P331 - Do NOT induce vomiting.
	P501 - Dispose of container to recycling.

2.3. Other hazards which do not result in classification or are not covered by the GHS

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to the United Nations GHS
Titanium dioxide	CAS-No.: 13463-67-7	10 – 18	Acute Tox. Not classified (Inhalation:dust,mist) Carc. 2, H351
Solvent naphtha (petroleum), medium aliph.	CAS-No.: 64742-88-7	7.5 – 15.3	Flam. Liq. 3, H226 Acute Tox. Not classified (Oral) Acute Tox. 3 (Inhalation:vapour), H331 STOT RE 1, H372 Asp. Tox. 1, H304
Solvent naphtha (petroleum), heavy arom.	CAS-No.: 64742-94-5	1.5 – 4.5	STOT RE 2, H373 Asp. Tox. 1, H304
Butanone oxime	CAS-No.: 96-29-7	0.0995 – 0.2985	Flam. Liq. 4, H227 Acute Tox. 3 (Oral), H301 Acute Tox. 4 (Dermal), H312 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 1B, H350 STOT SE 1, H370 STOT SE 3, H336 STOT RE 1, H372 Aquatic Chronic 2, H411
Cobalt bis(2-ethylhexanoate)	CAS-No.: CAS 136-52-7	0.094 – 0.294	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT RE 1, H372 Aquatic Chronic 2, H411

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

SECTION 4: First aid measures		
4.1. Description of necessary first aid measures		
First-aid measures general	: Call a physician immediately.	
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.	
First-aid measures after skin contact	 Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention. 	
First-aid measures after eye contact	: Rinse eyes with water as a precaution.	
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.	
4.2. Most important symptoms/effect, acute and delayed		
Symptoms/effects after skin contact Symptoms/effects after ingestion	May cause an allergic skin reaction.Risk of lung oedema.	

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures				
5.1. Suitable (and unsuitable) extinguishing media				
Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.			
5.2. Specific hazards arising from the chemical				
Fire hazard Hazardous decomposition products in case of fire	: Flammable liquid and vapour. : Toxic fumes may be released.			
5.3. Special protective actions for fire-fighters				
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.			

SECTION 6: Accidental release measures				
6.1. Personal precautions, protective	equipment and emergency procedures			
6.1.1. For non-emergency personnel				
Emergency procedures	 No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapours/spray. 			
6.1.2. For emergency responders				
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".			

6	.2.	En	/ironme	nta	l precau	tions
---	-----	----	---------	-----	----------	-------

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up		
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.	
Other information	: Dispose of materials or solid residues at an authorized site.	

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

SECTION 7: Handling and storage					
7.1. Precautions for safe handling	7.1. Precautions for safe handling				
Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.				
Hygiene measures	 Separate working clothes from town clothes. Launder separately. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. 				
7.2. Conditions for safe storage, incl	uding any incompatibilities				
Technical measures	: Ground/bond container and receiving equipment.				

: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Storage conditions

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Titanium dioxide (13463-67-7)			
South Africa - Occupational Exposure Limits (Restricted Limits)			
Local name Titanium dioxide			
RHCA - STEL/C 10 mg/m³ 10 mg/m³ total inhalable dust 5 mg/m³ respirable dust			
Remark CARC (denotes carcinogenicity, which is based on GHS categorisation, including 1A, 1B)			
Regulatory reference	Government Notice No. R. 280, 2021 Government Notice. R: 1179		
South Africa - Occupational Exposure Limits (Airborne Pollutants)			
Local name	Titanium dioxide		
OEL TWA	10 mg/m³ inhalable particulate 5 mg/m³ respirable particulate		
Regulatory reference	Government Notice No. R 904		
8.2. Appropriate engineering controls			
	Ensure good ventilation of the work station. Avoid release to the environment.		
8.3. Individual protection measures, such as personal protective equipment			
Hand protection:Eye protection:Skin and body protection:Respiratory protection:Personal protective equipment symbol(s)	Protective gloves Safety glasses Wear suitable protective clothing [In case of inadequate ventilation] wear respiratory protection.		

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: white. Can be tinted to various colours.
Odour	: Aromatic solvent like odour.
Odour threshold	: No data available
рН	: No data available
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 29 – < 70 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability	: Flammable liquid and vapour.
Vapour pressure	: No data available
Vapour pressure at 50°C	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: ≈ 1.07
Relative density of saturated gas/air mixture	: No data available
Density	: No data available
Relative gas density	: No data available
Solubility	: insoluble in water. Soluble in in aromatic solvents.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	$\therefore > 1 - < 4.3 \text{ mm}^2/\text{s}$
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Physical state	: Liquid
Appearance	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10: Stability and Reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical Stability

Stable under normal conditions.

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11.1. Information on toxicological ef	fects	
Acute toxicity (oral) Acute toxicity (dermal) Acute toxicity (inhalation)	 Not classified Not classified Not classified 	
Solvent naphtha (petroleum), mediu	ım aliph. (64742-88-7)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Remarks on results: other:	
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Remarks on results: other:	
LC50 Inhalation - Rat (Vapours)	> 5.28 mg/l/4h Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:, 95% CL: 0,42 -	
Solvent naphtha (petroleum), heavy arom. (64742-94-5)		
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Remarks on results: other:	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Remarks on results: other:	
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Remarks on results: other:	
Titanium dioxide (13463-67-7)		
_C50 Inhalation - Rat (Dust/Mist)	> 6.82 mg/l Source: ECHA	
Cobalt bis(2-ethylhexanoate) (CAS 136-52-7)		
LD50 oral rat	3129 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral Toxicity: Up-and-Down Procedure), 95% CL: 1750 - 5000	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
LD50 dermal rabbit	≈ 1244 mg/kg Category 4 based on GHS criteria ; Source: ECHA	
Butanone oxime (96-29-7)		
D50 dermal rabbit	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Derma Toxicity)	
_C50 Inhalation - Rat	> 4.83 mg/l/4h Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation	Not classified	

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

Respiratory or skin sensitisation	May cause an allergic skin reaction.	
Germ cell mutagenicity :	Not classified	
Carcinogenicity :	May cause cancer (Inhalation).	
Reproductive toxicity :	Not classified	
STOT-single exposure :	Not classified	
Cobalt bis(2-ethylhexanoate) (CAS 136-52-7)		
NOAEC (inhalation, rat, vapour)	>	
Butanone oxime (96-29-7)		
STOT-single exposure	Causes damage to organs. May cause drowsiness or dizziness.	
STOT-repeated exposure :	Causes damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation).	
Solvent naphtha (petroleum), medium aliph.	(64742-88-7)	
NOAEL (oral, rat, 90 days)	750 mg/kg bodyweight Animal: rat, Animal sex: female	
NOAEC (inhalation, rat, vapour, 90 days)	≥ 0.024 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.	
Solvent naphtha (petroleum), heavy arom. (64742-94-5)		
LOAEL (dermal, rat/rabbit, 90 days)	50 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)	
LOAEC (inhalation, rat, vapour, 90 days)	4.71 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90- Day Study)	
NOAEC (inhalation, rat, vapour, 90 days)	2355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90- Day Study)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.	
Cobalt bis(2-ethylhexanoate) (CAS 136-52-7)		
LOAEC (inhalation, rat,dust/mist/fume, 90 days)	0.31 mg/l air Animal: rat	
NOAEL (oral, rat, 90 days)	3 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.	
Butanone oxime (96-29-7)		
LOAEL (oral, rat, 90 days)	40 mg/kg bodyweight Animal: rat, Guideline: other:	
NOAEC (inhalation, rat, vapour, 90 days)	0.09 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)	
NOAEL (subchronic, oral, animal/male, 90 days)	110 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS	
	870.3100 (90-Day Oral Toxicity in Rodents)	
STOT-repeated exposure	870.3100 (90-Day Oral Toxicity in Rodents) Causes damage to organs through prolonged or repeated exposure.	
· · ·		
· · ·	Causes damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.	

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

Hazardous to the aquatic environment, short-term : Not classified (acute) Hazardous to the aquatic environment, long-term : Not classified (chronic)			
Solvent naphtha (petroleum), heavy arom. (64	Solvent naphtha (petroleum), heavy arom. (64742-94-5)		
EC50 - Crustacea [1]	1.2 mg/l Test organisms (species): Daphnia magna		
Titanium dioxide (13463-67-7)			
LOEC (acute)	≈ 160 mg/l Fish, 4 Days; Source: ECHA		
LOEC (chronic)	≈ 5 mg/l Crustacea, 21 Days; Source: ECHA		
NOEC (acute)	0.004 – 0.08 mg/l 28 Dday, fish; Source: Echa		
Cobalt bis(2-ethylhexanoate) (CAS 136-52-7)			
LC50 - Fish [1]	1.406 – 180 mg/l Source: ECHA		
EC50 - Crustacea [1]	5.89 mg/l Test organisms (species): Daphnia magna		
EC50 - Crustacea [2]	≈ 2.2827 mg/l Source: ECHA		
EC50 72h - Algae [1]	0.028 – 44.39 mg/l Source: ECHA		
EC50 96h - Algae [1]	10.8 – 71.314 mg/l Source: ECHA		
ErC50 algae	0.0288 – 44.39 mg/l Source: ECHA		
LOEC (acute)	1.43 – 88.7 mg/l Source: ECHA		
NOEC (chronic)	1.02 – 2.14 mg/l 33 days; Source: ECHA		
NOEC chronic fish	≈ 31.196 mg/l 28 days; Source: ECHA		
NOEC chronic crustacea	0.0165 – 0.684 mg/l 30 days; Source: ECHA		
NOEC chronic algae	≈ 0.0018 mg/l 7 days; Good morning,		
Butanone oxime (96-29-7)			
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes		
EC50 - Crustacea [1]	≈ 201 mg/l Test organisms (species): Daphnia magna		
EC50 72h - Algae [1]	≈ 11.8 mg/l Test organisms (species): Scenedesmus capricornutum		
EC50 72h - Algae [2]	≈ 6.09 mg/l Test organisms (species): Scenedesmus capricornutum		
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
12.2. Persistence and degradability			
Wedgewood - Opulent Super Gloss - White & Deep			
Persistence and degradability	No additional information available		
Cobalt bis(2-ethylhexanoate) (CAS 136-52-7)			
Not rapidly degradable			
Biodegradation in water: under test conditions no biodegradation observed			
Butanone oxime (96-29-7)			
Not rapidly degradable			
12.3. Bioaccumulative potential			
Wedgewood - Opulent Super Gloss - White &	Wedgewood - Opulent Super Gloss - White & Deep		
Bioaccumulative potential	No additional information available		

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

Cobalt bis(2-ethylhexanoate) (CAS 136-52-7)		
Partition coefficient n-octanol/water (Log Kow)	≈ 2.96 20 °C and pH 7; Source: ECHA	
12.4. Mobility in soil		
Wedgewood - Opulent Super Gloss - White & Deep		
Mobility in soil	No additional information available	
12.5. Other adverse effects		
	Not classified No additional information available	

SECTION 13: Disposal Considerations	
13.1. Disposal methods	
Waste treatment methods Additional information	Dispose of contents/container in accordance with licensed collector's sorting instructions.Flammable vapours may accumulate in the container.

SECTION 14: Transport information

SANS	IMDG	ΙΑΤΑ
I4.1. UN number		
1263	1263	1263
I4.2. UN Proper Shipping Name	·	
PAINT	PAINT	Paint
14.3. Transport hazard class(es)		
3	3	3
14.4. Packing group, if applicable		
Ш	Ш	III
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available	1	1

SANS

SANS	
Special provisions (SANS)	: 163, 187, 223
Limited quantities (SANS)	: 5 L
Limited quantities (SANS)	: 5 L
Packagings, large packagings and IBCs Packing	: P001, IBC03, LP01
instructions (SANS)	
Packagings, large packagings and IBCs Special	: PP1
packing instructions (SANS)	
Portable tank and bulk containers instructions	: T2
(SANS)	

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

Portable tank and bulk container special provisions : TP1, TP29 (SANS)

IMDG	
Special provisions (IMDG)	: 163, 223, 367, 955
Limited quantities (IMDG)	: 5L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

ΙΑΤΑ

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

14.7. Transport in bulk according to IMO instructions

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

SECTION 16: Other information

Issue date

: 21/06/2023

Full text of H-statements:	
H226	Flammable liquid and vapour
H227	Combustible liquid
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H331	Toxic if inhaled
H336	May cause drowsiness or dizziness
H350	May cause cancer

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 8

Full text of H-statements:	
H351	Suspected of causing cancer
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), South Africa (HCA)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.