

SECTION 1: Identification of the substance/mixture and of the supplier/undertaking

1.1. GHS product identifier

Product form	: Mixture
Trade name	: Dura - Quick Dry Enamel White
Type of product	: Coatings
Product code	: QDWG
Product group	: Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Light industrial coating applications

1.4. Supplier's details

Manufacturer

Dura Paints (Pty) Ltd.
5 Wakefield Road; Founders View South.
P.O. Box 303
1610 Edenvale; Johannesburg – South Africa
T 011 452 5221
Contact: Lizel Rosemann

1.5. Emergency phone number

Emergency number : 079 494 2731 / 011 452 5221

SECTION 2: Hazard identification

2.1. GHS classification of the substance/mixture and any national or regional information

Classification according to the United Nations GHS

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 2	H315
Germ cell mutagenicity, Category 1B	H340
Carcinogenicity, Category 1A	H350
Reproductive toxicity, Category 2	H361
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity – Repeated exposure, Category 2	H373
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects : Highly flammable liquid and vapour, May cause cancer, May cause genetic defects, Suspected of damaging fertility or the unborn child, May cause damage to organs through prolonged or repeated exposure, May cause drowsiness or dizziness, Causes skin irritation, May be fatal if swallowed and enters airways, Harmful to aquatic life with long lasting effects.

Dura - Quick Dry Enamel White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

2.2. GHS label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS ZA)



Signal word (GHS-ZA)	: Danger
Hazardous ingredients	: ethylbenzene; hexane; Solvent naphtha (petroleum), light aliph.; benzene; Toluene
Hazard statements (GHS ZA)	: H225 - Highly flammable liquid and vapour H304 - May be fatal if swallowed and enters airways H315 - Causes skin irritation H336 - May cause drowsiness or dizziness H340 - May cause genetic defects (Dermal, Inhalation) H350 - May cause cancer (Dermal, Inhalation) H361 - Suspected of damaging fertility, Suspected of damaging the unborn child. (Dermal, Inhalation) H373 - May cause damage to organs (Skin, central nervous system) through prolonged or repeated exposure (Dermal, Inhalation) H412 - Harmful to aquatic life with long lasting effects
Precautionary statements (GHS ZA)	: P102 - Keep out of reach of children. P103 - Read carefully and follow all instructions. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 - Avoid breathing vapours, spray, mist. P263 - Avoid contact during pregnancy and while nursing. P273 - Avoid release to the environment. P280 - Wear eye protection, protective clothing, protective gloves. P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P302+P352 - IF ON SKIN: Wash with plenty of soap and water IF INHALED: Remove person to fresh air and keep comfortable for breathing. P363 - Wash contaminated clothing before reuse. P501 - Dispose of container to recycling.
P-statements for label (GHS-ZA)	: P102 - Keep out of reach of children.; P103 - Read carefully and follow all instructions.; P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.; P261 - Avoid breathing vapours, spray, mist.; P263 - Avoid contact during pregnancy and while nursing.; P273 - Avoid release to the environment.; P280 - Wear eye protection, protective clothing, protective gloves.; P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.; P302+P352 - IF ON SKIN: Wash with plenty of soap and water; IF INHALED: Remove person to fresh air and keep comfortable for breathing.; P363 - Wash contaminated clothing before reuse.; P501 - Dispose of container to recycling.

2.3. Other hazards which do not result in classification or are not covered by the GHS

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Dura - Quick Dry Enamel White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

3.2. Mixture

Name	Product identifier	%	Classification according to the United Nations GHS
Toluene	CAS-No.: 108-88-3	4 – 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Xylene	CAS-No.: 1330-20-7	2.9 – 21.625	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. Not classified (Inhalation:dust,mist) Skin Irrit. 2, H315 STOT RE Not classified Aquatic Chronic Not classified
Solvent naphtha (petroleum), light aliph.	CAS-No.: 64742-89-8	4 – 21	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
Titanium dioxide	CAS-No.: 13463-67-7	10 – 20	Acute Tox. Not classified (Inhalation:dust,mist) Carc. 2, H351
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	-	7.5 – 17.5	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 4, H413
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS-No.: 64742-48-9	7.5 – 15	Flam. Liq. 3, H226 Asp. Tox. 1, H304
hexane	CAS-No.: 110-54-3	0.4 – 4.8	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
ethylbenzene	CAS-No.: 100-41-4	0.3 – 1.2	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapour), H332 STOT RE 2, H373 Asp. Tox. 1, H304
benzene	CAS-No.: 71-43-2	0.04 – 0.6	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Muta. 1B, H340 Carc. 1A, H350 STOT RE 1, H372 Asp. Tox. 1, H304

SECTION 4: First aid measures

4.1. Description of necessary first aid measures

- First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

Dura - Quick Dry Enamel White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms/effect, acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: Risk of lung oedema.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective actions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

For containment	: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
-----------------	---

Dura - Quick Dry Enamel White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
- Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
- Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Xylene (1330-20-7)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Xylene, o-, m-, p- or mixed isomers
OEL eight hour TWA	300 ppm
RHCA - STEL/C	200 ppm
Remark	SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Xylene, o-, m-, p- or mixed isomers
OEL TWA	218 mg/m ³ 50 ppm
OEL STEL	435 mg/m ³ 100 ppm
Remark	Sk (Danger of cutaneous absorption)
Regulatory reference	Government Notice No. R 904
South Africa - Biological limit values	
Local name	Xylenes

Dura - Quick Dry Enamel White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Xylene (1330-20-7)	
BEI	1.5 g/g creatinine Parameter: Methylhippuric acids - Medium: urine - Sampling time: End of shift
Regulatory reference	Government Notice No. R. 280, 2021
ethylbenzene (100-41-4)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Ethyl benzene
RHCA - STEL/C	40 ppm
Remark	CARC (denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B), SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Ethyl benzene
OEL TWA	435 mg/m ³
	100 ppm
OEL STEL	545 mg/m ³
	125 ppm
Regulatory reference	Government Notice No. R 904
South Africa - Biological limit values	
Local name	Ethyl benzene
BEI	0.15 g/g creatinine Parameter: Sum of mandelic acid and phenylglyoxylic acid - Medium: urine - Sampling time: End of shift - Notations: Ns (non-specific)
Regulatory reference	Government Notice No. R. 280, 2021
hexane (110-54-3)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	n-Hexane
RHCA - STEL/C	100 ppm
Remark	SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	n-Hexane
OEL TWA	70 mg/m ³
	20 ppm
Regulatory reference	Government Notice No. R 904
South Africa - Biological limit values	
Local name	n-Hexane
BEI	0.4 mg/l Parameter: 2,5-Hexanedione - Medium: urine - Sampling time: End of shift at end of workweek
Regulatory reference	Government Notice No. R. 280, 2021
benzene (71-43-2)	
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Benzene

Dura - Quick Dry Enamel White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

benzene (71-43-2)	
OEL TWA	3 mg/m ³ 1 ppm
Regulatory reference	Government Notice No. R 904
Toluene (108-88-3)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Toluene
OEL eight hour TWA	150 ppm 560 mg/m ³
RHCA - STEL/C	40 ppm 50 ppm 188 mg/m ³
Remark	SKIN (danger of cutaneous absorption) Sk
Regulatory reference	Government Notice No. R. 280, 2021 Government Notice. R: 1179
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Toluene
OEL TWA	188 mg/m ³ 50 ppm
OEL STEL	560 mg/m ³ 150 ppm
Remark	Sk (Danger of cutaneous absorption)
Regulatory reference	Government Notice No. R 904
South Africa - Biological limit values	
Local name	Toluene
BEI	0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: Prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: End of shift 0.3 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: End of shift - Notations: B (background)
Regulatory reference	Government Notice No. R. 280, 2021
Titanium dioxide (13463-67-7)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Titanium dioxide
RHCA - STEL/C	10 mg/m ³ 10 mg/m ³ total inhalable dust 5 mg/m ³ respirable dust
Remark	CARC (denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B)
Regulatory reference	Government Notice No. R. 280, 2021 Government Notice. R: 1179
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Titanium dioxide

Dura - Quick Dry Enamel White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Titanium dioxide (13463-67-7)	
OEL TWA	10 mg/m ³ inhalable particulate 5 mg/m ³ respirable particulate
Regulatory reference	Government Notice No. R 904

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection : Protective gloves
Eye protection : Safety glasses
Skin and body protection : Wear suitable protective clothing
Respiratory protection : [In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s)



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid
Appearance : Viscous liquid.
Colour : White
Odour : Aromatic solvent like odour
Odour threshold : > ppm
pH : No data available
pH solution : No data available
Relative evaporation rate (butylacetate=1) : No data available
Relative evaporation rate (ether=1) : No data available
Melting point : Not applicable
Freezing point : ≈ -95 °C Toluene: @ 101 325 Pa : Echa
Boiling point : ≈ 110.85 °C Toluene: @ 325 Pa : Echa
Flash point : < 23 °C TDS
Auto-ignition temperature : ≈ 480 °C Toluene: at 101 325 Pa : Echa
Decomposition temperature : No data available
Flammability : Highly flammable liquid and vapour.
Vapour pressure : ≈ 30.89 hPa Toluene: @ 21 deg. C : Echa
Vapour pressure at 50°C : No data available
Relative vapour density at 20°C : No data available
Relative density : > 0.87 – < 0.92 TDS
Relative density of saturated gas/air mixture : No data available
Density : No data available
Relative gas density : No data available
Solubility : soluble in most organic solvents. insoluble in water.
Partition coefficient n-octanol/water (Log Pow) : No data available
Partition coefficient n-octanol/water (Log Kow) : No data available
Viscosity, kinematic : ≈ 3.8 mm²/s
Viscosity, dynamic : > 440 – < 1000 cP TDS
Explosive properties : No data available
Oxidising properties : No data available

Dura - Quick Dry Enamel White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Explosive limits	: No data available
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Physical state	: Liquid
Appearance	: Viscous liquid.

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10: Stability and Reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical Stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Xylene (1330-20-7)	
LD50 oral rat	≈ 3523 mg/kg bodyweight
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male, Remarks on results: other:
LC50 Inhalation - Rat	≈ 27.124 mg/l Source: ECHA
ethylbenzene (100-41-4)	
LD50 oral rat	≈ 3500 mg/kg bodyweight Animal: rat
Solvent naphtha (petroleum), light aliph. (64742-89-8)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	≈ 5.61 mg/l Source: ECHA
Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg Source: ECHA
LD50 dermal rabbit	> 5000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	> 20 mg/l Source: ECHA

Dura - Quick Dry Enamel White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Titanium dioxide (13463-67-7)	
LC50 Inhalation - Rat (Dust/Mist)	> 6.82 mg/l Source: ECHA
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	≥ 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	≥ 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: May cause genetic defects (Dermal, Inhalation).
Carcinogenicity	: May cause cancer (Dermal, Inhalation).
Reproductive toxicity	: Suspected of damaging fertility, Suspected of damaging the unborn child. (Dermal, Inhalation).
Reproductive toxicity	: Suspected of damaging fertility, Suspected of damaging the unborn child. (Dermal, Inhalation).
STOT-single exposure	: May cause drowsiness or dizziness.
hexane (110-54-3)	
STOT-single exposure	May cause drowsiness or dizziness.
Toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs (Skin, central nervous system) through prolonged or repeated exposure (Dermal, Inhalation).
Xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
hexane (110-54-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Solvent naphtha (petroleum), light aliph. (64742-89-8)	
LOAEC (inhalation, rat, vapour, 90 days)	≈ 1.402 mg/l
NOAEC (inhalation, rat, gas, 90 days)	≈ 1402 mg/l Specimen: Rat - Source: ECHA
benzene (71-43-2)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Toluene (108-88-3)	
LOAEL (oral, rat, 90 days)	≈ 1250 mg/kg bodyweight/day Source: ECHA
LOAEC (inhalation, rat, gas, 90 days)	≈ 2.261 mg/l Source: ECHA

Dura - Quick Dry Enamel White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Toluene (108-88-3)	
NOAEL (oral, rat, 90 days)	≈ 625 mg/kg bodyweight/day Rat
NOAEC (inhalation, rat, gas, 90 days)	1.131 – 2.355 mg/l Air, Source: ECHA
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.

Dura - Quick Dry Enamel White	
Viscosity, kinematic	≈ 3.8 mm ² /s

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Xylene (1330-20-7)	
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

ethylbenzene (100-41-4)	
LC50 - Fish [1]	5.1 mg/l Test organisms (species): Menidia menidia
EC50 72h - Algae [1]	5.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	4.9 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [1]	3.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	7.7 mg/l Test organisms (species): Skeletonema costatum
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'

Solvent naphtha (petroleum), light aliph. (64742-89-8)	
EC50 - Crustacea [1]	≈ 4.5 mg/l EL50 value Source: ECHA
NOEC chronic fish	≈ 2.6 mg/l

Toluene (108-88-3)	
LC50 - Fish [1]	5.5 mg/l Source: ECHA
EC50 - Crustacea [1]	3.78 mg/l Source: ECHA
NOEC chronic crustacea	≈ 0.74 mg/l Source: ECHA

Titanium dioxide (13463-67-7)	
LOEC (acute)	≈ 160 mg/l Fish, 4 Days; Source: ECHA
LOEC (chronic)	≈ 5 mg/l Crustacea, 21 Days; Source: ECHA
NOEC (acute)	0.004 – 0.08 mg/l 28 Dday, fish; Source: Echa

Dura - Quick Dry Enamel White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	
NOEC (chronic)	0.011 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

Dura - Quick Dry Enamel White	
Persistence and degradability	Rapidly degradable

Xylene (1330-20-7)	
Persistence and degradability	

ethylbenzene (100-41-4)	
Persistence and degradability	

hexane (110-54-3)	
Persistence and degradability	

Solvent naphtha (petroleum), light aliph. (64742-89-8)	
Persistence and degradability	

benzene (71-43-2)	
Persistence and degradability	

Toluene (108-88-3)	
Persistence and degradability	

Titanium dioxide (13463-67-7)	
Persistence and degradability	

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)	
Persistence and degradability	

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	
Persistence and degradability	

12.3. Bioaccumulative potential

Dura - Quick Dry Enamel White	
Bioaccumulative potential	No additional information available

hexane (110-54-3)	
Partition coefficient n-octanol/water (Log Kow)	≈ 4 20 °C and pH 7 - Source: ECHA

benzene (71-43-2)	
Partition coefficient n-octanol/water (Log Kow)	≈ 2.13 Temperature: 20°C Source: ECHA

Toluene (108-88-3)	
Partition coefficient n-octanol/water (Log Kow)	2.73 Source: HSDB

12.4. Mobility in soil

Dura - Quick Dry Enamel White	
Mobility in soil	No additional information available

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No additional information available

Dura - Quick Dry Enamel White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9




SECTION 13: Disposal Considerations

13.1. Disposal methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Flammable vapours may accumulate in the container. Do not re-use empty containers.

SECTION 14: Transport information

In accordance with SANS / IMDG / IATA

SANS	IMDG	IATA
14.1. UN number		
1294	1294	1294
14.2. UN Proper Shipping Name		
TOLUENE	TOLUENE	Toluene
14.3. Transport hazard class(es)		
3	3	3
		
14.4. Packing group, if applicable		
II	II	II
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available		

14.6. Special precautions for user

SANS

Limited quantities (SANS)	: 1 L
Limited quantities (SANS)	: 1 L
Packagings, large packagings and IBCs Packing instructions (SANS)	: P001, IBC02
Portable tank and bulk containers instructions (SANS)	: T4
Portable tank and bulk container special provisions (SANS)	: TP1

IMDG

Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG)	: B
Flash point (IMDG)	: 7°C c.c.

Dura - Quick Dry Enamel White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Properties and observations (IMDG) : Colourless liquid with a benzene-like odour. Flashpoint: 7°C c.c. Explosive limits: 1.27% to 7%. Immiscible with water.

IATA

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
ERG code (IATA) : 3L

14.7. Transport in bulk according to IMO instructions

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

15.1.1. OCCUPATIONAL HEALTH AND SAFETY ACT, 1993

Prohibited Hazardous Chemical Agents

Not regulated

15.2. Safety, health, and environmental national regulations specific for the product

No additional information available

SECTION 16: Other information

Issue date : 16/02/2023
Revision date : 14/08/2024
Supersedes : 14/08/2024

Full text of H-statements:

H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Dura - Quick Dry Enamel White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Full text of H-statements:

H413

May cause long lasting harmful effects to aquatic life

Safety Data Sheet (SDS), South Africa (HCA)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.