

## WEDGEWOOD OPULENT SHEEN

## WD 007

PRODUCT CODE:	White/Pastel (Wedgewood Plastic Containers)	: opshnw (05) (20)
	Deep (Wedgewood Plastic Containers)	: opshnde (05) (20)
	Transparent (Wedgewood Plastic Containers)	: opshntr (05) (20)

**PRODUCT DESCRIPTION:** *Opulent Sheen* is a long lasting premium coating with a sheen finish that is highly washable. It is ideal for high traffic areas such as passages, bedrooms, and stair wells. It is also ideal as a premium coating for exterior use. *Opulent Sheen* is water-based and non- flammable.

**INTENDED USES:** Suitable for previously primed or painted areas such as cement plaster, gypsum plaster, concrete, fibre cement, ceiling boards, unglazed brick, and steel, provided that appropriate preparation is carried out.

**FEATURES:** A pure acrylic suitable for interior and exterior use. Stain resistant. Low odour. Washable. Excellent durability. This product comes with a 7 year quality guarantee. (Subject to Terms and Conditions – [www.durapaints.co.za](http://www.durapaints.co.za))

PRODUCT INFORMATION:	• APPEARANCE	Sheen finish.
	• COLOUR	White, can be tinted
	• VOLUME SOLIDS	42% by mass (Varies by colour/base)
		31% by volume (Varies by colour/base)
	• S G @ 25°C	1.23 (Varies by colour/base)
	• RECOMMENDED DFT	MIN : 25µm MAX: 35µm
	• PRACTICAL SPREADING RATE	8 to 10 m². (dependant on substrate and application thickness (DFT)
	• VISCOSITY @ 25°C (WHITE)	100-105 KU (varies by colour/base.)

APPLICATION DETAILS:	• MIXING	Stir thoroughly with a flat paddle until homogeneous
	• METHOD	Brush, roller or airless spray
	• THINNING	Not recommended.
	• CLEANING	Water
	• SUBSTRATE	Cement plaster, concrete, fibre-cement, ceiling boards, gypsum plaster.
	• APPLICATION ENVIRONMENT	

Surface Temp	Ambient Temp	Relative Humidity
Min 10°C or 2°C above dew point	Min 10°C or 2°C above dew point	Min: 10%
Max : 40°C	Max : 40°C	Max : 85%

• DRYING TIME	Touch dry	30 Min @ 25°C
	Dry to handle	2 hours @ 25°C
	Overcoating	2 hours @ 25°

**STORAGE AND PACKAGING:**

- Store away from direct sun, heat and severe cold. Do not exceed 50°C.
- Keep containers tightly closed.
- Packaging 5lt & 20lt
- Shelf life. 12 months from date of manufacture when correctly stored and unopened.

# TECHNICAL DATA SHEET

## WEDGEWOOD OPULENT SHEEN (contd.)

### TRANSPORTATION:

SHIPPING NAME:	Not classified
PACKAGING GROUP:	Not classified
HAZARD CLASS:	4-H-C
S.I./UN NUMBER:	Not classified dangerous for transport

### SURFACE PREPARATION:

Ensure all surfaces are dry, have less than 12% moisture content and are free from algae, rust, dirt, dust, chalking, oil, grease and any other contaminant before painting.

#### Unpainted Substrate:

Cement plaster, concrete, ceiling boards, fibre cement, gypsum board.

- Prime with one coat of **Wedgewood Water Based Plaster Primer** as per instructions.
- Apply two to three coats **Wedgewood Opulent Sheen**, depending on colour.

#### **Mild Steel.**

- Degrease with **ProLong Grease Devil** and rinse thoroughly with water. Allow to dry.
- Prime with one coat **Dura Hydro Prime Grey/Biscuit**. (water based steel primer).
- Apply two to three coats **Wedgewood Opulent Sheen**, depending on colour.

#### Previously painted substrate

- Remove all loose and flaking paint by scrapping, sanding or hydro blasting - allow to dry. Clean with **ProLong ProSoap or ProLong ProSoap Liquid** to remove all contaminants. Rinse off with clean water.
- Apply two to three coats **Wedgewood Opulent Sheen**, depending on colour.
- If the surface is chalky and cannot be thoroughly cleaned, apply one coat of **Opulent Bonding Liquid**, allow to dry overnight, then apply two or three coats **Wedgewood Opulent Sheen**, depending on colour.
- Fill defects with **ProLong Crackfill** or **ProLong Profill**, as part of the preparation. Fill defects in wood with **ProLong Timberfill**
- Mould/Algae. Remove by scrubbing with a solution of 4:1 Water/Bleach or Water/Chlorine. Saturate affected areas and allow to stand for a minimum of 4 hours. Rinse off thoroughly with clean water and allow to dry before painting.

### APPLICATION:

Apply two (three coats for some low hiding colours) un-thinned to prepared surfaces so as to achieve complete obliteration. When applying with airless equipment thinning is not normally required or recommended.

### CAUTIONS:

- Avoid painting during inclement weather or if temperature is below 10°C.
- For optimum performance a practical recommended spreading rate of 8 m<sup>2</sup> / l should not be exceeded.
- It is very important to purchase sufficient paint to complete the project. Different batches may result in slight variations in colour that are beyond the control of the manufacturer.
- Do not apply to concrete or plaster substrates that contain more than 12% moisture.

# TECHNICAL DATA SHEET

## WEDGEWOOD OPULENT SHEEN (contd.)

### SAFETY PRECAUTIONS:

- Keep out of reach of children.
- Ensure good ventilation during application and drying.
- In case of skin contact, wash with soap and water or a recognized skin cleaner. Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist. If ingested give plenty of water / milk. Do not induce vomiting. Seek medical attention.
- Refer to Material Safety Data Sheet for complete information. See [www.durapaints.co.za](http://www.durapaints.co.za).

### DISCLAIMER:

- *The recommendations contained herein are given in good faith and are meant to guide the specifier or the user.*
- *They are based on results gained from our experiences and tests and are believed to be reliable.*
- *Products are manufactured to stringent specifications under laboratory controlled conditions. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control. Warranty is restricted to the replacement of defective product and excludes any direct, indirect or consequential loss of any nature howsoever caused.*
- *Technology may change necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used. See [www.durapaints.co.za](http://www.durapaints.co.za).*