

WEDGEWOOD OPULENT SIGNATURE COAT

WD008

PRODUCT CODE:	White/Pastel (Wedgewood Plastic Containers)	: opsigw (05) (20)
	Deep (Wedgewood Plastic Containers)	: opsigde (05) (20)
	Transparent (Wedgewood Plastic Containers)	: opshntr (05) (20)

PRODUCT DESCRIPTION: *Opulent Signature Coat* is a long lasting premium coating with a low sheen finish, excellent washability and opacity. It is ideal for high traffic areas such as passages, bedrooms and offices. It is also recommended as a high quality UV resistant coating for exterior surfaces. The product is water-based and non- flammable.

INTENDED USES: Suitable for previously primed or painted areas such as cement plaster, gypsum plaster, concrete, fibre cement, ceiling boards, unglazed brick, and steel, provided that appropriate preparation is carried out.

FEATURES: A pure acrylic suitable for interior and exterior use. Hides imperfections. Stain resistant. Low odour. Washable. Excellent coverage, can be used as a one coat system for ceilings. Great durability, over 1000 colours This product comes with a 7 year quality guarantee. (Subject to Terms and Conditions)

PRODUCT INFORMATION:	• APPEARANCE	Low sheen finish.
	• COLOUR	White, can be tinted
	• VOLUME SOLIDS	49% by mass (Varies by colour/base) 36% by volume (Varies by colour/base)
	• S G @ 25°C	1.31 (Varies by colour/base)
	• RECOMMENDED DFT	MIN : 25µm MAX: 35µm
	• PRACTICAL SPREADING RATE	10 - 12 m². (dependant on substrate and application thickness (DFT))
	• VISCOSITY @ 25°C (WHITE)	110-115 KU (varies by colour/base.)

APPLICATION DETAILS:	• MIXING	Stir thoroughly with a flat paddle until homogeneous
	• METHOD	Brush, roller or airless spray
	• THINNING	Not recommended.
	• CLEANING	Water
	• SUBSTRATE	Cement plaster, concrete, fibre-cement, ceiling boards, gypsum plaster.
	• APPLICATION ENVIRONMENT	

Surface Temp	Ambient Temp	Relative Humidity
Min 10°C or 2°C above dew point	Min 10°C or 2°C above dew point	Min: 10%
Max : 40°C	Max : 40°C	Max : 85%

• DRYING TIME	Touch dry	30 Min @ 25°C
	Dry to handle	2 hours @ 25°C
	Overcoating	2 hours @ 25°C

STORAGE AND PACKAGING:

- Store away from direct sun, heat and severe cold. Do not exceed 50°C.
- Keep containers tightly closed.
- Packaging 5lt & 20lt
- Shelf life. 12 months from date of manufacture when correctly stored and unopened.

TECHNICAL DATA SHEET

WEDGEWOOD OPULENT SIGNATURE COAT (cont.)

TRANSPORTATION:

SHIPPING NAME:	Not classified
PACKAGING GROUP:	Not classified
HAZARD CLASS:	4-H-C
S.I.N/UN NUMBER:	Not classified dangerous for transport

SURFACE PREPARATION:

Ensure all surfaces are dry, less than 12% moisture content, and free from rust, dirt, dust, chalking, oil, grease and any other contamination before painting.

Unpainted Substrate:

Cement plaster, concrete, ceiling boards, fibre cement, gypsum board.

- Prime with one coat **Wedgewood Opulent 2 in 1** water based primer/topcoat.
- Apply two or three coats **Wedgewood Opulent Signature Coat**, depending on colour.

Mild Steel.

- Degrease with **ProLong Grease Devil** and rinse thoroughly with water. Allow to dry.
- Prime with one coat **Dura Hydro Prime**. (water based steel primer).
- Apply two or three coats **Wedgewood Opulent Signature Coat**, depending on colour.

Previously painted substrate

- Remove all loose and flaking paint by scrapping, sanding or hydro blasting - allow to dry. Clean with **ProLong ProSoap** or **ProLong ProSoap Liquid** to remove all contaminants. Rinse off **ProLong ProSoap/ProSoap Liquid** with water.
- Apply two or three coats **Wedgewood Opulent Signature Coat**, depending on colour.
- If the surface is chalky and cannot be thoroughly cleaned, apply one coat of **Opulent Bonding Liquid**, allow to dry overnight, then apply two or three coats **Wedgewood Opulent Signature Coat**, depending on colour.
- Fill defects with ProLong **Crackfill** or **ProLong Profill**, as part of the preparation. Fill defects in wood with **ProLong Timberfill**.
- Mould/Algae. Remove by scrubbing with a solution of 4:1 Water/Bleach or Water/Chlorine. Saturate affected areas and allow to stand for a minimum of 4 hours. Rinse off thoroughly with clean water and allow to dry before painting.

APPLICATION:

Apply two (three coats for some low hiding colours) un-thinned to prepared surfaces so as to achieve complete obliteration. Thin with a minimum amount of water for conventional spray application. For airless spraying thinning is not normally required

CAUTIONS:

- Avoid painting during inclement weather or if temperature is below 10°C.
- For optimum performance a practical recommended spreading rate of 10 m² / l should not be exceeded.
- It is very important to purchase sufficient paint to complete the project. Different batches may result in slight variations in colour that are beyond the control of the manufacturer.
- Do not apply to concrete or plaster substrates that contain more than 12% moisture.

TECHNICAL DATA SHEET

WEDGEWOOD OPULENT SIGNATURE COAT (cont.)

SAFETY PRECAUTIONS:

- Keep out of reach of children.
- Ensure good ventilation during application and drying.
- In case of skin contact, wash with soap and water or a recognized skin cleaner. Avoid contact with eyes – In case of contact with eyes rinse immediately with plenty of water and seek medical advice if symptoms persist. If ingested give plenty of water / milk. Do not induce vomiting. Seek medical attention.
- Refer to Material Safety Data Sheet for complete information. See www.durapaints.co.za.

DISCLAIMER:

- *The recommendations contained herein are given in good faith and are meant to guide the specifier or the user.*
- *They are based on results gained from our experiences and tests and are believed to be reliable.*
- *No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.*
- *Technology may change necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used. See www.durapaints.co.za.*