

WEDGEWOOD OPULENT COVER COAT/CEILING PAINT

WD 009

PRODUCT CODE: White only (Wedgewood Plastic Containers) : opcovw (05)
: opcovw (20)

PRODUCT DESCRIPTION: *Opulent Cover Coat/Ceiling Paint* is an economical, smooth, white acrylic with excellent hiding power.

INTENDED USES: Good quality low odour coating, ideal for interior ceilings. Also for use as a filler coat on primed/painted, cement plastered walls or as an obliteration coat to cover existing dark colours. Specially formulated to cover in one coat for most applications.

FEATURES: Suitable for interior use. Low odour. Excellent hiding. Low roller splatter.

PRODUCT INFORMATION:

• APPEARANCE	Smooth matt finish.
• COLOUR	White.
• VOLUME SOLIDS	53% by mass 31% by volume
• S G @ 25°C	1.46 (typical)
• RECOMMENDED DFT	MIN : 30µm MAX: 40µm
• PRACTICAL SPREADING RATE	6 to 8 m². (dependant on substrate and application thickness (DFT))
• VISCOSITY @ 25°C (WHITE)	110-115 KU (typical)

APPLICATION DETAILS:

• MIXING	Stir thoroughly with a flat paddle until homogeneous
• METHOD	Brush, roller or airless spray
• THINNING	Not recommended.
• CLEANING	Water
• SUBSTRATE	Primed cement plaster and ceilings.
• APPLICATION ENVIRONMENT	

Surface Temp	Ambient Temp	Relative Humidity
Min 10°C or 2°C above dew point	Min 10°C or 2°C above dew point	Min: 10%
Max : 40°C	Max : 40°C	Max : 85%

• DRYING TIME	Touch dry	30 Min @ 25°C
	Dry to handle	1 hour @ 25°C
	Overcoating	1 hour @ 25°C

STORAGE AND PACKAGING:

- Store away from direct sun, heat and severe cold. Do not exceed 50°C.
- Keep containers tightly closed.
- Packaging 5lt & 20lt
- Shelf life. 12 months from date of manufacture when correctly stored and unopened.

TRANSPORTATION:

SHIPPING NAME: Not classified
PACKAGING GROUP: Not classified
HAZARD CLASS: 4-H-C
S.I.N/UN NUMBER: Not classified dangerous for transport

WEDGEWOOD OPULENT COVER COAT/CEILING PAINT (contd.)

SURFACE PREPARATION:

Ensure all surfaces are dry, less than 12% moisture content, and free from dirt, dust, chalking, oil, grease and other contaminants before painting.

Unpainted Substrate:

Cement plaster.

- Apply one coat *Wedgewood Opulent 2 in 1 or Opulent Plaster Primer*, then overcoat with **one coat of Opulent Cover Coat/Ceiling Paint**. Top coat with appropriate *Opulent product*.

Ceiling.

- Apply one or two coats of *Opulent Cover Coat / Ceiling paint*.

Previously painted substrate

- Remove all loose and flaking paint by scrapping, sanding or hydro blasting - allow to dry. Clean with *ProLong ProSoap or ProLong ProSoap Liquid* to remove all contaminants. Rinse off *ProLong ProSoap/ProSoap Liquid* with water.
- Apply one coat *Wedgewood Opulent Cover Coat/Ceiling Paint*, then overcoat with **appropriate Wedgewood product**.
- If the surface is chalky and cannot be thoroughly cleaned, apply one coat of *Opulent Bonding Liquid*, allow to dry overnight, then apply one coat *Wedgewood Opulent Cover Coat/Ceiling Paint* and over coat with appropriate *Wedgewood product*.
- Fill defects with *ProLong Crackfill* or *ProLong Profill*, as part of the preparation.
- Mould/Algae. Remove by scrubbing with a solution of 4:1 Water/Bleach or Water/Chlorine. Saturate affected areas and allow to stand for a minimum of 4 hours. Rinse off thoroughly with clean water and allow to dry before painting.

APPLICATION:

Apply one or two coats un-thinned to prepared surfaces so as to achieve complete obliteration. Thin with a minimum amount of water for conventional spray application. For airless spraying thinning is not normally required. To achieve best obliteration in one coat a (WFT) wet film thickness of 100µ should be applied.

CAUTIONS:

- Avoid painting during inclement weather or if temperature is below 10°C.
- For optimum performance a practical recommended spreading rate of 6 m² / l should not be exceeded.
- For interior ceilings only.

SAFETY PRECAUTIONS:

- Keep out of reach of children.
- Ensure good ventilation during application and drying.
- In case of skin contact, wash with soap and water or a recognized skin cleaner. Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist. If ingested give plenty of water / milk. Do not induce vomiting. Seek medical attention.
- Refer to Material Safety Data Sheet for complete information. See www.durapaints.co.za.

WEDGEWOOD OPULENT COVER COAT/CEILING PAINT (contd.)

DISCLAIMER:

- *The recommendations contained herein are given in good faith and are meant to guide the specifier or the user.*
- *They are based on results gained from our experiences and tests and are believed to be reliable.*
- *No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.*
- *Technology may change necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used. See www.durapaints.co.za.*