TRANSPORT EMERGENCY CARD Road transport

In accordance with SANS 10232-4

PROPER SHIPPING NAME

PETROLEUM DISTILLATES, N.O.S.

UN-No. 1268 Class 3 Subsidiary risk Packing group III ERG No. 128

APPEARANCE

Liquid

Clear, colorless liquid

Colourless

Aromatic solvent like odour

DANGER

HIGHLY FLAMMABLE LIQUID & VAPOUR: Easily ignited by heat, sparks or flames

Vapour could travel to source of ignition and flash back

Vapours may cause drowsiness and dizziness

Contact could be irritating to skin and eyes

Fire could produce a combination of irritating and corrosive gases

PERSONAL PROTECTIVE EQUIPMENT

Evewash bottle with clean water

Light protective clothing

Protective gloves

Protective goggles or face shield

Protective shoes

EMERGENCY RESPONSE EQUIPMENT

Use clean non-sparking tools to collect absorbed material

Broom

Dry chemical or CO2, or water spray

Positive pressure self-contained breathing apparatus (SCBA)

DRIVER FIRST ACTIONS - Only if it can be carried out without personal risk

Stop the engine

Warn road users and passers by to keep away from danger area

Keep upwind

Contact the emergency services

No smoking allowed

DRIVER SPECIAL ACTIONS - Only if it can be carried out without personal risk

Contain or absorb spilled liquid with earth or other absorbent material

Avoid sparks

Prevent runoff from entering water courses, sewers and basements

Notify authorities if product enters sewers or public waters

DRIVER ACTIONS IN CASE OF FIRE - Only if it can be carried out without personal risk

Use fire extinguisher on small fire only if it can be done without personal risk; Do not attempt to deal with any major fire that involves the load

FIRST AID

Give first-aid treatment according to the nature of the injury

Immediately remove contaminated clothing or footwear

In case of contact with substance, immediately flush skin or eyes (or both) with running water for at least 20 min

Do not delay care and transport of a seriously injured person

Effects of contact or inhalation might be delayed

SPECIAL INFORMATION FOR EMERGENCY SERVICES

Cool containers with flooding quantities of water until well after fire is out

Do not use straight streams

Use dry chemical, CO2, water spray or regular foam

Dyke fire control water for later disposal

ADDITIONAL INFORMATION

Product name: Dura - Autocote Thinners **Trade name:** Dura - Autocote Thinners

Supplier: Dura Paints (Pty) Ltd., 5 Wakefield Road; , 1610 Johannesburg

Emergency telephone number: 079 494 2731 / 011 452 5221

Prepared by Dura Paints (Pty) Ltd. from the best knowledge currently available; no guarantee is provided that the

information is sufficient or correct under all circumstances.

Preparation date