

Prolong - Cement Grout - White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10
Issue date: 9/26/2023 Revision date: 7/20/2026 Supersedes: 8/25/2025 Version: 1.2

SECTION 1: Identification of the substance/mixture and of the supplier/undertaking

1.1. GHS product identifier

Product form	: Mixture
Trade name	: Prolong - Cement Grout - White
Type of product	: adhesives
Product code	: PLCEMGRO
Product group	: Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use	: Tile Grout
-----------------	--------------

1.4. Supplier's details

Manufacturer

Dura Paints (Pty) Ltd.
5 Wakefield Road; Founders View South.
P.O. Box 303
1610 Edenvale; Johannesburg – South Africa
T 011 452 5221
orders@durapaints.co.za - www.durapaints.co.za

1.5. Emergency phone number

Emergency number	: 079 494 2731 / 011 452 5221
------------------	-------------------------------

SECTION 2: Hazard identification

2.1. GHS classification of the substance/mixture and any national or regional information

Classification according to the United Nations GHS

Skin corrosion/irritation, Category 1	H314
Serious eye damage/eye irritation, Category 1	H318
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 1	H350
Specific target organ toxicity – Single exposure, Category 3,	H335
Respiratory tract irritation	
Specific target organ toxicity – Repeated exposure, Category 2	H373

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects	: May cause cancer, May cause damage to organs through prolonged or repeated exposure, May cause respiratory irritation, Causes severe skin burns and eye damage, May cause an allergic skin reaction, Causes serious eye damage.
---	---

2.2. GHS label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS ZA)



Signal word (GHS ZA)	: Danger
Hazardous ingredients	: Portland Cement; Diiron trioxide; calcium oxide; Quartz (SiO ₂)
Hazard statements (GHS ZA)	: H314 - Causes severe skin burns and eye damage H317 - May cause an allergic skin reaction

Prolong - Cement Grout - White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

	H335 - May cause respiratory irritation H350 - May cause cancer (Inhalation) H373 - May cause damage to organs (Respiratory tract) through prolonged or repeated exposure (Inhalation)
Precautionary statements (GHS ZA)	: P101 - If medical advice is needed, have product container or label and product safety data sheet at hand. P102 - Keep out of reach of children. P103 - Read carefully and follow all instructions. P260 - Do not breathe dusts or mists. P264 - Wash hands, forearms and face thoroughly after handling. P280 - Wear eye protection, protective clothing, protective gloves. P302+P352 - IF ON SKIN: Wash with plenty of soap and water P305+P354+P338 - IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention P501 - Dispose of container to recycling, according to local regulations.
P-statements for label (GHS-ZA)	: P101 - If medical advice is needed, have product container or label and product safety data sheet at hand.; P102 - Keep out of reach of children.; P103 - Read carefully and follow all instructions.; P260 - Do not breathe dusts or mists.; P264 - Wash hands, forearms and face thoroughly after handling.; P280 - Wear eye protection, protective clothing, protective gloves.; P302+P352 - IF ON SKIN: Wash with plenty of soap and water; P305+P354+P338 - IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.; P333+P313 - If skin irritation or rash occurs: Get medical advice/attention; P501 - Dispose of container to recycling, according to local regulations.

2.3. Other hazards which do not result in classification or are not covered by the GHS

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to the United Nations GHS
Portland Cement	CAS-No.: 65997-15-1	15 – 57	Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 STOT SE 3, H335
Diiron trioxide	CAS-No.: 1309-37-1	0.3 – 9	Acute Tox. Not classified (Oral) Acute Tox. Not classified (Inhalation:dust,mist) Eye Irrit. 2, H319 STOT RE 2, H373 Aquatic Chronic 2, H411
Calcium sulfate	CAS-No.: 7778-18-9	0.3 – 6	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 STOT RE Not classified

Prolong - Cement Grout - White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Name	Product identifier	%	Classification according to the United Nations GHS
calcium oxide	CAS-No.: 1305-78-8	0.3 – 3	Acute Tox. 4 (Oral), H302 Acute Tox. Not classified (Inhalation:dust,mist) Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT RE Not classified Aquatic Chronic Not classified
Quartz (SiO ₂)	CAS-No.: 14808-60-7	0.3 – 3	Carc. 1, H350

SECTION 4: First aid measures

4.1. Description of necessary first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.
Self protection of the first-aider	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effect, acute and delayed

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective actions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

Prolong - Cement Grout - White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
- 6.1.1. For non-emergency personnel**
- Protective equipment : Wear recommended personal protective equipment.
- Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapours/spray.
- 6.1.2. For emergency responders**
- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Evacuate non-essential personnel.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

- For containment : Using a clean shovel, put the material in a dry container and cover without compressing it.
- Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Wear personal protective equipment. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
- Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep in a cool, well-ventilated place away from heat.
- Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed.
- Packaging materials : Always store product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Portland Cement (65997-15-1)

South Africa - Occupational Exposure Limits (Restricted Limits)

Local name	Portland cement
RHCA - STEL/C	10 mg/m ³ total inhalable dust 5 mg/m ³ respirable dust

Prolong - Cement Grout - White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Portland Cement (65997-15-1)	
Regulatory reference	Government Notice. R: 1179
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Portland cement
OEL TWA	10 mg/m ³ inhalable particulate 5 mg/m ³ respirable particulate
Regulatory reference	Government Notice No. R 904
Diiron trioxide (1309-37-1)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Iron oxide fume
RHCA - STEL/C	10 mg/m ³ (R: respirable fraction) [as Fe]
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Iron oxide
OEL TWA	5 mg/m ³ dust and fume [as Fe]
OEL STEL	10 mg/m ³ dust and fume [as Fe]
Regulatory reference	Government Notice No. R 904
Calcium sulfate (7778-18-9)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Calcium sulphate [including plaster of Paris and gypsum]
RHCA - STEL/C	10 mg/m ³ (I: inhalable fraction)
Regulatory reference	Government Notice No. R. 280, 2021
calcium oxide (1305-78-8)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Calcium oxide
RHCA - STEL/C	4 mg/m ³
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Calcium oxide
OEL TWA	2 mg/m ³
Regulatory reference	Government Notice No. R 904
Quartz (SiO₂) (14808-60-7)	
South Africa - Occupational Exposure Limits (Maximum Limits)	
Local name	Silica, crystalline: Quartz
RHCA - STEL/C	0.1 mg/m ³ (R: Respirable fraction)
Remark	CARC (denotes carcinogenicity, which is based on GHS categorisation, including category 1A and 1B)
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Quartz, crystalline
RHCA - STEL/C	0.4 mg/m ³ respirable dust

Prolong - Cement Grout - White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Quartz (SiO ₂) (14808-60-7)	
Regulatory reference	Government Notice. R: 1179
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Quartz (Silica, crystalline)
OEL TWA	0 mg/m ³ respirable particulate
Regulatory reference	Government Notice No. R 904

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: [In case of inadequate ventilation] wear respiratory protection.
Personal protective equipment symbol(s)	



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Solid
Appearance	: Powder.
Colour	: white
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Flammability	: Non flammable
Vapour pressure	: No data available
Vapour pressure at 50°C	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: ≈ 2.95
Relative density of saturated gas/air mixture	: No data available
Density	: No data available
Relative gas density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: Not applicable

Prolong - Cement Grout - White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: Not applicable
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Physical state	: Solid
Appearance	: Powder.

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10: Stability and Reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical Stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Diiron trioxide (1309-37-1)	
LD50 oral	> 5000 mg/kg bodyweight Animal: , Guideline: EU Method B.1 (Acute Toxicity (Oral))
LC50 Inhalation - Rat	> 5 mg/l Source: ECHA
Calcium sulfate (7778-18-9)	
LD50 oral rat	> 1581 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LC50 Inhalation - Rat	> 3.26 mg/l/4h Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
calcium oxide (1305-78-8)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))

Prolong - Cement Grout - White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

calcium oxide (1305-78-8)	
LC50 Inhalation - Rat (Dust/Mist)	> 6.04 mg/l/4h Animal: rat, Guideline: OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class Method)
Skin corrosion/irritation	: Causes severe skin burns.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer (Inhalation).
Calcium sulfate (7778-18-9)	
NOAEL (chronic, oral, animal/male, 2 years)	256 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: other:
NOAEL (chronic, oral, animal/female, 2 years)	284 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:
Quartz (SiO₂) (14808-60-7)	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.
Portland Cement (65997-15-1)	
STOT-single exposure	May cause respiratory irritation.
calcium oxide (1305-78-8)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs (Respiratory tract) through prolonged or repeated exposure (Inhalation).
Diiron trioxide (1309-37-1)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.2102 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
NOAEL (oral, rat, 28 days)	> 1000 mg/kg bodyweight/day Source: ECHA
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	≥ 0.03 mg/l air Animal: rat, Animal sex: male
STOT-repeated exposure	May cause damage to organs (respiratory system) through prolonged or repeated exposure (Inhalation).
Calcium sulfate (7778-18-9)	
LOAEL (oral, rat, 90 days)	237 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (oral, rat, 28 days)	> 79 – < 790 mg/kg bodyweight/day Source: ECHA
calcium oxide (1305-78-8)	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Aspiration hazard	: Not classified
Prolong - Cement Grout - White	
Viscosity, kinematic	Not applicable

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

Prolong - Cement Grout - White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Diiron trioxide (1309-37-1)	
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	> 100 mg/l Test organisms (species):
EC50 72h - Algae [1]	> 20 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC chronic fish	≈ 20 mg/l Source: ECHA
NOEC chronic algae	≈ 20 mg/l Source: ECHA

Calcium sulfate (7778-18-9)	
LC50 - Fish [1]	> 79 mg/l Test organisms (species): Oryzias latipes
EC50 72h - Algae [1]	> 79 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
ErC50 algae	> 79 mg/l Source: ECHA

calcium oxide (1305-78-8)	
LC50 - Fish [1]	50.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	49.1 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	184.57 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	32 mg/l Test organisms (species): Crangon septemspinosus Duration: '14 d'
NOEC chronic algae	≈ 48 mg/l Freshwater algae; Source: ECHA

12.2. Persistence and degradability

Prolong - Cement Grout - White	
Persistence and degradability	Rapidly degradable

Portland Cement (65997-15-1)	
Persistence and degradability	

Diiron trioxide (1309-37-1)	
Persistence and degradability	

Calcium sulfate (7778-18-9)	
Persistence and degradability	

calcium oxide (1305-78-8)	
Persistence and degradability	

Quartz (SiO ₂) (14808-60-7)	
Persistence and degradability	

12.3. Bioaccumulative potential

Prolong - Cement Grout - White	
Bioaccumulative potential	No additional information available

Prolong - Cement Grout - White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

12.4. Mobility in soil

Prolong - Cement Grout - White

Mobility in soil	No additional information available
------------------	-------------------------------------

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No additional information available

SECTION 13: Disposal Considerations

13.1. Disposal methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Comply with applicable regulations for solid waste disposal. Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

SECTION 14: Transport information

In accordance with SANS / UN RTDG / IMDG / IATA

SANS	UN RTDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. UN Proper Shipping Name			
Not applicable	Not applicable	Not applicable	Not applicable
Transport document description			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group, if applicable			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available			

14.6. Special precautions for user

SANS

No data available

UN RTDG

No data available

IMDG

No data available

Prolong - Cement Grout - White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

IATA

No data available

14.7. Transport in bulk according to IMO instructions

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

15.1.1. OCCUPATIONAL HEALTH AND SAFETY ACT, 1993

Prohibited Hazardous Chemical Agents

Not regulated

15.1.2. National Environmental Management Act, 1998

Regulation No. 51358 (Prior Informed Consent Procedure Regulations, 2024)

Not regulated

15.2. Safety, health, and environmental national regulations specific for the product

State or local regulations : This product complies with South African legal lead limit of 90ppm or less.

SECTION 16: Other information

Issue date : 26/09/2023
Revision date : 20/07/2026
Supersedes : 25/08/2025

Full text of H-statements:	
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H350	May cause cancer
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), South Africa (HCA)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.