

Prolong - Crackfill White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10
Issue date: 7/25/2022 Revision date: 7/21/2026 Supersedes: 7/30/2024 Version: 7.1

SECTION 1: Identification of the substance/mixture and of the supplier/undertaking

1.1. GHS product identifier

Product form	: Mixture
Trade name	: Prolong - Crackfill White
Substance type	: Mixture of mineral powders
Type of product	: Filler
Product code	: PLCRACKFILLW
Product group	: Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use	: Filler for patching holes and cracks in most interior and exterior surfaces
-----------------	---

1.4. Supplier's details

Manufacturer

Dura Paints (Pty) Ltd.
5 Wakefield Road; Founders View South.
P.O. Box 303
1610 Edenvale; Johannesburg – South Africa
T 011 452 5221
orders@durapaints.co.za - www.durapaints.co.za

1.5. Emergency phone number

Emergency number	: 079 494 2731 / 011 452 5221
------------------	-------------------------------

SECTION 2: Hazard identification

2.1. GHS classification of the substance/mixture and any national or regional information

Classification according to the United Nations GHS

Acute toxicity (dermal), Category 4	H312
Skin corrosion/irritation, Category 1	H314
Serious eye damage/eye irritation, Category 1	H318
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 1	H350
Specific target organ toxicity – Single exposure, Category 3,	H335
Respiratory tract irritation	
Specific target organ toxicity – Repeated exposure, Category 2	H373
Hazardous to the aquatic environment – Acute Hazard Not classified	

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects	: May cause damage to organs through prolonged or repeated exposure, May cause respiratory irritation, Causes severe skin burns and eye damage, May cause an allergic skin reaction, Causes serious eye damage.
---	---

2.2. GHS label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS ZA)



Prolong - Crackfill White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Signal word (GHS ZA)	: Danger
Hazardous ingredients	: Magnesium oxide; calcium oxide; Quartz (SiO ₂); Silicon dioxide; Portland Cement; Diiron trioxide; Calcium sulfate
Hazard statements (GHS ZA)	: H312 - Harmful in contact with skin H314 - Causes severe skin burns and eye damage H317 - May cause an allergic skin reaction H335 - May cause respiratory irritation H350 - May cause cancer (Inhalation) H373 - May cause damage to organs (Respiratory tract) through prolonged or repeated exposure (Inhalation)
Precautionary statements (GHS ZA)	: P101 - If medical advice is needed, have product container or label and product safety data sheet at hand. P102 - Keep out of reach of children. P103 - Read carefully and follow all instructions. P260 - Do not breathe dusts or mists. P264 - Wash hands, forearms and face thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear eye protection, protective gloves, protective clothing. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention P363 - Wash contaminated clothing before reuse. P501 - Dispose of container to recycling, according to local regulations.
P-statements for label (GHS-ZA)	: P101 - If medical advice is needed, have product container or label and product safety data sheet at hand.; P102 - Keep out of reach of children.; P103 - Read carefully and follow all instructions.; P260 - Do not breathe dusts or mists.; P264 - Wash hands, forearms and face thoroughly after handling.; P271 - Use only outdoors or in a well-ventilated area.; P280 - Wear eye protection, protective gloves, protective clothing.; P333+P313 - If skin irritation or rash occurs: Get medical advice/attention; P363 - Wash contaminated clothing before reuse.; P501 - Dispose of container to recycling, according to local regulations.

2.3. Other hazards which do not result in classification or are not covered by the GHS

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to the United Nations GHS
Silicon dioxide	CAS-No.: 7631-86-9	35 – 55	Acute Tox. 4 (Dermal), H312 Acute Tox. Not classified (Inhalation:dust,mist) STOT RE Not classified Aquatic Acute Not classified Aquatic Chronic Not classified
Portland Cement	-	10 – 28.5	Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 STOT SE 3, H335
Calcium carbonate	CAS-No.: 471-34-1	9.5 – 19	Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr./Irrit. Not classified STOT RE Not classified Aquatic Chronic Not classified

Prolong - Crackfill White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Name	Product identifier	%	Classification according to the United Nations GHS
Diiron trioxide	CAS-No.: 1309-37-1	0.2 – 4.5	Acute Tox. Not classified (Oral) Acute Tox. Not classified (Inhalation:dust,mist) Eye Irrit. 2, H319 STOT RE 2, H373 Aquatic Chronic 2, H411
Calcium sulfate	CAS-No.: 7778-18-9	0.2 – 3	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 STOT RE Not classified
calcium oxide	CAS-No.: 1305-78-8	0.2 – 1.5	Acute Tox. 4 (Oral), H302 Acute Tox. Not classified (Inhalation:dust,mist) Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT RE Not classified Aquatic Chronic Not classified
Quartz (SiO ₂)	CAS-No.: 14808-60-7	0.2 – 1.5	Carc. 1, H350

SECTION 4: First aid measures

4.1. Description of necessary first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.
Self protection of the first-aiders	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effect, acute and delayed

Symptoms/effects after inhalation	: Adverse symptoms may include nausea or vomiting, headache, respiratory irritation. May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes severe skin burns. Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Adverse symptoms may include pain, irritation, watering and redness. Serious damage to eyes.
Symptoms/effects after ingestion	: Harmful if swallowed. May cause damage to organs through prolonged or repeated exposure. Burns.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard.
-------------	-------------------

Prolong - Crackfill White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective actions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate non-essential personnel.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

For containment	: Using a clean shovel, put the material in a dry container and cover without compressing it.
Methods for cleaning up	: Mechanically recover the product.
Other information	: Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Packaging materials	: Always store product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

calcium oxide (1305-78-8)

South Africa - Occupational Exposure Limits (Restricted Limits)

Local name	Calcium oxide
------------	---------------

Prolong - Crackfill White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

calcium oxide (1305-78-8)	
RHCA - STEL/C	4 mg/m ³
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Calcium oxide
OEL TWA	2 mg/m ³
Regulatory reference	Government Notice No. R 904
Quartz (SiO₂) (14808-60-7)	
South Africa - Occupational Exposure Limits (Maximum Limits)	
Local name	Silica, crystalline: Quartz
RHCA - STEL/C	0.1 mg/m ³ (R: Respirable fraction)
Remark	CARC (denotes carcinogenicity, which is based on GHS categorisation, including category 1A and 1B)
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Quartz, crystalline
RHCA - STEL/C	0.4 mg/m ³ respirable dust
Regulatory reference	Government Notice. R: 1179
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Quartz (Silica, crystalline)
OEL TWA	0 mg/m ³ respirable particulate
Regulatory reference	Government Notice No. R 904
Silicon dioxide (7631-86-9)	
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Silica, amorphous
OEL TWA	6 mg/m ³ inhalable particulate 3 mg/m ³ respirable particulate
Regulatory reference	Government Notice No. R 904
Portland Cement	
South Africa - Occupational Exposure Limits (Restricted Limits)	
RHCA - STEL/C	10 mg/m ³ total inhalable dust 5 mg/m ³ respirable dust
Regulatory reference	Government Notice. R: 1179
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
OEL TWA	10 mg/m ³ inhalable particulate 5 mg/m ³ respirable particulate
Regulatory reference	Government Notice No. R 904
Diiron trioxide (1309-37-1)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Iron oxide fume
RHCA - STEL/C	10 mg/m ³ (R: respirable fraction) [as Fe]
Regulatory reference	Government Notice No. R. 280, 2021

Prolong - Crackfill White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Diiron trioxide (1309-37-1)

South Africa - Occupational Exposure Limits (Airborne Pollutants)

Local name	Iron oxide
OEL TWA	5 mg/m ³ dust and fume [as Fe]
OEL STEL	10 mg/m ³ dust and fume [as Fe]
Regulatory reference	Government Notice No. R 904

Calcium sulfate (7778-18-9)

South Africa - Occupational Exposure Limits (Restricted Limits)

Local name	Calcium sulphate [including plaster of Paris and gypsum]
RHCA - STEL/C	10 mg/m ³ (I: inhalable fraction)
Regulatory reference	Government Notice No. R. 280, 2021

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment
Personal protective equipment symbol(s)	



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Solid
Appearance	: Fine white powder.
Colour	: White
Odour	: Odourless
Odour threshold	: No data available
pH	: No data available
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Flammability	: Non flammable
Vapour pressure	: No data available
Vapour pressure at 50°C	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: ≈ 2.7

Prolong - Crackfill White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Relative density of saturated gas/air mixture	: No data available
Density	: No data available
Relative gas density	: No data available
Solubility	: Miscible.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: Not applicable
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Physical state	: Solid
Appearance	: Fine white powder.

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10: Stability and Reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical Stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Likely routes of exposure : Ingestion. Inhalation. Dermal.

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Causes severe skin burns and eye damage.
Acute toxicity (inhalation)	: Adverse symptoms may include nausea or vomiting, headache, respiratory irritation

Prolong - Crackfill White	
ATE ZA (Dermal)	2000 mg/kg bodyweight
calcium oxide (1305-78-8)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))

Prolong - Crackfill White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

calcium oxide (1305-78-8)	
LC50 Inhalation - Rat (Dust/Mist)	> 6.04 mg/l/4h Animal: rat, Guideline: OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class Method)
Silicon dioxide (7631-86-9)	
LD50 oral rat	3160 mg/kg Source: TOMES; HAZARTEXT
LD50 dermal rat	≥ 2000 mg/kg bodyweight Source: ECHA
LD50 dermal rabbit	> 5000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Dust/Mist)	5.01 mg/l Source: ECHA
Calcium carbonate (471-34-1)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LC50 Inhalation - Rat	> 3 mg/l/4h Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
Diiron trioxide (1309-37-1)	
LD50 oral	> 5000 mg/kg bodyweight Animal: , Guideline: EU Method B.1 (Acute Toxicity (Oral))
LC50 Inhalation - Rat	> 5 mg/l Source: ECHA
Calcium sulfate (7778-18-9)	
LD50 oral rat	> 1581 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LC50 Inhalation - Rat	> 3.26 mg/l/4h Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
Skin corrosion/irritation	: Causes severe skin burns.
Prolong - Crackfill White	
Additional information	Causes severe skin burns
Serious eye damage/irritation	: Causes serious eye burns
Respiratory or skin sensitization	: Adverse symptoms may include nausea or vomiting, headache, respiratory irritation
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer (Inhalation).
Quartz (SiO2) (14808-60-7)	
IARC group	1 - Carcinogenic to humans
Silicon dioxide (7631-86-9)	
IARC group	3 - Not classifiable
Calcium sulfate (7778-18-9)	
NOAEL (chronic, oral, animal/male, 2 years)	256 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: other:
NOAEL (chronic, oral, animal/female, 2 years)	284 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:
Reproductive toxicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.
calcium oxide (1305-78-8)	
STOT-single exposure	May cause respiratory irritation.

Prolong - Crackfill White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Portland Cement	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs (Respiratory tract) through prolonged or repeated exposure (Inhalation).
calcium oxide (1305-78-8)	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Silicon dioxide (7631-86-9)	
NOAEL (oral, rat, 28 days)	> 2500 mg/kg bodyweight/day Source: ECHA
NOAEC (inhalation, rat, 28 days)	> 1.3 – < 46 mg/l Source: ECHA
Calcium carbonate (471-34-1)	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	≥ 0.212 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (subchronic, oral, animal/male, 90 days)	> 1000 mg/kg bodyweight/day Source: ECHA
Diiron trioxide (1309-37-1)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.2102 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
NOAEL (oral, rat, 28 days)	> 1000 mg/kg bodyweight/day Source: ECHA
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	≥ 0.03 mg/l air Animal: rat, Animal sex: male
STOT-repeated exposure	May cause damage to organs (respiratory system) through prolonged or repeated exposure (Inhalation).
Calcium sulfate (7778-18-9)	
LOAEL (oral, rat, 90 days)	237 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (oral, rat, 28 days)	> 79 – < 790 mg/kg bodyweight/day Source: ECHA
Aspiration hazard	: Not classified
Prolong - Crackfill White	
Viscosity, kinematic	Not applicable

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Before neutralisation, the product may represent a danger to aquatic organisms.
Hazardous to the aquatic environment, short-term (acute)	: Not classified.
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

calcium oxide (1305-78-8)	
LC50 - Fish [1]	50.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	49.1 mg/l Test organisms (species): Daphnia magna

Prolong - Crackfill White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

calcium oxide (1305-78-8)	
EC50 72h - Algae [1]	184.57 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	32 mg/l Test organisms (species): Crangon septemspinosa Duration: '14 d'
NOEC chronic algae	≈ 48 mg/l Freshwater algae; Source: ECHA
Silicon dioxide (7631-86-9)	
LC50 - Fish [1]	10000 mg/l Source: ECHA
EC50 - Crustacea [1]	> 5000 mg/l Source: ECHA
EC50 72h - Algae [1]	> 173.1 mg/l Source: ECHA
EC50 96h - Algae [1]	> 217.576 – < 217.6 mg/l Source: ECHA
LOEC (chronic)	≈ 149.2 mg/l Source: ECHA
NOEC (chronic)	> 68 – < 250 mg/l 21 days; Source: ECHA
NOEC chronic fish	> 57.001 – < 86.03 mg/l Source: ECHA
NOEC chronic algae	> 42.1 – < 42.11 mg/l Source: ECHA
Calcium carbonate (471-34-1)	
EC50 72h - Algae [1]	≈ 14 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC chronic algae	≈ 14 mg/l Source: ECHA
Diiron trioxide (1309-37-1)	
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	> 100 mg/l Test organisms (species):
EC50 72h - Algae [1]	> 20 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC chronic fish	≈ 20 mg/l Source: ECHA
NOEC chronic algae	≈ 20 mg/l Source: ECHA
Calcium sulfate (7778-18-9)	
LC50 - Fish [1]	> 79 mg/l Test organisms (species): Oryzias latipes
EC50 72h - Algae [1]	> 79 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
ErC50 algae	> 79 mg/l Source: ECHA
12.2. Persistence and degradability	
Prolong - Crackfill White	
Persistence and degradability	Rapidly degradable
calcium oxide (1305-78-8)	
Persistence and degradability	
Quartz (SiO2) (14808-60-7)	
Persistence and degradability	
Silicon dioxide (7631-86-9)	
Persistence and degradability	

Prolong - Crackfill White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Calcium carbonate (471-34-1)	
Persistence and degradability	
Portland Cement	
Persistence and degradability	
Diiron trioxide (1309-37-1)	
Persistence and degradability	
Calcium sulfate (7778-18-9)	
Persistence and degradability	

12.3. Bioaccumulative potential

Prolong - Crackfill White	
Bioaccumulative potential	No additional information available
Silicon dioxide (7631-86-9)	
Partition coefficient n-octanol/water (Log Kow)	≈ 0.53 @ 25 °C and pH 7; Source: ECHA

12.4. Mobility in soil

Prolong - Crackfill White	
Mobility in soil	No additional information available

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No additional information available

SECTION 13: Disposal Considerations

13.1. Disposal methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Comply with applicable regulations for solid waste disposal. Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

SECTION 14: Transport information

In accordance with SANS / UN RTDG / IMDG / IATA

SANS	UN RTDG	IMDG	IATA
14.1. UN number			
3066	Not applicable	3066	3066
14.2. UN Proper Shipping Name			
PAINT PAINT RELATED MATERIAL	Not applicable	PAINT RELATED MATERIAL	Paint related material
Transport document description			
Not applicable	Not applicable	UN 3066 PAINT RELATED MATERIAL, 8, III	UN 3066 Paint related material, 8, III

Prolong - Crackfill White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

SANS	UN RTDG	IMDG	IATA
14.3. Transport hazard class(es)			
8	Not applicable	8	8
	Not applicable		
14.4. Packing group, if applicable			
III	Not applicable	III	III
14.5. Environmental hazards			
Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available			

14.6. Special precautions for user

SANS

Special provisions (SANS) : 163, 223
Limited quantities (SANS) : 5 L
Excepted quantities (SANS) : E1
Packagings, large packagings and IBCs Packing instructions (SANS) : P001, IBC03
Portable tank and bulk containers instructions (SANS) : T4
Portable tank and bulk container special provisions (SANS) : TP1, TP29

UN RTDG

No data available

IMDG

Special provisions (IMDG) : 163, 223, 367
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage) : S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES
Stowage category (IMDG) : A
Stowage and handling (IMDG) : SW2
Properties and observations (IMDG) : Corrosive content. Causes burns to skin, eyes and mucous membranes.

IATA

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y841
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 852
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 856
CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A3, A72, A192, A803
ERG code (IATA) : 8L

14.7. Transport in bulk according to IMO instructions

Not applicable

Prolong - Crackfill White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

SECTION 15: Regulatory information

15.1. National regulations

15.1.1. OCCUPATIONAL HEALTH AND SAFETY ACT, 1993

Prohibited Hazardous Chemical Agents

Not regulated

15.1.2. National Environmental Management Act, 1998

Regulation No. 51358 (Prior Informed Consent Procedure Regulations, 2024)

Not regulated

15.2. Safety, health, and environmental national regulations specific for the product

State or local regulations : This product complies with South African legal lead limit of 90ppm or less.

SECTION 16: Other information

Issue date : 25/07/2022
Revision date : 21/07/2026
Supersedes : 30/07/2024

Section	Changed item	Comments
	Supersedes	Modified
	Limited quantities (IMDG)	Added
	Stowage and handling (IMDG)	Added
	Tank special provisions (IMDG)	Added
	Tank instructions (IMDG)	Added
	IBC packing instructions (IMDG)	Added
	Excepted quantities (IMDG)	Added
	Special provisions (IATA)	Modified
	CAO max net quantity (IATA)	Modified
	CAO packing instructions (IATA)	Modified
	PCA max net quantity (IATA)	Modified
	PCA packing instructions (IATA)	Modified
	PCA limited quantity max net quantity (IATA)	Modified
	PCA Limited quantities (IATA)	Modified
	Proper Shipping Name (IATA)	Modified
	Properties and observations (IMDG)	Modified
	Proper Shipping Name (IMDG)	Modified
	Stowage category (IMDG)	Modified
	Special provisions (IMDG)	Modified
	Packagings, large packagings and IBCs Special packing instructions (SANS)	Removed
	Portable tank and bulk container special provisions (SANS)	Modified

Prolong - Crackfill White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Section	Changed item	Comments
	Portable tank and bulk containers instructions (SANS)	Modified
	Packagings, large packagings and IBCs Packing instructions (SANS)	Modified
	Special provisions (SANS)	Modified
	Limited quantities (SANS)	Modified
	Proper Shipping Name (SANS)	Modified
	EmS-No. (Fire)	Added
	EmS-No. (Spillage)	Added
	Revision date	Modified
	UN-No.(SANS)	Modified
1.2	Use of the substance/mixture	Removed
2.1	Adverse physicochemical, human health and environmental effects	Modified
3	Composition/information on ingredients	Modified
4	Symptoms/effects after ingestion	Added
4	Symptoms/effects after skin contact	Modified
4	First-aid measures after skin contact	Modified
4	First-aid measures general	Modified
4	First-aid measures after ingestion	Modified
5.1	Unsuitable extinguishing media	Added
5.2	Explosion hazard	Added
5.2	Fire hazard	Added
5.3	Firefighting instructions	Added
6	For containment	Added
6	Emergency procedures	Added
6	Protective equipment	Added
6	General measures	Added
7.1	Additional hazards when processed	Added
7.2	Packaging materials	Added
7.2	Storage conditions	Modified
7.2	Technical measures	Added
8.2	Personal protective equipment	Added
9	Freezing point	Modified
9	Relative density	Modified
12.1	Ecology - general	Modified
13	Product/Packaging disposal recommendations	Added
13	Sewage disposal recommendations	Added
13	Additional information	Added
13	Regional waste regulation	Added

Prolong - Crackfill White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Section	Changed item	Comments
14.1	UN-No. (IATA)	Modified
14.1	UN-No. (IMDG)	Modified
14.4	Packing group (IMDG)	Added
14.6	Packing instructions (IMDG)	Added

Full text of H-statements:	
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H350	May cause cancer
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), South Africa (HCA)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.