

Dura Paints - Heavy Duty Polyurethane - Clear & Clear Matt

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9
Issue date: 6/10/2025 Revision date: 7/28/2026 Supersedes: 6/10/2025 Version: 1.1

SECTION 1: Identification of the substance/mixture and of the supplier/undertaking

1.1. GHS product identifier

Product form	: Mixture
Trade name	: Dura Paints - Heavy Duty Polyurethane - Clear & Clear Matt
Type of product	: Coatings
Product code	: HDPCLEAR/MATT
Product group	: Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use	: Light industrial coating applications
-----------------	---

1.4. Supplier's details

Manufacturer

Dura Paints (Pty) Ltd.
5 Wakefield Road; Founders View South.
P.O. Box 303
1610 Edenvale; Johannesburg – South Africa
T 011 452 5221
orders@durapaints.co.za - www.durapaints.co.za

1.5. Emergency phone number

Emergency number	: 079 494 2731 / 011 452 5221
------------------	-------------------------------

SECTION 2: Hazard identification

2.1. GHS classification of the substance/mixture and any national or regional information

Classification according to the United Nations GHS

Flammable liquids, Category 2	H225
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Carcinogenicity, Category 1B	H350
Specific target organ toxicity – single exposure, Category 1	H370
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity – Repeated exposure, Category 2	H373
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects	: Highly flammable liquid and vapour,May cause cancer,May cause damage to organs through prolonged or repeated exposure,Causes damage to organs,May cause drowsiness or dizziness,Harmful if inhaled,Harmful in contact with skin,Causes skin irritation,Causes serious eye irritation,May be fatal if swallowed and enters airways,Toxic to aquatic life,Toxic to aquatic life with long lasting effects.
---	--

Dura Paints - Heavy Duty Polyurethane - Clear & Clear Matt

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

2.2. GHS label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS ZA)



Signal word (GHS ZA)

: Danger

Hazardous ingredients

: Ethylbenzene; Xylene; Methyl Isobutyl Ketone; Aromatic hydrocarbons, C9; Cumene; 2-butoxyethanol

Hazard statements (GHS ZA)

: H225 - Highly flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H315+H319 - Causes skin irritation and serious eye irritation
H332 - Harmful if inhaled
H336 - May cause drowsiness or dizziness
H350 - May cause cancer (Inhalation)
H370 - Causes damage to organs (central nervous system, Skin, lung/respiratory system) (Dermal, Oral, Inhalation)
H373 - May cause damage to organs (cardiovascular system, kidneys, liver) through prolonged or repeated exposure (Dermal, Oral, Inhalation)
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS ZA)

: P101 - If medical advice is needed, have product container or label and product safety data sheet at hand.
P102 - Keep out of reach of children.
P103 - Read carefully and follow all instructions.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240 - Ground and bond container and receiving equipment.
P261 - Avoid breathing mist, spray, vapours, fume.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear eye protection, protective clothing, protective gloves.
P501 - Dispose of container to Recycling, according to local regulations.

P-statements for label (GHS-ZA)

: P101 - If medical advice is needed, have product container or label and product safety data sheet at hand.; P102 - Keep out of reach of children.; P103 - Read carefully and follow all instructions.; P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.; P240 - Ground and bond container and receiving equipment.; P261 - Avoid breathing mist, spray, vapours, fume.; P271 - Use only outdoors or in a well-ventilated area.; P273 - Avoid release to the environment.; P280 - Wear eye protection, protective clothing, protective gloves.; P501 - Dispose of container to Recycling, according to local regulations.

2.3. Other hazards which do not result in classification or are not covered by the GHS

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Dura Paints - Heavy Duty Polyurethane - Clear & Clear Matt

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

3.2. Mixture

Name	Product identifier	%	Classification according to the United Nations GHS
Xylene	CAS-No.: 1330-20-7	22.025 – 44.575	Flam. Liq. 3, H226 Acute Tox. Not classified (Oral) Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. Not classified (Inhalation:vapour) Skin Irrit. 2, H315 STOT SE 1, H370 STOT RE Not classified Aquatic Chronic 2, H411
Ethylbenzene	CAS-No.: 100-41-4	10.01 – 21.03125	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapour), H332 STOT RE 2, H373 Asp. Tox. 1, H304
Methyl Isobutyl Ketone	CAS-No.: 108-10-1	5 – 12	Flam. Liq. 2, H225 Acute Tox. Not classified (Dermal) Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H336 STOT RE 2, H373 Aquatic Acute Not classified Aquatic Chronic Not classified
Aromatic hydrocarbons, C9	CAS-No.: 128601-23-0	5 – 12	Flam. Liq. 3, H226 Acute Tox. 3 (Inhalation:vapour), H331 STOT SE 3, H336 STOT SE 3, H335 STOT RE Not classified Aquatic Acute 1, H400 Aquatic Chronic 2, H411
2-butoxyethanol	CAS-No.: 111-76-2	1.2 – 3.5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319
Cumene	CAS-No.: 98-82-8	0.005 – 0.24	Flam. Liq. 3, H226 Carc. 1B, H350 STOT SE 3, H335 STOT RE Not classified Asp. Tox. 1, H304 Aquatic Chronic 2, H411

SECTION 4: First aid measures

4.1. Description of necessary first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Dura Paints - Heavy Duty Polyurethane - Clear & Clear Matt

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.
Self protection of the first-aider	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effect, acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Harmful if inhaled.
Symptoms/effects after skin contact	: May be harmful in contact with skin. Irritation.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: Risk of lung oedema.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective actions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate non-essential personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

For containment	: Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

Dura Paints - Heavy Duty Polyurethane - Clear & Clear Matt

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing.
Hygiene measures	: Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Packaging materials	: Always store product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethylbenzene (100-41-4)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Ethyl benzene
RHCA - STEL/C	40 ppm
Remark	CARC (denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B), SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Ethyl benzene
OEL TWA	435 mg/m ³ 100 ppm
OEL STEL	545 mg/m ³ 125 ppm
Regulatory reference	Government Notice No. R 904
South Africa - Biological limit values	
Local name	Ethyl benzene
BEI	0.15 g/g creatinine Parameter: Sum of mandelic acid and phenylglyoxylic acid - Medium: urine - Sampling time: End of shift - Notations: Ns (non-specific)
Regulatory reference	Government Notice No. R. 280, 2021
Xylene (1330-20-7)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Xylene, o-, m-, p- or mixed isomers

Dura Paints - Heavy Duty Polyurethane - Clear & Clear Matt

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Xylene (1330-20-7)	
OEL eight hour TWA	300 ppm
RHCA - STEL/C	200 ppm
Remark	SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Xylene, o-, m-, p- or mixed isomers
OEL TWA	218 mg/m ³
	50 ppm
OEL STEL	435 mg/m ³
	100 ppm
Remark	Sk (Danger of cutaneous absorption)
Regulatory reference	Government Notice No. R 904
South Africa - Biological limit values	
Local name	Xylenes
BEI	1.5 g/g creatinine Parameter: Methylhippuric acids - Medium: urine - Sampling time: End of shift
Regulatory reference	Government Notice No. R. 280, 2021
Methyl Isobutyl Ketone (108-10-1)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	4-Methylpentan-2-one (Isobutyl methyl ketone) (Methyl isobutyl ketone) (MIBK)
OEL eight hour TWA	75 ppm
	300 mg/m ³
RHCA - STEL/C	50 ppm
	205 mg/m ³
Remark	Sk
Regulatory reference	Government Notice. R: 1179
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Methyl isobutyl ketone [MIBK] (Hexone; Isobutyl methyl ketone; 4-Methylpentan-2-one)
OEL TWA	82 mg/m ³
	20 ppm
OEL STEL	205 mg/m ³
	50 ppm
Remark	Sk (Danger of cutaneous absorption)
Regulatory reference	Government Notice No. R 904
South Africa - Biological limit values	
Local name	Methyl isobutyl ketone (MIBK)
BEI	1 mg/l Parameter: Methyl isobutyl ketone (MIBK) - Medium: urine - Sampling time: End of shift
Regulatory reference	Government Notice No. R. 280, 2021

Dura Paints - Heavy Duty Polyurethane - Clear & Clear Matt

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Cumene (98-82-8)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Cumene [isopropyl benzene]
RHCA - STEL/C	100 ppm
Remark	CARC (denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B), SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Cumene (Isopropyl benzene)
OEL TWA	120 mg/m ³
	25 ppm
OEL STEL	370 mg/m ³
	75 ppm
Remark	Sk (Danger of cutaneous absorption)
Regulatory reference	Government Notice No. R 904
2-butoxyethanol (111-76-2)	
South Africa - Occupational Exposure Limits (Maximum Limits)	
Local name	2-Butoxyethanol [EGBE]
RHCA - STEL/C	40 ppm
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	2-Butoxyethanol (Ethylene glycol monobutyl ether [EGBE])
OEL TWA	120 mg/m ³
	25 ppm
Remark	Sk (Danger of cutaneous absorption)
Regulatory reference	Government Notice No. R 904
South Africa - Biological limit values	
Local name	2-Butoxyethanol
BEI	200 mg/g creatinine Parameter: Butoxyacetic acid (BAA) - Medium: urine - Sampling time: End of shift
Regulatory reference	Government Notice No. R. 280, 2021

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: [In case of inadequate ventilation] wear respiratory protection.
Personal protective equipment symbol(s)	

Dura Paints - Heavy Duty Polyurethane - Clear & Clear Matt

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear liquid.
Colour	: Colourless to yellow liquid, Can be tinted to various colours
Odour	: Aromatic solvent like odour
Odour threshold	: No data available
pH	: No data available
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: > -39.3 – < -38.67 °C XYLENE @ 101.3 kPa: ECHA
Boiling point	: > 136.16 – < 144.5 °C XYLENE @ 101.3 kPa: ECHA
Flash point	: ≈ 18 °C XYLENE @ 101 325 Pa: ECHA
Auto-ignition temperature	: > 487.5 – < 488 °C XYLENE:101 325 Pa : ECHA
Decomposition temperature	: No data available
Flammability	: Highly flammable liquid and vapour.
Vapour pressure	: > 8.21 – < 11.057 hPa XYLENE @ 20 - 25 °C : ECHA
Vapour pressure at 50°C	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: > 0.86 – < 0.88 XYLENE @ 20 - 25 °C : ECHA
Relative density of saturated gas/air mixture	: No data available
Density	: > 0.86 – < 0.88 g/cm³ XYLENE @ 25 °C : ECHA
Relative gas density	: No data available
Solubility	: soluble in most organic solvents.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: ≈ 0.74 mm²/s XYLENE : ECHA
Viscosity, dynamic	: > 0.581 – < 0.76 mPa·s XYLENE : ECHA
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Physical state	: Liquid
Appearance	: Clear liquid.

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10: Stability and Reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical Stability

Stable under normal conditions.

Dura Paints - Heavy Duty Polyurethane - Clear & Clear Matt

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Inhalation:dust,mist: Harmful if inhaled.

Dura Paints - Heavy Duty Polyurethane - Clear & Clear Matt

ATE ZA (dust, mist)	2.651 mg/l/4h
---------------------	---------------

Ethylbenzene (100-41-4)

LD50 oral rat	≈ 3500 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	≥ 15400 mg/kg bodyweight Source: ECHA
LC50 Inhalation - Rat	≥ 17.629 mg/l Source: ECHA

Xylene (1330-20-7)

LD50 oral rat	> 3523 – < 6631 mg/kg bodyweight XYLENE : ECHA
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male, Remarks on results: other:
LC50 Inhalation - Rat	≥ 27.124 mg/l XYLENE : ECHA

Methyl Isobutyl Ketone (108-10-1)

LD50 oral rat	≥ 2080 mg/kg Source: Supplier SDS
LD50 dermal rabbit	≥ 16000 mg/kg Source: Supplier SDS
LC50 Inhalation - Rat [ppm]	≥ 2000 ppm/4h Source: Supplier SDS

Aromatic hydrocarbons, C9 (128601-23-0)

LD50 oral rat	≈ 3492 mg/kg bodyweight Source: ECHA
LD50 dermal rabbit	> 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 6.193 mg/l/4h Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

Cumene (98-82-8)

LD50 oral rat	> 2260 – < 2700 mg/kg Source: ECHA
LD50 dermal rabbit	> 3160 mg/kg bodyweight Animal: rabbit

2-butoxyethanol (111-76-2)

LD50 oral	1414 mg/kg bodyweight Animal: guinea pig, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1020 - 1961
LD50 dermal rabbit	≈ 435 mg/kg bodyweight ECHA

Dura Paints - Heavy Duty Polyurethane - Clear & Clear Matt

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

2-butoxyethanol (111-76-2)	
LC50 Inhalation - Rat [ppm]	> 633 – < 691 ppm guinea pig 60min : ECHA
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer (Inhalation).
Reproductive toxicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Causes damage to organs (central nervous system, Skin, lung/respiratory system) (Dermal, Oral, Inhalation). May cause drowsiness or dizziness.
Xylene (1330-20-7)	
LOAEL (oral, rat)	≈ 150 mg/kg bodyweight XYLENE : ECHA
NOAEL (oral, rat)	≈ 250 mg/kg bodyweight XYLENE : ECHA
NOAEC (inhalation, rat, gas)	> 450 – < 1800 ppmv/4h XYLENE : 12H : ECHA
STOT-single exposure	Causes damage to organs (central nervous system) (Inhalation).
Methyl Isobutyl Ketone (108-10-1)	
STOT-single exposure	May cause drowsiness or dizziness.
Aromatic hydrocarbons, C9 (128601-23-0)	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
Cumene (98-82-8)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs (cardiovascular system, kidneys, liver) through prolonged or repeated exposure (Dermal, Oral, Inhalation).
Ethylbenzene (100-41-4)	
NOAEL (oral, rat, 28 days)	≈ 75 mg/kg bodyweight/day Source: ECHA
NOAEC (inhalation, rat, gas, 28 days)	> 250 – < 1000 ppmv/6h/day Source: ECHA
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	May cause damage to organs (hearing organs) through prolonged or repeated exposure (Inhalation, Dermal).
Xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
Methyl Isobutyl Ketone (108-10-1)	
NOAEL (oral, rat, 28 days)	≈ 250 mg/kg bodyweight/day
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aromatic hydrocarbons, C9 (128601-23-0)	
NOAEL (oral, rat, 28 days)	≥ 600 mg/kg bodyweight/day Source: ECHA
NOAEC (inhalation, rat, 28 days)	≥ 900 mg/l Source: ECHA
NOAEL (oral, rat, 90 days)	600 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
Cumene (98-82-8)	
NOAEL (oral, rat, 28 days)	≥ 535.8 mg/kg bodyweight/day Source: ECHA

Dura Paints - Heavy Duty Polyurethane - Clear & Clear Matt

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

2-butoxyethanol (111-76-2)	
LOAEL (oral, rat, 90 days)	≈ 69 mg/kg bodyweight/day ECHA
LOAEC (inhalation, rat, gas, 90 days)	≈ 31 ppmv/6h/day ECHA
NOAEL (dermal, rat/rabbit, 28 days)	≈ 150 mg/kg bodyweight/day ECHA
NOAEL (dermal, rat/rabbit, 90 days)	> 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study), Remarks on results: other:

Aspiration hazard : May be fatal if swallowed and enters airways.

Dura Paints - Heavy Duty Polyurethane - Clear & Clear Matt	
Viscosity, kinematic	≈ 0.74 mm ² /s XYLENE : ECHA

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life. Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

Ethylbenzene (100-41-4)	
LC50 - Fish [1]	5.1 mg/l Test organisms (species): Menidia menidia
EC50 - Crustacea [1]	> 1.8 – < 2.4 mg/l Source: ECHA
EC50 72h - Algae [1]	5.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	4.9 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [1]	3.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	7.7 mg/l Test organisms (species): Skeletonema costatum
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC chronic algae	≈ 3.4 mg/l Fresh water algae; Source: ECHA

Xylene (1330-20-7)	
LC50 - Fish [1]	> 2.6 – < 9.6 mg/l Source: ECHA
EC50 - Crustacea [1]	≥ 10.389 mg/l Source: Echa
EC50 72h - Algae [1]	> 4.6 – < 4.9 mg/l XYLENE : Aquatic Algae : ECHA
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
NOEC chronic algae	≈ 0.44 mg/l XYLENE : Aquatic Algae 73H : ECHA

Methyl Isobutyl Ketone (108-10-1)	
LC50 - Fish [1]	≥ 505 mg/l Species: Fathead minnow; Source: Supplier SDS
LOEC (acute)	≈ 179 mg/l Source: ECHA
LOEC (chronic)	> 64 – < 156 mg/l 21 Days; Source: ECHA
NOEC (chronic)	≈ 200 mg/l 48 Hrs, Source: ECHA
NOEC chronic fish	≈ 179 mg/l Source: ECHA

Dura Paints - Heavy Duty Polyurethane - Clear & Clear Matt

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Aromatic hydrocarbons, C9 (128601-23-0)	
LC50 - Fish [1]	≥ 9.2 mg/l Source: ECHA
EC50 72h - Algae [1]	0.42 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.29 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≈ 0.59 mg/l 590 µg/L; Source: ECHA
NOEC chronic fish	≈ 0.34 mg/l 340 µg/L; Source: ECHA

Cumene (98-82-8)	
LC50 - Fish [1]	≈ 4.7 mg/l Test organisms (species): Cyprinodon variegatus
LC50 - Fish [2]	≈ 4.8 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	≈ 2.14 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	≈ 2.45 mg/l Source: ECHA
EC50 72h - Algae [1]	≈ 2.01 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	≈ 1.29 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	≈ 0.35 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	≈ 0.38 mg/l Test organisms (species): other: Duration: '28 d'
NOEC chronic algae	≈ 1.49 mg/l Source: ECHA

2-butoxyethanol (111-76-2)	
LC50 - Fish [1]	1474 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	≈ 1800 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	≈ 623 mg/l Fresh water algae : ECHA
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	≥ 100 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'
NOEC chronic algae	≈ 88 mg/l Fresh water algae : ECHA

12.2. Persistence and degradability

Dura Paints - Heavy Duty Polyurethane - Clear & Clear Matt	
Persistence and degradability	Not rapidly degradable

Ethylbenzene (100-41-4)	
Persistence and degradability	

Xylene (1330-20-7)	
Persistence and degradability	
Chemical oxygen demand (COD)	> 2.56 – < 2.91 g O ₂ /g substance

Methyl Isobutyl Ketone (108-10-1)	
Persistence and degradability	
Biochemical oxygen demand (BOD)	≈ 2.03 g O ₂ /g substance Source: Supplier SDS
Chemical oxygen demand (COD)	≈ 2016 g O ₂ /g substance Source: Supplier SDS

Dura Paints - Heavy Duty Polyurethane - Clear & Clear Matt

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Aromatic hydrocarbons, C9 (128601-23-0)	
Persistence and degradability	
Cumene (98-82-8)	
Persistence and degradability	
2-butoxyethanol (111-76-2)	
Persistence and degradability	

12.3. Bioaccumulative potential

Dura Paints - Heavy Duty Polyurethane - Clear & Clear Matt	
Bioaccumulative potential	No additional information available
Ethylbenzene (100-41-4)	
BCF - Fish [1]	≈ 110 l/kg Source: ECHA
Partition coefficient n-octanol/water (Log Kow)	> 3.03 – < 3.6 @ 20 °C and pH 7.84; Source: ECHA
Xylene (1330-20-7)	
Partition coefficient n-octanol/water (Log Pow)	> 3.155 – < 3.16 XYLENE @ 20 °C : ECHA
Partition coefficient n-octanol/water (Log Kow)	> 3.12 – < 3.2 XYLENE @ 20 °C and pH 7: ECHA
Methyl Isobutyl Ketone (108-10-1)	
Partition coefficient n-octanol/water (Log Pow)	≈ 1.2 Source: Supplier SDS
Partition coefficient n-octanol/water (Log Kow)	≈ 1.3 20 °C and pH 6.7 ;Source: ECHA
Aromatic hydrocarbons, C9 (128601-23-0)	
Partition coefficient n-octanol/water (Log Kow)	> 3.03 – < 4.73 @ 20 °C and pH 7; Source: ECHA
Cumene (98-82-8)	
Partition coefficient n-octanol/water (Log Kow)	≈ 3.55 @ 20 °C; Source: ECHA
2-butoxyethanol (111-76-2)	
Partition coefficient n-octanol/water (Log Pow)	≈ 0.81 @ 20 °C : ECHA
Partition coefficient n-octanol/water (Log Kow)	≈ 0.81 @ 25 °C and pH 7 : ECHA

12.4. Mobility in soil

Dura Paints - Heavy Duty Polyurethane - Clear & Clear Matt	
Mobility in soil	No additional information available
Ethylbenzene (100-41-4)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	≈ 1331 at 20°C : ECHA
Xylene (1330-20-7)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	≈ 537 XYLENE: @ 20 °C : ECHA
Aromatic hydrocarbons, C9 (128601-23-0)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	> 358.67 – < 8544.76 L/kg @ 20 °C;Source: ECHA

12.5. Other adverse effects

Ozone : Not classified

Dura Paints - Heavy Duty Polyurethane - Clear & Clear Matt

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Other adverse effects : No additional information available

SECTION 13: Disposal Considerations

13.1. Disposal methods

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
Additional information : Flammable vapours may accumulate in the container. Do not re-use empty containers.

SECTION 14: Transport information

In accordance with SANS / UN RTDG / IMDG / IATA

SANS	UN RTDG	IMDG	IATA
14.1. UN number			
1307	Not applicable	1307	1307
14.2. UN Proper Shipping Name			
XYLENES	Not applicable	XYLENES	Xylenes
Transport document description			
Not applicable	Not applicable	UN 1307 XYLENES, 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS (23°C c.c.)	UN 1307 Xylenes, 3, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)			
3	Not applicable	3	3
	 Not applicable		
14.4. Packing group, if applicable			
III	Not applicable	III	III
14.5. Environmental hazards			
Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes
No supplementary information available			

14.6. Special precautions for user

SANS

Special provisions (SANS) : 223
Limited quantities (SANS) : 5 L
Excepted quantities (SANS) : E1
Packagings, large packagings and IBCs Packing instructions (SANS) : P001, IBC03, LP01
Portable tank and bulk containers instructions (SANS) : T2
Portable tank and bulk container special provisions (SANS) : TP1

Dura Paints - Heavy Duty Polyurethane - Clear & Clear Matt

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

UN RTDG

No data available

IMDG

Special provisions (IMDG)	: 223
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG)	: A
Flash point (IMDG)	: 23°C to 30°C c.c.
Properties and observations (IMDG)	: Colourless liquids. Flashpoint: 23°C to 30°C c.c. Explosive limits: 1.1% to 7%. Immiscible with water.

IATA

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

14.7. Transport in bulk according to IMO instructions

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

15.1.1. OCCUPATIONAL HEALTH AND SAFETY ACT, 1993

Prohibited Hazardous Chemical Agents

Not regulated

15.1.2. National Environmental Management Act, 1998

Regulation No. 51358 (Prior Informed Consent Procedure Regulations, 2024)

Not regulated

15.2. Safety, health, and environmental national regulations specific for the product

No additional information available

SECTION 16: Other information

Issue date	: 10/06/2025
Revision date	: 28/07/2026
Supersedes	: 10/06/2025

Full text of H-statements:

H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour

Dura Paints - Heavy Duty Polyurethane - Clear & Clear Matt

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Full text of H-statements:	
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), South Africa (HCA)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.