

SECTION 1: Identification of the substance/mixture and of the supplier/undertaking

1.1. GHS product identifier

Product form	: Mixture
Trade name	: Dura Paints - Autocote Enamel - Clear
Type of product	: Coatings
Product code	: AUTCL
Product group	: Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use	: Light industrial coating applications
-----------------	---

1.4. Supplier's details

Manufacturer

Dura Paints (Pty) Ltd.
5 Wakefield Road; Founders View South.
P.O. Box 303
1610 Edenvale; Johannesburg – South Africa
T 011 452 5221
orders@durapaints.co.za - www.durapaints.co.za

1.5. Emergency phone number

Emergency number	: 079 494 2731 / 011 452 5221
------------------	-------------------------------

SECTION 2: Hazard identification

2.1. GHS classification of the substance/mixture and any national or regional information

Classification according to the United Nations GHS

Flammable liquids, Category 3	H226
Acute toxicity (inhalation:vapour) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 1	H350
Reproductive toxicity, Category 2	H361
Specific target organ toxicity – single exposure, Category 1	H370
Specific target organ toxicity – Repeated exposure, Category 2	H373
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects	: Flammable liquid and vapour,May cause cancer,Causes damage to organs through prolonged or repeated exposure,Harmful if inhaled,Causes skin irritation,May cause an allergic skin reaction,May be fatal if swallowed and enters airways.
---	---

2.2. GHS label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS ZA)



Dura Paints - Autocote Enamel - Clear

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Signal word (GHS ZA)	: Danger
Hazardous ingredients	: ethylbenzene; Xylene; Butanone oxime; Kerosine (petroleum) [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150°C to 290°C (320°F to 554°F).]; Toluene
Hazard statements (GHS ZA)	: H226 - Flammable liquid and vapour H304 - May be fatal if swallowed and enters airways H315 - Causes skin irritation H317 - May cause an allergic skin reaction H332 - Harmful if inhaled H350 - May cause cancer (Inhalation) H361 - Suspected of damaging fertility, Suspected of damaging the unborn child. (Dermal, Inhalation) H370 - Causes damage to organs (respiratory system, eyes, Skin, central nervous system, kidneys, liver) (Dermal, Inhalation, Oral) H373 - May cause damage to organs (hearing organs, liver, kidneys) through prolonged or repeated exposure (Dermal, Inhalation) H411 - Toxic to aquatic life with long lasting effects
Precautionary statements (GHS ZA)	: P101 - If medical advice is needed, have product container or label and product safety data sheet at hand. P102 - Keep out of reach of children. P103 - Read carefully and follow all instructions. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 - Ground and bond container and receiving equipment. P261 - Avoid breathing mist, spray, vapours, fume. P263 - Avoid contact during pregnancy and while nursing. P273 - Avoid release to the environment. P280 - Wear eye protection, protective clothing, protective gloves. P501 - Dispose of container to according to local regulations.
P-statements for label (GHS-ZA)	: P101 - If medical advice is needed, have product container or label and product safety data sheet at hand.; P102 - Keep out of reach of children.; P103 - Read carefully and follow all instructions.; P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.; P240 - Ground and bond container and receiving equipment.; P261 - Avoid breathing mist, spray, vapours, fume.; P263 - Avoid contact during pregnancy and while nursing.; P273 - Avoid release to the environment.; P280 - Wear eye protection, protective clothing, protective gloves.; P501 - Dispose of container to according to local regulations.

2.3. Other hazards which do not result in classification or are not covered by the GHS

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Dura Paints - Autocote Enamel - Clear

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

3.2. Mixture

Name	Product identifier	%	Classification according to the United Nations GHS
Xylene	CAS-No.: 1330-20-7	44.76 – 48.5066	Flam. Liq. 3, H226 Acute Tox. Not classified (Oral) Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. Not classified (Inhalation:vapour) Skin Irrit. 2, H315 STOT SE 1, H370 STOT RE Not classified Aquatic Chronic 2, H411
Kerosine (petroleum) [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150°C to 290°C (320°F to 554°F).]	CAS-No.: 8008-20-6	19.065 – 38.13	Flam. Liq. 3, H226 Acute Tox. Not classified (Oral) Carc. 1, H350 STOT RE 2, H373 Asp. Tox. 1, H304
ethylbenzene	CAS-No.: 100-41-4	14.92 – 18.6666	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapour), H332 STOT RE 2, H373 Asp. Tox. 1, H304
Naphthalene	CAS-No.: 91-20-3	0 – 1.1439	Acute Tox. 4 (Oral), H302 Acute Tox. 2 (Inhalation:dust,mist), H330 Carc. 2, H351 STOT RE Not classified Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Cumene	CAS-No.: 98-82-8	0 – 0.3813	Flam. Liq. 3, H226 Carc. 1B, H350 STOT SE 3, H335 STOT RE Not classified Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Toluene	CAS-No.: 108-88-3	0 – 0.3813	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Butanone oxime	CAS-No.: 96-29-7	0.16915	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 1B, H350 STOT SE 1, H370 STOT SE 3, H336 STOT RE 1, H372 Aquatic Chronic Not classified

Dura Paints - Autocote Enamel - Clear

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

SECTION 4: First aid measures

4.1. Description of necessary first aid measures

First-aid measures general	: Get medical advice/attention if you feel unwell. If medical advice is needed, have product container or label and product safety data sheet at hand.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If breathing stops, give artificial respiration. If respiratory irritation, dizziness, nausea or unconsciousness occurs, seek immediate medical assistance.
First-aid measures after skin contact	: Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If product is injected into or under the skin, or any part of the body, it should be treated as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.
First-aid measures after eye contact	: Immediately rinse with water for a prolonged period while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do NOT induce vomiting. Rinse mouth out with water. Keep the affected person calm and seated upright. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get immediate medical advice/attention.
Self protection of the first-aiders	: First-aiders should pay attention to their own protection and use the recommended personal protective equipment (see section 8).

4.2. Most important symptoms/effect, acute and delayed

Symptoms/effects	: Harmful if inhaled. May cause drowsiness or dizziness. Harmful in contact with skin. Causes serious eye irritation. May be fatal if swallowed and enters airways.
Symptoms/effects after inhalation	: Adverse symptoms may include nausea or vomiting, headache, respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. May cause redness, dryness, and discomfort.
Symptoms/effects after eye contact	: Adverse symptoms may include pain, irritation, watering and redness. Blurred vision.
Symptoms/effects after ingestion	: Swallowing material may cause irritation of the gastrointestinal lining, nausea, vomiting, diarrhea, and abdominal pain. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.
Symptoms/effects upon intravenous administration	: Pain, swelling, and erythema: Rapid onset at the injection site; Chemical necrotising cellulitis: Inflammatory destruction of soft tissue, often within 24 hours. Get medical attention immediately.
Chronic symptoms	: Neurological: Headaches, memory loss, fatigue; Dermal: Can lead to dermatitis, with symptoms like cracking, scaling, and inflammation; Renal/Hepatic: Liver and kidney stress.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

See section 4.1. Description of first-aid measures. Treat symptomatically. Monitor respiratory and neurological status.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Dry powder. Foam. Carbon dioxide. Water spray or fog. Use water spray or fog for cooling exposed containers.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: Vapours may form explosive mixture with air. When vapors accumulate in enclosed or poorly ventilated areas, any ignition source (e.g. static discharge, open flame, hot surfaces) can trigger an explosion. This is especially critical in spray booths, storage tanks, and confined mixing areas.
Reactivity in case of fire	: Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

Dura Paints - Autocote Enamel - Clear

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

5.3. Special protective actions for fire-fighters

- | | |
|--|--|
| Precautionary measures fire | : Evacuate area. Eliminate all ignition sources if safe to do so. Cool endangered containers with water spray or fog. |
| Firefighting instructions | : Fight fire from safe distance and protected location. Stay upwind of fire. |
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |
| Personal protection (Emergency response) | : Fire-resistant protective clothing, Use breathing equipment (SCBA), Use only explosion-proof equipment and PPE |



- | | |
|-------------------|---|
| Other information | : Dyke fire control water for later disposal. Do not allow run-off from fire-fighting to enter drains or water courses. Notify authorities if run-off does enter drains or water courses. |
|-------------------|---|

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- | | |
|---|--|
| General measures | : Evacuate non-essential personnel. Eliminate every possible source of ignition. Ventilate spillage area. |
| Personal Precautions, Protective Equipment and Emergency Procedures | : Avoid contact with skin and eyes, avoid breathing vapours. Use only non-sparking tools. Complete protective clothing. |
| Prevention Measures for Secondary Accidents | : Stop leaks if it can be done without personal risk. Remove ignition sources. Avoid sparks. Take precautionary measures against static discharge. |

6.1.1. For non-emergency personnel

- | | |
|----------------------|--|
| Protective equipment | : Wear recommended personal protective equipment. |
| Emergency procedures | : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe mist, spray, vapours. Avoid contact with skin, eyes and clothing. |

6.1.2. For emergency responders

- | | |
|----------------------|---|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
| Emergency procedures | : Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. |

6.2. Environmental precautions

Prevent liquid from entering sewers, watercourses, underground or low areas. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

- | | |
|-------------------------|---|
| For containment | : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. |
| Methods for cleaning up | : Absorb spillage with vermiculite or sand; Scoop into labeled hazardous waste container. Use non-sparking tools. Clean spill area with detergent and water — avoid solvents. |
| Other information | : Dispose of contaminated materials according to Section 13. |

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- | | |
|-------------------------------|--|
| Precautions for safe handling | : Avoid all contact with skin, eyes, or clothing. Avoid breathing mist, spray, vapours. Provide local exhaust or general room ventilation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use only non-sparking tools. Use explosion-proof equipment. Wear personal protective equipment. |
| Local and general ventilation | : Local exhaust ventilation. |
| Hygiene measures | : Do not eat, drink or smoke when using this product. Wash hands, forearms and face thoroughly after handling. Wash contaminated clothing before reuse. |

Dura Paints - Autocote Enamel - Clear

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in tightly sealed containers in a cool, dry, well-ventilated area. Store away from direct sunlight and sources of ignition.
Storage area	: Ensure electrical equipment and fittings comply with local fire prevention regulations for this class of product. Refer to national or local regulations covering safety at petroleum handling and storage areas for this product.
Incompatible products	: Oxidizing agent. Strong acids. Strong bases.
Packaging materials	: Always store product in container of same material as original container.
Material used in packaging/containers	: steel, hdpu or approved chemical drums.
Storage temperature	: < 30 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ethylbenzene (100-41-4)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Ethyl benzene
RHCA - STEL/C	40 ppm
Remark	CARC (denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B), SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Ethyl benzene
OEL TWA	435 mg/m ³
	100 ppm
OEL STEL	545 mg/m ³
	125 ppm
Regulatory reference	Government Notice No. R 904
South Africa - Biological limit values	
Local name	Ethyl benzene
BEI	0.15 g/g creatinine Parameter: Sum of mandelic acid and phenylglyoxylic acid - Medium: urine - Sampling time: End of shift - Notations: Ns (non-specific)
Regulatory reference	Government Notice No. R. 280, 2021
Xylene (1330-20-7)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Xylene, o-, m-, p- or mixed isomers
OEL eight hour TWA	300 ppm
RHCA - STEL/C	200 ppm
Remark	SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Xylene, o-, m-, p- or mixed isomers
OEL TWA	218 mg/m ³

Dura Paints - Autocote Enamel - Clear

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Xylene (1330-20-7)	
	50 ppm
OEL STEL	435 mg/m ³
	100 ppm
Remark	Sk (Danger of cutaneous absorption)
Regulatory reference	Government Notice No. R 904
South Africa - Biological limit values	
Local name	Xylenes
BEI	1.5 g/g creatinine Parameter: Methylhippuric acids - Medium: urine - Sampling time: End of shift
Regulatory reference	Government Notice No. R. 280, 2021
Naphthalene (91-20-3)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Naphthalene
OEL eight hour TWA	15 ppm
	75 mg/m ³
RHCA - STEL/C	20 ppm
	10 ppm
	50 mg/m ³
Remark	CARC (denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B), SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021 Government Notice. R: 1179
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Naphthalene
OEL TWA	50 mg/m ³
	10 ppm
OEL STEL	75 mg/m ³
	15 ppm
Regulatory reference	Government Notice No. R 904
Cumene (98-82-8)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Cumene [isopropyl benzene]
RHCA - STEL/C	100 ppm
Remark	CARC (denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B), SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Cumene (Isopropyl benzene)
OEL TWA	120 mg/m ³
	25 ppm
OEL STEL	370 mg/m ³

Dura Paints - Autocote Enamel - Clear

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Cumene (98-82-8)	
	75 ppm
Remark	Sk (Danger of cutaneous absorption)
Regulatory reference	Government Notice No. R 904
Toluene (108-88-3)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Toluene
OEL eight hour TWA	150 ppm
	560 mg/m ³
RHCA - STEL/C	40 ppm
	50 ppm
	188 mg/m ³
Remark	SKIN (danger of cutaneous absorption) Sk
Regulatory reference	Government Notice No. R. 280, 2021 Government Notice. R: 1179
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Toluene
OEL TWA	188 mg/m ³
	50 ppm
OEL STEL	560 mg/m ³
	150 ppm
Remark	Sk (Danger of cutaneous absorption)
Regulatory reference	Government Notice No. R 904
South Africa - Biological limit values	
Local name	Toluene
BEI	0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: Prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: End of shift 0.3 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: End of shift - Notations: B (background)
Regulatory reference	Government Notice No. R. 280, 2021

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Materials for protective clothing	: Chemical resistant overalls
Hand protection	: Protective gloves
Eye protection	: Wear security glasses which protect from splashes
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: [In case of inadequate ventilation] wear respiratory protection.
Personal protective equipment symbol(s)	

Dura Paints - Autocote Enamel - Clear

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear, colorless liquid.
Colour	: Can be tinted to various colours
Odour	: Aromatic solvent like odour
Odour threshold	: No data available
pH	: No data available
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 136.16 – < 144.5 °C Derived form Xylene value; @ 101.3 kPa; Source: ECHA
Flash point	: ≈ 27 °C Derived form Xylene value; Source: Supplier SDS
Auto-ignition temperature	: > 487.5 – < 488 °C @ 101 325 Pa; Source : ECHA
Decomposition temperature	: No data available
Flammability	: Flammable liquid and vapour.
Vapour pressure	: ≈ 14.2 hPa Derived form Xylene value; Source: ECHA
Vapour pressure at 50°C	: No data available
Relative vapour density at 20°C	: ≈ 0.865 Derived form Xylene value
Relative density	: ≈ 1.2 Source: Product TDS
Relative density of saturated gas/air mixture	: No data available
Density	: No data available
Relative gas density	: No data available
Solubility	: insoluble in water. soluble in most organic solvents.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: < 1 mm ² /s Derived form Xylene value; @ 40 degrees C; Source: Supplier SDS
Viscosity, dynamic	: > 240 – < 500 cP Source: Product TDS
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available
Lower explosion limit	: ≈ 1.9 Vol-% Source: Supplier SDS; (Derived from values for xylene)
Upper explosion limit	: ≈ 12.3 Vol-% Source: Supplier SDS; (Derived from values for xylene)
Physical state	: Liquid
Appearance	: Clear, colorless liquid.

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10: Stability and Reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical Stability

Stable under normal conditions.

Dura Paints - Autocote Enamel - Clear

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Direct sunlight.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Likely routes of exposure : Dermal. Ingestion. Inhalation.

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Inhalation:vapour: Harmful if inhaled.

Dura Paints - Autocote Enamel - Clear

ATE ZA (vapours)	16.376 mg/l/4h
------------------	----------------

ethylbenzene (100-41-4)

LD50 oral rat	≈ 3500 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	≥ 15400 mg/kg bodyweight Source: ECHA
LC50 Inhalation - Rat	≥ 17.629 mg/l Source: ECHA

Xylene (1330-20-7)

LD50 oral rat	> 3523 – < 6631 mg/kg bodyweight XYLENE : ECHA
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male, Remarks on results: other:
LC50 Inhalation - Rat	≥ 27.124 mg/l XYLENE : ECHA

Butanone oxime (96-29-7)

LD50 oral rat	> 900 – < 2326 mg/kg bodyweight Source: Echa
LD50 dermal rabbit	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 4.83 mg/l/4h Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

Kerosine (petroleum) [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150°C to 290°C (320°F to 554°F).] (8008-20-6)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5.28 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 -

Naphthalene (91-20-3)

LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
---------------	--

Dura Paints - Autocote Enamel - Clear

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Naphthalene (91-20-3)	
LC50 Inhalation - Rat	> 0.4 mg/l air Animal: rat, Guideline: other:, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
Cumene (98-82-8)	
LD50 oral rat	> 2260 – < 2700 mg/kg Source: ECHA
LD50 dermal rabbit	> 3160 mg/kg bodyweight Animal: rabbit
Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg Source: ECHA
LD50 dermal rabbit	> 5000 mg/kg Source: ECHA
LC50 Inhalation - Rat	> 25.7 – < 30 mg/l Source: ECHA
LC50 Inhalation - Rat (Vapours)	> 20 mg/l Source: ECHA
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer (Inhalation).
Toluene (108-88-3)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Suspected of damaging fertility, Suspected of damaging the unborn child. (Dermal, Inhalation).
Butanone oxime (96-29-7)	
NOAEL (animal/male, F0/P)	> 200 mg/kg bodyweight Source: ECHA
Kerosine (petroleum) [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150°C to 290°C (320°F to 554°F).] (8008-20-6)	
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)]
Naphthalene (91-20-3)	
LOAEL (animal/female, F0/P)	50 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:
LOAEL (animal/female, F1)	450 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:
NOAEL (animal/female, F0/P)	120 mg/kg bodyweight Animal: rabbit, Animal sex: female, Guideline: other:
Reproductive toxicity	: Suspected of damaging fertility, Suspected of damaging the unborn child. (Dermal, Inhalation).
STOT-single exposure	: Causes damage to organs (respiratory system, eyes, Skin, central nervous system, kidneys, liver) (Dermal, Inhalation, Oral).
Xylene (1330-20-7)	
LOAEL (oral, rat)	≈ 150 mg/kg bodyweight XYLENE : ECHA
NOAEL (oral, rat)	≈ 250 mg/kg bodyweight XYLENE : ECHA
NOAEC (inhalation, rat, gas)	> 450 – < 1800 ppmv/4h XYLENE : 12H : ECHA
STOT-single exposure	Causes damage to organs (central nervous system) (Inhalation).
Butanone oxime (96-29-7)	
STOT-single exposure	Causes damage to organs. May cause drowsiness or dizziness.
Cumene (98-82-8)	
STOT-single exposure	May cause respiratory irritation.

Dura Paints - Autocote Enamel - Clear

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs (hearing organs, liver, kidneys) through prolonged or repeated exposure (Dermal, Inhalation).
ethylbenzene (100-41-4)	
NOAEL (oral, rat, 28 days)	≈ 75 mg/kg bodyweight/day Source: ECHA
NOAEC (inhalation, rat, gas, 28 days)	> 250 – < 1000 ppmv/6h/day Source: ECHA
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	May cause damage to organs (hearing organs) through prolonged or repeated exposure (Inhalation, Dermal).
Xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
Butanone oxime (96-29-7)	
LOAEL (oral, rat, 90 days)	40 mg/kg bodyweight Animal: rat, Guideline: other:
NOAEC (inhalation, rat, 28 days)	≈ 0.054 mg/l Source: ECHA
NOAEC (inhalation, rat, vapour, 90 days)	0.09 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
NOAEL (subchronic, oral, animal/male, 90 days)	110 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Kerosine (petroleum) [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150°C to 290°C (320°F to 554°F).] (8008-20-6)	
LOAEL (dermal, rat/rabbit, 90 days)	≈ 165 mg/kg bodyweight/day Rat; Source: ECHA
NOAEL (oral, rat, 28 days)	> 750 mg/kg bodyweight/day Source: ECHA
NOAEL (dermal, rat/rabbit, 28 days)	≈ 495 mg/kg bodyweight/day Rat; Source: ECHA
NOAEC (inhalation, rat, 28 days)	< 1 mg/l Source: ECHA
NOAEL (oral, rat, 90 days)	750 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	≥ 495 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Naphthalene (91-20-3)	
LOAEL (oral, rat, 90 days)	400 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
LOAEC (inhalation, rat, vapour, 90 days)	0.011 mg/l air Animal: rat, Guideline: EPA OPP 82-4 (90-Day Inhalation Toxicity), Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (oral, rat, 90 days)	200 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

Dura Paints - Autocote Enamel - Clear

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Cumene (98-82-8)	
NOAEL (oral, rat, 28 days)	≥ 535.8 mg/kg bodyweight/day Source: ECHA
Toluene (108-88-3)	
LOAEL (oral, rat, 90 days)	≈ 1250 mg/kg bodyweight/day Source: ECHA
LOAEC (inhalation, rat, gas, 90 days)	≈ 2.261 mg/l Source: ECHA
NOAEL (oral, rat, 28 days)	≥ 625 mg/kg bodyweight/day
NOAEC (inhalation, rat, 28 days)	> 2.261 – < 4.71 mg/l Source : ECHA
NOAEL (oral, rat, 90 days)	≈ 625 mg/kg bodyweight/day Rat
NOAEC (inhalation, rat, gas, 90 days)	1.131 – 2.355 mg/l Air, Source: ECHA
NOAEC (inhalation, rat, vapour, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)
STOT-repeated exposure	May cause damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation).
Aspiration hazard	: May be fatal if swallowed and enters airways.
Dura Paints - Autocote Enamel - Clear	
Viscosity, kinematic	< 1 mm²/s Derived from Xylene value;@ 40 degrees C; Source: Supplier SDS

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Avoid release to the environment. May cause long lasting harmful effects to aquatic life.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

ethylbenzene (100-41-4)	
LC50 - Fish [1]	5.1 mg/l Test organisms (species): Menidia menidia
EC50 - Crustacea [1]	> 1.8 – < 2.4 mg/l Source: ECHA
EC50 72h - Algae [1]	5.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	4.9 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [1]	3.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	7.7 mg/l Test organisms (species): Skeletonema costatum
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC chronic algae	≈ 3.4 mg/l Fresh water algae; Source: ECHA
Xylene (1330-20-7)	
LC50 - Fish [1]	> 2.6 – < 9.6 mg/l Source: ECHA
EC50 - Crustacea [1]	≥ 10.389 mg/l Source: Echa
EC50 72h - Algae [1]	> 4.6 – < 4.9 mg/l XYLENE : Aquatic Algae : ECHA
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

Dura Paints - Autocote Enamel - Clear

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Xylene (1330-20-7)	
NOEC chronic algae	≈ 0.44 mg/l XYLENE : Aquatic Algae 73H : ECHA
Butanone oxime (96-29-7)	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	≈ 201 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	≈ 11.8 mg/l Test organisms (species): Scenedesmus capricornutum
EC50 72h - Algae [2]	≈ 6.09 mg/l Test organisms (species): Scenedesmus capricornutum
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 50 – < 100 mg/l Source: Echa
NOEC chronic algae	≥ 2.56 mg/l Freshwater Algae; Source: Echa
Naphthalene (91-20-3)	
LC50 - Fish [1]	> 1.6 – < 7.9 mg/l Source: ECHA
EC50 - Crustacea [1]	2.16 mg/l Test organisms (species): Daphnia magna
NOEC (chronic)	0.59 mg/l Test organisms (species): Daphnia pulex Duration: '125 d'
NOEC chronic fish	> 0.12 – < 0.37 mg/l Source: ECHA
Cumene (98-82-8)	
LC50 - Fish [1]	≈ 4.7 mg/l Test organisms (species): Cyprinodon variegatus
LC50 - Fish [2]	≈ 4.8 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	≈ 2.14 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	≈ 2.45 mg/l Source: ECHA
EC50 72h - Algae [1]	≈ 2.01 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	≈ 1.29 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	≈ 0.35 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	≈ 0.38 mg/l Test organisms (species): other: Duration: '28 d'
NOEC chronic algae	≈ 1.49 mg/l Source: ECHA
Toluene (108-88-3)	
LC50 - Fish [1]	5.5 mg/l Source: ECHA
EC50 - Crustacea [1]	3.78 mg/l Source: ECHA
EC50 72h - Algae [1]	≥ 134 mg/l Source: ECHA
ErC50 algae	≥ 84 mg/l Source : ECHA
LOEC (chronic)	≥ 2.76 mg/l 7 Days - Source : ECHA
NOEC (chronic)	0.74 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC chronic fish	≥ 1.39 mg/l Source : ECHA
NOEC chronic crustacea	≈ 0.74 mg/l Source: ECHA
NOEC chronic algae	≥ 10 mg/l Sourc: ECHA

Dura Paints - Autocote Enamel - Clear

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

12.2. Persistence and degradability

Dura Paints - Autocote Enamel - Clear

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

ethylbenzene (100-41-4)

Persistence and degradability	
-------------------------------	--

Xylene (1330-20-7)

Persistence and degradability	
-------------------------------	--

Chemical oxygen demand (COD)	> 2.56 – < 2.91 g O ₂ /g substance
------------------------------	---

Butanone oxime (96-29-7)

Persistence and degradability	
-------------------------------	--

Kerosine (petroleum) [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150°C to 290°C (320°F to 554°F).] (8008-20-6)

Persistence and degradability	
-------------------------------	--

Naphthalene (91-20-3)

Persistence and degradability	
-------------------------------	--

Cumene (98-82-8)

Persistence and degradability	
-------------------------------	--

Toluene (108-88-3)

Persistence and degradability	
-------------------------------	--

12.3. Bioaccumulative potential

Dura Paints - Autocote Enamel - Clear

Bioaccumulative potential	No additional information available
---------------------------	-------------------------------------

ethylbenzene (100-41-4)

BCF - Fish [1]	≈ 110 l/kg Source: ECHA
----------------	-------------------------

Partition coefficient n-octanol/water (Log Kow)	> 3.03 – < 3.6 @ 20 °C and pH 7.84; Source: ECHA
---	--

Xylene (1330-20-7)

Partition coefficient n-octanol/water (Log Pow)	> 3.155 – < 3.16 XYLENE @ 20 °C : ECHA
---	--

Partition coefficient n-octanol/water (Log Kow)	> 3.12 – < 3.2 XYLENE @ 20 °C and pH 7: ECHA
---	--

Butanone oxime (96-29-7)

Bioconcentration factor (BCF REACH)	≈ 5.8 Source: ECHA
-------------------------------------	--------------------

Partition coefficient n-octanol/water (Log Pow)	≈ 0.63 @ 25 °C; Source: Echa
---	------------------------------

Partition coefficient n-octanol/water (Log Kow)	≈ 0.63 Source: Echa
---	---------------------

Bioaccumulative potential	Not readily biodegradable.
---------------------------	----------------------------

Naphthalene (91-20-3)

Partition coefficient n-octanol/water (Log Pow)	≈ 3.7 At 25 °C; Source: ECHA
---	------------------------------

Partition coefficient n-octanol/water (Log Kow)	≈ 3.4 At 25 °C and pH 7 - 7.5; Source: ECHA
---	---

Cumene (98-82-8)

Partition coefficient n-octanol/water (Log Kow)	≈ 3.55 @ 20 °C; Source: ECHA
---	------------------------------

Dura Paints - Autocote Enamel - Clear

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Toluene (108-88-3)	
Partition coefficient n-octanol/water (Log Kow)	2.73 Source: HSDB

12.4. Mobility in soil

Dura Paints - Autocote Enamel - Clear	
Mobility in soil	No additional information available

ethylbenzene (100-41-4)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	≈ 1331 at 20°C : ECHA

Xylene (1330-20-7)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	≈ 537 XYLENE: @ 20 °C : ECHA

Butanone oxime (96-29-7)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	≈ 3.52 at 20°C; Source: Echa

Toluene (108-88-3)	
Surface tension	≈ 27.73 mN/m

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No additional information available

SECTION 13: Disposal Considerations

13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with SANS / UN RTDG / IMDG / IATA

SANS	UN RTDG	IMDG	IATA
14.1. UN number			
1263	1263	1263	1263
14.2. UN Proper Shipping Name			
PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	Paint related material
Transport document description			
Not applicable	UN 1263 PAINT RELATED MATERIAL, 3, II	UN 1263 PAINT RELATED MATERIAL, 3, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1263 Paint related material, 3, II, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)			
3	3	3	3

Dura Paints - Autocote Enamel - Clear

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

SANS	UN RTDG	IMDG	IATA
	 Not applicable		
14.4. Packing group, if applicable			
II	II	II	II
14.5. Environmental hazards			
Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes
No supplementary information available			

14.6. Special precautions for user

SANS

Special provisions (SANS)	: 163, 187
Limited quantities (SANS)	: 5 L
Excepted quantities (SANS)	: E2
Packagings, large packagings and IBCs Packing instructions (SANS)	: P001, IBC02
Packagings, large packagings and IBCs Special packing instructions (SANS)	: PP1
Portable tank and bulk containers instructions (SANS)	: T4
Portable tank and bulk container special provisions (SANS)	: TP1, TP8, TP28

UN RTDG

Special provisions (UN RTDG)	: 163, 367
Limited quantities (UN RTDG)	: 5L
Excepted quantities (UN RTDG)	: E2
Packing instruction (UN RTDG)	: P001, IBC02
Special packing provisions (UN RTDG)	: PP1
Portable tank and bulk container special instructions (UN RTDG)	: T4
Portable tank and bulk container special provisions (UN RTDG)	: TP1, TP8, TP28

IMDG

Special provisions (IMDG)	: 163, 367
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP8, TP28
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG)	: B
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

IATA

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353

Dura Paints - Autocote Enamel - Clear

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

14.7. Transport in bulk according to IMO instructions

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

15.1.1. OCCUPATIONAL HEALTH AND SAFETY ACT, 1993

Prohibited Hazardous Chemical Agents

Not regulated

15.1.2. National Environmental Management Act, 1998

Regulation No. 51358 (Prior Informed Consent Procedure Regulations, 2024)

Not regulated

15.2. Safety, health, and environmental national regulations specific for the product

State or local regulations : Complies with the South African legal lead limit of 90ppm or less.

SECTION 16: Other information

Issue date	: 13/07/2023
Revision date	: 24/07/2026
Supersedes	: 16/03/2026

Full text of H-statements:

H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H330	Fatal if inhaled
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer

Dura Paints - Autocote Enamel - Clear

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9

Full text of H-statements:	
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), South Africa (HCA)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.