

SECTION 1: Identification of the substance/mixture and of the supplier/undertaking

1.1. GHS product identifier

Product form	: Mixture
Trade name	: Dura Paints - Genral Purpose Primer - Grey RFU
Product code	: GPGREY
Product group	: Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use	: General purpose, ready for use, fast drying primer for application onto clean steel.
-----------------	--

1.4. Supplier's details

Manufacturer

Dura Paints (Pty) Ltd.
5 Wakefield Road; Founders View South.
P.O. Box 303
1610 Edenvale; Johannesburg – South Africa
T 011 452 5221
orders@durapaints.co.za - www.durapaints.co.za

1.5. Emergency phone number

Emergency number	: 079 494 2731 / 011 452 5221
------------------	-------------------------------

SECTION 2: Hazard identification

2.1. GHS classification of the substance/mixture and any national or regional information

Classification according to the United Nations GHS

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Skin sensitisation, Category 1	H317
Germ cell mutagenicity, Category 1B	H340
Carcinogenicity, Category 1B	H350
Reproductive toxicity, Category 2	H361
Specific target organ toxicity – single exposure, Category 1	H370
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity – Repeated exposure, Category 2	H373
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Acute Hazard, Category 1	H400
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects	: Highly flammable liquid and vapour, May cause cancer, May cause genetic defects, Suspected of damaging fertility or the unborn child, May cause damage to organs through prolonged or repeated exposure, Causes damage to organs, May cause drowsiness or dizziness, Causes skin irritation, May cause an allergic skin reaction, Causes serious eye irritation, May be fatal if swallowed and enters airways, Very toxic to aquatic life, Toxic to aquatic life with long lasting effects.
---	---

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

2.2. GHS label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS ZA)

:



Signal word (GHS ZA)

: Danger

Hazardous ingredients

: Naphtha (petroleum), hydrotreated heavy; Xylene; Hexane; Toluene; Naphta (petroleum), hydrotreated light; Cyclohexane; Solvent naphtha (petroleum), light arom.; Fatty acids, tall-oil, compds. with oleylamine; Talc; Silicon dioxide; Aluminium oxide; Cobalt bis(2-ethylhexanoate); Methanol

Hazard statements (GHS ZA)

: H225 - Highly flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H315+H319 - Causes skin irritation and serious eye irritation
H317 - May cause an allergic skin reaction
H336 - May cause drowsiness or dizziness
H340 - May cause genetic defects (Inhalation, Dermal, Oral)
H350 - May cause cancer (Inhalation, Dermal, Oral)
H361 - Suspected of damaging fertility, Suspected of damaging the unborn child. (Inhalation, Dermal, Oral)
H370 - Causes damage to organs (central nervous system, kidneys, liver, Skin) (Dermal, Inhalation, Oral)
H373 - May cause damage to organs (peripheral nervous system, central nervous system, kidneys, liver) through prolonged or repeated exposure (Dermal, Inhalation, Oral)
H400 - Very toxic to aquatic life
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS ZA)

: P101 - If medical advice is needed, have product container or label and product safety data sheet at hand.
P102 - Keep out of reach of children.
P103 - Read carefully and follow all instructions.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240 - Ground and bond container and receiving equipment.
P261 - Avoid breathing mist, spray, vapours, fume.
P263 - Avoid contact during pregnancy and while nursing.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear eye protection, protective clothing, protective gloves.
P501 - Dispose of container to Recycling, according to local regulations.
P101 - If medical advice is needed, have product container or label and product safety data sheet at hand.; P102 - Keep out of reach of children.; P103 - Read carefully and follow all instructions.; P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.; P240 - Ground and bond container and receiving equipment.; P261 - Avoid breathing mist, spray, vapours, fume.; P263 - Avoid contact during pregnancy and while nursing.; P271 - Use only outdoors or in a well-ventilated area.; P273 - Avoid release to the environment.; P280 - Wear eye protection, protective clothing, protective gloves.; P501 - Dispose of container to Recycling, according to local regulations.

P-statements for label (GHS-ZA)

2.3. Other hazards which do not result in classification or are not covered by the GHS

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

3.2. Mixture

Name	Product identifier	%	Classification according to the United Nations GHS
Toluene	CAS-No.: 108-88-3	3.43 – 17.15	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Talc	CAS-No.: 14807-96-6	10 – 15	Acute Tox. Not classified (Oral) Acute Tox. 4 (Inhalation:dust,mist), H332 STOT RE 2, H373 Aquatic Acute Not classified Aquatic Chronic Not classified
Silicon dioxide	CAS-No.: 7631-86-9	10.4002	Acute Tox. 4 (Dermal), H312 Acute Tox. Not classified (Inhalation:dust,mist) STOT RE Not classified Aquatic Acute Not classified Aquatic Chronic Not classified
Xylene	CAS-No.: 1330-20-7	1.717683 – 10.303415	Flam. Liq. 3, H226 Acute Tox. Not classified (Oral) Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. Not classified (Inhalation:vapour) Skin Irrit. 2, H315 STOT SE 1, H370 STOT RE Not classified Aquatic Chronic 2, H411
Naphta (petroleum), hydrotreated light	CAS-No.: 64742-49-0	1.029 – 10.29	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 3 (Inhalation:vapour), H331 Muta. 1B, H340 Carc. 1B, H350 STOT RE Not classified Asp. Tox. 1, H304
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	-	6.7075 – 9.3905	Flam. Liq. 3, H226 Acute Tox. Not classified (Oral) Acute Tox. 3 (Inhalation:vapour), H331 STOT RE Not classified Asp. Tox. 1, H304
Naphtha (petroleum), hydrotreated heavy	CAS-No.: 64742-48-9	6.7075 – 8.049	Flam. Liq. 3, H226 Acute Tox. Not classified (Oral) Acute Tox. 3 (Inhalation:vapour), H331 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Name	Product identifier	%	Classification according to the United Nations GHS
Cyclohexane	CAS-No.: 110-82-7	0.343 – 3.43	Flam. Liq. 2, H225 Acute Tox. Not classified (Oral) Acute Tox. Not classified (Inhalation:vapour) Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Titanium dioxide	CAS-No.: 13463-67-7	2.98745	Acute Tox. Not classified (Oral) Acute Tox. Not classified (Inhalation:dust,mist) Carc. 2, H351 Aquatic Chronic Not classified
Aluminium oxide	CAS-No.: 1344-28-1	2.6671	Acute Tox. Not classified (Oral) Acute Tox. Not classified (Inhalation:dust,mist) STOT RE 1, H372 Aquatic Acute 1, H400
Hexane	CAS-No.: 110-54-3	0.343 – 1.715	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Sodium oxide	CAS-No.: 1313-59-3	1.639	Skin Corr. 1, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute Not classified Aquatic Chronic Not classified
Methanol	CAS-No.: 67-56-1	1.489851	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Acute Tox. Not classified (Inhalation:dust,mist) Carc. 2, H351 STOT SE 1, H370 Aquatic Chronic Not classified
Cobalt bis(2-ethylhexanoate)	CAS-No.: 136-52-7	0.426	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT RE 1, H372 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 2, H411

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Name	Product identifier	%	Classification according to the United Nations GHS
Solvent naphtha (petroleum), light arom.	CAS-No.: 64742-95-6	0.18 – 0.3	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Muta. 1B, H340 Carc. 1B, H350 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Fatty acids, tall-oil, compds. with oleylamine	CAS-No.: 85711-55-3	0.12 – 0.15	Eye Dam. 1, H318 Skin Sens. 1A, H317 STOT RE 2, H373 Aquatic Chronic Not classified

SECTION 4: First aid measures

4.1. Description of necessary first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.
Self protection of the first-aiders	: First-aiders should pay attention to their own protection and use the recommended personal protective equipment (see section 8).

4.2. Most important symptoms/effect, acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: Risk of lung oedema.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective actions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.
Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate non-essential personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

For containment : Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Packaging materials : Always store product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Xylene (1330-20-7)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Xylene, o-, m-, p- or mixed isomers
OEL eight hour TWA	300 ppm
RHCA - STEL/C	200 ppm
Remark	SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Xylene, o-, m-, p- or mixed isomers
OEL TWA	218 mg/m ³
	50 ppm
OEL STEL	435 mg/m ³
	100 ppm
Remark	Sk (Danger of cutaneous absorption)
Regulatory reference	Government Notice No. R 904
South Africa - Biological limit values	
Local name	Xylenes
BEI	1.5 g/g creatinine Parameter: Methylhippuric acids - Medium: urine - Sampling time: End of shift
Regulatory reference	Government Notice No. R. 280, 2021
Hexane (110-54-3)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	n-Hexane
RHCA - STEL/C	100 ppm
Remark	SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	n-Hexane
OEL TWA	70 mg/m ³
	20 ppm
Regulatory reference	Government Notice No. R 904
South Africa - Biological limit values	
Local name	n-Hexane
BEI	0.4 mg/l Parameter: 2,5-Hexanedione - Medium: urine - Sampling time: End of shift at end of workweek
Regulatory reference	Government Notice No. R. 280, 2021
Toluene (108-88-3)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Toluene
OEL eight hour TWA	150 ppm
	560 mg/m ³

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Toluene (108-88-3)	
RHCA - STEL/C	40 ppm
	50 ppm
	188 mg/m ³
Remark	SKIN (danger of cutaneous absorption) Sk
Regulatory reference	Government Notice No. R. 280, 2021 Government Notice. R: 1179
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Toluene
OEL TWA	188 mg/m ³
	50 ppm
OEL STEL	560 mg/m ³
	150 ppm
Remark	Sk (Danger of cutaneous absorption)
Regulatory reference	Government Notice No. R 904
South Africa - Biological limit values	
Local name	Toluene
BEI	0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: Prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: End of shift 0.3 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: End of shift - Notations: B (background)
Regulatory reference	Government Notice No. R. 280, 2021
Cyclohexane (110-82-7)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Cychlohexane
RHCA - STEL/C	200 ppm
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Cychlohexane
OEL TWA	340 mg/m ³
	100 ppm
OEL STEL	1030 mg/m ³
	300 ppm
Regulatory reference	Government Notice No. R 904
Talc (14807-96-6)	
South Africa - Occupational Exposure Limits (Maximum Limits)	
Local name	Talc (containing asbestos fibres)
RHCA - OEL	0.6 fibers/mL (measured over a continuous 10-minute period)
RHCA - STEL/C	0.1 fibers/mL
Remark	CARC (denotes carcinogenicity, which is based on GHS categorisation, including category 1A and 1B)

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Talc (14807-96-6)	
Regulatory reference	Government Notice No. R. 280, 2021; Government Notice No. R. 11196, 2020
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Talc (containing no asbestos fibers)
RHCA - STEL/C	4 mg/m ³ (E: the value is for particulate matter containing no asbestos and ≤ 1% crystalline silica, R: respirable fraction) 10 mg/m ³ total inhalable dust 1 mg/m ³ respirable dust
Regulatory reference	Government Notice No. R. 280, 2021 Government Notice. R: 1179
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Talc
OEL TWA	10 mg/m ³ inhalable particulate 1 mg/m ³ respirable particulate
Regulatory reference	Government Notice No. R 904
Silicon dioxide (7631-86-9)	
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Silica, amorphous
OEL TWA	6 mg/m ³ inhalable particulate 3 mg/m ³ respirable particulate
Regulatory reference	Government Notice No. R 904
Aluminium oxide (1344-28-1)	
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Aluminium oxides
OEL TWA	10 mg/m ³ 5 mg/m ³
Remark	[c] The OEL for Aluminium does not include exposure to aluminium coated with mineral oil, or to fume arising from aluminium welding processes.
Regulatory reference	Government Notice No. R 904
Titanium dioxide (13463-67-7)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Titanium dioxide
RHCA - STEL/C	10 mg/m ³ 10 mg/m ³ total inhalable dust 5 mg/m ³ respirable dust
Remark	CARC (denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B)
Regulatory reference	Government Notice No. R. 280, 2021 Government Notice. R: 1179
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Titanium dioxide
OEL TWA	10 mg/m ³ inhalable particulate 5 mg/m ³ respirable particulate
Regulatory reference	Government Notice No. R 904

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Methanol (67-56-1)

South Africa - Occupational Exposure Limits (Restricted Limits)

Local name	Methanol [methyl alcohol]
OEL eight hour TWA	500 ppm
RHCA - STEL/C	400 ppm
Remark	SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021

South Africa - Occupational Exposure Limits (Airborne Pollutants)

Local name	Methanol (Methyl alcohol)
OEL TWA	260 mg/m ³ 200 ppm
OEL STEL	310 mg/m ³ 250 ppm
Remark	Sk (Danger of cutaneous absorption)
Regulatory reference	Government Notice No. R 904

South Africa - Biological limit values

Local name	Methanol
BEI	15 mg/l Parameter: Methanol - Medium: urine - Sampling time: End of shift - Notations: B (background), Ns (non-specific)
Regulatory reference	Government Notice No. R. 280, 2021

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: [In case of inadequate ventilation] wear respiratory protection.
Personal protective equipment symbol(s)	



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Opaque.
Colour	: Grey
Odour	: Aromatic solvent like odour
Odour threshold	: No data available
pH	: No data available

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 110.6 °C Derived from value for Toluene; Source: HSDB
Flash point	: 4 °C Derived from value for Toluene; Source: HSDB
Auto-ignition temperature	: 480 °C Derived from value for Toluene; Source: HSDB
Decomposition temperature	: No data available
Flammability	: Highly flammable liquid and vapour.
Vapour pressure	: No data available
Vapour pressure at 50°C	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: ≈ 1.04 Source: Product TDS
Relative density of saturated gas/air mixture	: No data available
Density	: No data available
Relative gas density	: No data available
Solubility	: insoluble in water. soluble in most organic solvents.
Partition coefficient n-octanol/water (Log Pow)	: 2.73 Derived from value for Toluene; Source: HSDB
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: ≈ 0.45 mm²/s Derived from Toluene value: at 25 deg. C at atmospheric pressure; Source: Journal of Chemical & Engineering Data
Viscosity, dynamic	: 0.56 cP Derived from value for Toluene; Source: HSDB
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available
Lower explosion limit	: No data available
Upper explosion limit	: 1 – 7.8 % Derived from value for Toluene; Source: GESTIS
Physical state	: Liquid
Appearance	: Opaque.

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10: Stability and Reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical Stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Naphtha (petroleum), hydrotreated heavy (64742-48-9)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	≥ 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	≥ 5.61 mg/l Source: ECHA

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics

LD50 oral rat	≥ 5000 mg/kg bodyweight Source : Echa
LD50 oral	> 5000 mg/kg bodyweight Animal:
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	≥ 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5 mg/l Source : Echa

Xylene (1330-20-7)

LD50 oral rat	> 3523 – < 6631 mg/kg bodyweight XYLENE : ECHA
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male, Remarks on results: other:
LC50 Inhalation - Rat	≥ 27.124 mg/l XYLENE : ECHA

Hexane (110-54-3)

LD50 oral rat	≈ 1600 mg/kg bodyweight Source : ECHA
LD50 dermal rabbit	> 3350 mg/kg bodyweight Source : ECHA
LC50 Inhalation - Rat	≥ 17.6 mg/l Source: ECHA

Toluene (108-88-3)

LD50 oral rat	5580 mg/kg Source: ECHA
LD50 dermal rabbit	> 5000 mg/kg Source: ECHA
LC50 Inhalation - Rat	> 25.7 – < 30 mg/l Source: ECHA
LC50 Inhalation - Rat (Vapours)	> 20 mg/l Source: ECHA

Naphta (petroleum), hydrotreated light (64742-49-0)

LD50 oral rat	≥ 5000 mg/kg bodyweight ECHA
LD50 dermal rat	2800 – 3100 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	≥ 2000 mg/kg bodyweight ECHA
LC50 Inhalation - Rat	> 5.61 mg/l ECHA

Cyclohexane (110-82-7)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
---------------	--

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Cyclohexane (110-82-7)	
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 32.88 mg/l/4h Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
Solvent naphtha (petroleum), light arom. (64742-95-6)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	≈ 2000 mg/kg bodyweight Source : ECHA
Fatty acids, tall-oil, compds. with oleylamine (85711-55-3)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), Guideline: EU Method B.1 tris (Acute Oral Toxicity - Acute Toxic Class Method), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity), Guideline: other:, Remarks on results: other:
Talc (14807-96-6)	
LD50 oral rat	> 5000 mg/l Animal: rat, Animal sex: male, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 2.1 mg/l Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
Silicon dioxide (7631-86-9)	
LD50 oral rat	3160 mg/kg Source: TOMES; HAZARTEXT
LD50 dermal rat	≥ 2000 mg/kg bodyweight Source: ECHA
LD50 dermal rabbit	> 5000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Dust/Mist)	5.01 mg/l Source: ECHA
Aluminium oxide (1344-28-1)	
LD50 oral rat	2000 – 15900 mg/kg bodyweight Source: ECHA
LC50 Inhalation - Rat	≈ 7.6 mg/l 60 min; Source: ECHA
Titanium dioxide (13463-67-7)	
LD50 oral rat	> 2000 – < 25000 mg/kg bodyweight Practically nontoxic; Source: ECHA
LC50 Inhalation - Rat (Dust/Mist)	> 3.43 – < 6.82 mg/l/4h Source: ECHA
Cobalt bis(2-ethylhexanoate) (136-52-7)	
LD50 oral rat	3129 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), 95% CL: 1750 - 5000
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Methanol (67-56-1)	
LD50 oral rat	1187 – 2769 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	≥ 17100 mg/kg bodyweight Source: ECHA
LC50 Inhalation - Rat	≈ 43.7 mg/l Source: ECHA
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: May cause genetic defects (Inhalation, Dermal, Oral).

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Carcinogenicity : May cause cancer (Inhalation, Dermal, Oral).

Toluene (108-88-3)	
IARC group	3 - Not classifiable

Silicon dioxide (7631-86-9)	
IARC group	3 - Not classifiable

Titanium dioxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Suspected of damaging fertility, Suspected of damaging the unborn child. (Inhalation, Dermal, Oral).

Reproductive toxicity : Suspected of damaging fertility, Suspected of damaging the unborn child. (Inhalation, Dermal, Oral).

STOT-single exposure : Causes damage to organs (central nervous system, kidneys, liver, Skin) (Dermal, Inhalation, Oral). May cause drowsiness or dizziness.

Xylene (1330-20-7)	
LOAEL (oral, rat)	≈ 150 mg/kg bodyweight XYLENE : ECHA
NOAEL (oral, rat)	≈ 250 mg/kg bodyweight XYLENE : ECHA
NOAEC (inhalation, rat, gas)	> 450 – < 1800 ppmv/4h XYLENE : 12H : ECHA
STOT-single exposure	Causes damage to organs (central nervous system) (Inhalation).

Hexane (110-54-3)	
STOT-single exposure	May cause drowsiness or dizziness.

Toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.

Cyclohexane (110-82-7)	
STOT-single exposure	May cause drowsiness or dizziness.

Solvent naphtha (petroleum), light arom. (64742-95-6)	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.

Sodium oxide (1313-59-3)	
STOT-single exposure	May cause respiratory irritation.

Methanol (67-56-1)	
STOT-single exposure	Causes damage to organs (optic nerve, central nervous system) (Inhalation, Dermal, Oral).

STOT-repeated exposure : May cause damage to organs (peripheral nervous system, central nervous system, kidneys, liver) through prolonged or repeated exposure (Dermal, Inhalation, Oral).

Naphtha (petroleum), hydrotreated heavy (64742-48-9)	
NOAEC (inhalation, rat, 28 days)	≥ 1.402 mg/l Source: ECHA

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	
NOAEL (oral, rat, 28 days)	> 1000 mg/kg bodyweight/day Source : Echa
NOAEC (inhalation, rat, 28 days)	> 10.4 mg/l Source : Echa
NOAEL (oral, rat, 90 days)	> 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	> 10.4 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
Hexane (110-54-3)	
LOAEL (oral, rat, 90 days)	≥ 200 mg/kg bodyweight/day Source : ECHA
NOAEL (oral, rat, 28 days)	≥ 40 mg/kg bodyweight/day Source : ECHA
STOT-repeated exposure	May cause damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation).
Toluene (108-88-3)	
LOAEL (oral, rat, 90 days)	≈ 1250 mg/kg bodyweight/day Source: ECHA
LOAEC (inhalation, rat, gas, 90 days)	≈ 2.261 mg/l Source: ECHA
NOAEL (oral, rat, 28 days)	≥ 625 mg/kg bodyweight/day
NOAEC (inhalation, rat, 28 days)	> 2.261 – < 4.71 mg/l Source : ECHA
NOAEL (oral, rat, 90 days)	≈ 625 mg/kg bodyweight/day Rat
NOAEC (inhalation, rat, gas, 90 days)	1.131 – 2.355 mg/l Air, Source: ECHA
NOAEC (inhalation, rat, vapour, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)
STOT-repeated exposure	May cause damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation).
Naphta (petroleum), hydrotreated light (64742-49-0)	
LOAEC (inhalation, rat, vapour, 90 days)	16.6 mg/l air Animal: rat, Animal sex: male
NOAEC (inhalation, rat, 28 days)	≈ 1.402 mg/l ECHA
NOAEC (inhalation, rat, vapour, 90 days)	3.3 mg/l air Animal: rat, Animal sex: male
Cyclohexane (110-82-7)	
NOAEC (inhalation, rat, gas, 28 days)	> 500 – < 7000 ppmv/6h/day
Solvent naphtha (petroleum), light arom. (64742-95-6)	
LOAEC (inhalation, rat, vapour, 90 days)	≈ 1.402 mg/l Source : ECHA
Fatty acids, tall-oil, compds. with oleylamine (85711-55-3)	
NOAEL (oral, rat, 90 days)	7.1 – 21.9 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Talc (14807-96-6)	
NOAEL (oral, rat, 28 days)	> 100 mg/kg bodyweight/day Source: ECHA
NOAEL (oral, rat, 90 days)	100 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Silicon dioxide (7631-86-9)	
NOAEL (oral, rat, 28 days)	> 2500 mg/kg bodyweight/day Source: ECHA
NOAEC (inhalation, rat, 28 days)	> 1.3 – < 46 mg/l Source: ECHA

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Aluminium oxide (1344-28-1)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.015 mg/l air Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Cobalt bis(2-ethylhexanoate) (136-52-7)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.31 mg/l air Animal: rat
NOAEL (oral, rat, 90 days)	3 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Methanol (67-56-1)	
NOAEC (inhalation, rat, 28 days)	> 260 – < 6660 mg/l Source: ECHA
Aspiration hazard : May be fatal if swallowed and enters airways.	
Dura Paints - Genral Purpose Primer - Grey RFU	
Viscosity, kinematic	≈ 0.45 mm ² /s Derived from Toluene value: at 25 deg. C at atmospheric pressure; Source: Journal of Chemical & Engineering Data

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Very toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	
LC50 - Fish [1]	≈ 76.8 g/l Source: ECHA
EC50 72h - Algae [1]	≈ 100 mg/l Source : Echa
NOEC (chronic)	0.011 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Xylene (1330-20-7)	
LC50 - Fish [1]	> 2.6 – < 9.6 mg/l Source: ECHA
EC50 - Crustacea [1]	≥ 10.389 mg/l Source: Echa
EC50 72h - Algae [1]	> 4.6 – < 4.9 mg/l XYLENE : Aquatic Algae : ECHA
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
NOEC chronic algae	≈ 0.44 mg/l XYLENE : Aquatic Algae 73H : ECHA
Hexane (110-54-3)	
EC50 72h - Algae [1]	≈ 9.285 mg/l Source: ECHA
Toluene (108-88-3)	
LC50 - Fish [1]	5.5 mg/l Source: ECHA
EC50 - Crustacea [1]	3.78 mg/l Source: ECHA
EC50 72h - Algae [1]	≥ 134 mg/l Source: ECHA
ErC50 algae	≥ 84 mg/l Source : ECHA
LOEC (chronic)	≥ 2.76 mg/l 7 Days - Source : ECHA

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Toluene (108-88-3)	
NOEC (chronic)	0.74 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC chronic fish	≥ 1.39 mg/l Source : ECHA
NOEC chronic crustacea	≈ 0.74 mg/l Source: ECHA
NOEC chronic algae	≥ 10 mg/l Sourc: ECHA
Naphta (petroleum), hydrotreated light (64742-49-0)	
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Cyclohexane (110-82-7)	
LC50 - Fish [1]	≥ 4.53 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	≥ 0.9 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	≥ 4.42 mg/l Fresh water algae - Source : ECHA
NOEC chronic algae	≥ 0.925 mg/l freshwater algae - Source : ECHA
Solvent naphtha (petroleum), light arom. (64742-95-6)	
LC50 - Fish [1]	> 8.2 – < 10 mg/l Species: Oncorhynchus mykiss; Source : ECHA
ErC50 algae	≈ 3.1 mg/l Source : Echa
NOEC chronic fish	≈ 10 mg/l Source : ECHA
Fatty acids, tall-oil, compds. with oleylamine (85711-55-3)	
LC50 - Fish [1]	≥ 100 mg/l Source : ECHA
LOEC (chronic)	4.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Talc (14807-96-6)	
LC50 - Fish [1]	89581.02 mg/l Test organisms (species): other:
LC50 - Fish [2]	110000 mg/l Test organisms (species): other:
EC50 96h - Algae [1]	7202.7 mg/l Test organisms (species): other:
NOEC (chronic)	1459798 mg/l Test organisms (species): other: Duration: '30 d'
NOEC chronic fish	> 1.413 – < 5.98 g/l 30 days; Source: ECHA
NOEC chronic algae	≈ 91.81 mg/l Marine water algae; Source: ECHA
Silicon dioxide (7631-86-9)	
LC50 - Fish [1]	10000 mg/l Source: ECHA
EC50 - Crustacea [1]	> 5000 mg/l Source: ECHA
EC50 72h - Algae [1]	> 173.1 mg/l Source: ECHA
EC50 96h - Algae [1]	> 217.576 – < 217.6 mg/l Source: ECHA
LOEC (chronic)	≈ 149.2 mg/l Source: ECHA
NOEC (chronic)	> 68 – < 250 mg/l 21 days; Source: ECHA
NOEC chronic fish	> 57.001 – < 86.03 mg/l Source: ECHA
NOEC chronic algae	> 42.1 – < 42.11 mg/l Source: ECHA
Aluminium oxide (1344-28-1)	
LC50 - Fish [1]	78 – 218644.1 µg/l Source: ECHA
EC50 - Crustacea [1]	1.5 – 500 mg/l Source: ECHA
EC50 - Crustacea [2]	5.7 – 5000000 µg/l Source: ECHA

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Aluminium oxide (1344-28-1)	
EC50 72h - Algae [1]	1.05 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (acute)	≈ 5.314 mg/l (7 days); Source: ECHA
NOEC (chronic)	4.7 – 2.31 mg/l (28 days); Source: ECHA
NOEC chronic crustacea	0.2326 – 0.4538 mg/l (42 days); Source: ECHA
NOEC chronic algae	≈ 1 g/l (6 days); Source: ECHA
Sodium oxide (1313-59-3)	
LC50 - Fish [1]	208000000 mg/l Source: QSAR
EC50 96h - Algae [1]	56800000 mg/l Source: QSAR
Titanium dioxide (13463-67-7)	
EC50 - Crustacea [1]	> 2.41 – < 103.9 mg/l Source: ECHA
EC50 - Other aquatic organisms [1]	> 100 mg/l Test organisms (species):
EC50 72h - Algae [1]	≥ 100 mg/l Source: ECHA
LOEC (acute)	≈ 160 mg/l Fish, 4 Days; Source: ECHA
LOEC (chronic)	≈ 5 mg/l Crustacea, 21 Days; Source: ECHA
NOEC (acute)	0.004 – 0.08 mg/l 28 Dday, fish; Source: Echa
NOEC (chronic)	≥ 100 mg/l 28 days; Source: ECHA
NOEC chronic fish	> 80 – < 160 mg/l 6 days; Source: ECHA
Cobalt bis(2-ethylhexanoate) (136-52-7)	
LC50 - Fish [1]	> 1.406 – < 180 mg/l 4 days; Source: ECHA
EC50 - Crustacea [1]	5.89 mg/l Test organisms (species): Daphnia magna
ErC50 algae	0.31 mg/l freshwater algae; Source: ECHA
ErC50 other aquatic plants	0.0241 mg/l marinewater algae; Source: ECHA
NOEC (chronic)	> 0.00683 – < 3.73 mg/l 28 days; Source: ECHA
NOEC chronic fish	≥ 31.196 mg/l 28 Days; Source: ECHA
Methanol (67-56-1)	
LC50 - Fish [1]	15400 mg/l Test organisms (species): Lepomis macrochirus
EC50 - Crustacea [1]	≈ 18.26 g/l Source: ECHA
EC50 96h - Algae [1]	≈ 22000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
NOEC (chronic)	208 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	446.7 mg/l Test organisms (species): Pimephales promelas Duration: '28 d'
NOEC chronic algae	≥ 208 mg/l Source: ECHA
12.2. Persistence and degradability	
Dura Paints - Genral Purpose Primer - Grey RFU	
Persistence and degradability	Not rapidly degradable

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Naphtha (petroleum), hydrotreated heavy (64742-48-9)	
Persistence and degradability	
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	
Persistence and degradability	
Xylene (1330-20-7)	
Persistence and degradability	
Chemical oxygen demand (COD)	> 2.56 – < 2.91 g O ₂ /g substance
Hexane (110-54-3)	
Persistence and degradability	
Toluene (108-88-3)	
Persistence and degradability	
Naphta (petroleum), hydrotreated light (64742-49-0)	
Persistence and degradability	
Cyclohexane (110-82-7)	
Persistence and degradability	
Solvent naphtha (petroleum), light arom. (64742-95-6)	
Persistence and degradability	
Fatty acids, tall-oil, compds. with oleylamine (85711-55-3)	
Persistence and degradability	
Talc (14807-96-6)	
Persistence and degradability	
Silicon dioxide (7631-86-9)	
Persistence and degradability	
Aluminium oxide (1344-28-1)	
Persistence and degradability	
Sodium oxide (1313-59-3)	
Persistence and degradability	
Titanium dioxide (13463-67-7)	
Persistence and degradability	
Cobalt bis(2-ethylhexanoate) (136-52-7)	
Persistence and degradability	
Methanol (67-56-1)	
Persistence and degradability	
Biochemical oxygen demand (BOD)	> 1.067 – < 1.236 g O ₂ /g substance Source: ECHA
12.3. Bioaccumulative potential	
Dura Paints - Genral Purpose Primer - Grey RFU	
Partition coefficient n-octanol/water (Log Kow)	2.73 Derived from value for Toluene; Source: HSDB
Bioaccumulative potential	No additional information available

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	
Partition coefficient n-octanol/water (Log Kow)	> 1.99 – < 6.73 @ 20 °C and pH 7; Source : Echa
Xylene (1330-20-7)	
Partition coefficient n-octanol/water (Log Pow)	> 3.155 – < 3.16 XYLENE @ 20 °C : ECHA
Partition coefficient n-octanol/water (Log Kow)	> 3.12 – < 3.2 XYLENE @ 20 °C and pH 7: ECHA
Hexane (110-54-3)	
Partition coefficient n-octanol/water (Log Kow)	> 3.42 – < 5.8 At 20 °C and pH 7 - Source: ECHA
Toluene (108-88-3)	
Partition coefficient n-octanol/water (Log Kow)	2.73 Source: HSDB
Cyclohexane (110-82-7)	
Bioconcentration factor (BCF REACH)	≈ 167 l/kg ww Source : ECHA
Partition coefficient n-octanol/water (Log Pow)	≈ 3.44 @ 20 °C Source : ECHA
Partition coefficient n-octanol/water (Log Kow)	≈ 3.44 @ 25 °C and pH 7 Source : ECHA
Fatty acids, tall-oil, compds. with oleylamine (85711-55-3)	
Partition coefficient n-octanol/water (Log Kow)	> 1 – < 6.2 @ 25 °C and pH 4 - 9; Source : ECHA
Talc (14807-96-6)	
Partition coefficient n-octanol/water (Log Kow)	≈ -9.4 @ 25 °C and pH 7; Source: ECHA
Silicon dioxide (7631-86-9)	
Partition coefficient n-octanol/water (Log Kow)	≈ 0.53 @ 25 °C and pH 7; Source: ECHA
Cobalt bis(2-ethylhexanoate) (136-52-7)	
Partition coefficient n-octanol/water (Log Kow)	≈ 2.96 @ 20 °C and pH 7; Source: ECHA
Bioaccumulative potential	Not biodegradable.
Methanol (67-56-1)	
Partition coefficient n-octanol/water (Log Pow)	≈ -0.77 @ 20 °C; Source: ECHA
Partition coefficient n-octanol/water (Log Kow)	≈ -0.77 Source: ECHA
12.4. Mobility in soil	
Dura Paints - Genral Purpose Primer - Grey RFU	
Mobility in soil	No additional information available
Xylene (1330-20-7)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	≈ 537 XYLENE: @ 20 °C : ECHA
Hexane (110-54-3)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	≈ 2187.76 @ 20 °C - Source : ECHA
Toluene (108-88-3)	
Surface tension	≈ 27.73 mN/m
Cyclohexane (110-82-7)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	≈ 770 at 20°C; Source: ECHA

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Fatty acids, tall-oil, compds. with oleylamine (85711-55-3)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	≈ 4.6 20°C; Source : ECHA
--	---------------------------

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No additional information available

SECTION 13: Disposal Considerations

13.1. Disposal methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Ecological waste information	: The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.
Additional information	: Flammable vapours may accumulate in the container. Do not re-use empty containers.

SECTION 14: Transport information

In accordance with SANS / UN RTDG / IMDG / IATA

SANS	UN RTDG	IMDG	IATA
14.1. UN number			
1263	1263	1263	1263
14.2. UN Proper Shipping Name			
PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	Paint
Transport document description			
Not applicable	UN 1263 PAINT RELATED MATERIAL, 3, II	UN 1263 PAINT RELATED MATERIAL, 3, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1263 Paint, 3, II, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)			
3	3	3	3
	 Not applicable		
14.4. Packing group, if applicable			
II	II	II	II
14.5. Environmental hazards			
Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes
No supplementary information available			

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

14.6. Special precautions for user

SANS

Special provisions (SANS)	: 163, 187
Limited quantities (SANS)	: 5 L
Excepted quantities (SANS)	: E2
Packagings, large packagings and IBCs Packing instructions (SANS)	: P001, IBC02
Packagings, large packagings and IBCs Special packing instructions (SANS)	: PP1
Portable tank and bulk containers instructions (SANS)	: T4
Portable tank and bulk container special provisions (SANS)	: TP1, TP8, TP28

UN RTDG

Special provisions (UN RTDG)	: 163, 367
Limited quantities (UN RTDG)	: 5L
Excepted quantities (UN RTDG)	: E2
Packing instruction (UN RTDG)	: P001, IBC02
Special packing provisions (UN RTDG)	: PP1
Portable tank and bulk container special instructions (UN RTDG)	: T4
Portable tank and bulk container special provisions (UN RTDG)	: TP1, TP8, TP28

IMDG

Special provisions (IMDG)	: 163, 367
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP8, TP28
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG)	: B
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

IATA

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

14.7. Transport in bulk according to IMO instructions

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

15.1.1. OCCUPATIONAL HEALTH AND SAFETY ACT, 1993

Prohibited Hazardous Chemical Agents

Not regulated

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

15.1.2. National Environmental Management Act, 1998

Regulation No. 51358 (Prior Informed Consent Procedure Regulations, 2024)

Not regulated

15.2. Safety, health, and environmental national regulations specific for the product

State or local regulations : This product complies with South African legal lead limit of 90ppm or less.

SECTION 16: Other information

Issue date : 24/07/2026
Revision date : 24/07/2026
Supersedes : 24/07/2026

Full text of H-statements:

H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H227	Combustible liquid
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H330	Fatal if inhaled
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects

Dura Paints - Genral Purpose Primer - Grey RFU

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Full text of H-statements:

H411	Toxic to aquatic life with long lasting effects
------	---

Safety Data Sheet (SDS), South Africa (HCA)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.