

SECTION 1: Identification of the substance/mixture and of the supplier/undertaking

1.1. GHS product identifier

Product form	: Mixture
Trade name	: Dura Paints - Hydro - Direct to Metal - Orange
Type of product	: Coatings
Product code	: HYDRODTMOR
Product group	: Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use	: Water-based coating for light industrial applications
-----------------	---

1.4. Supplier's details

Manufacturer

Dura Paints (Pty) Ltd.
5 Wakefield Road; Founders View South.
P.O. Box 303
1610 Edenvale; Johannesburg – South Africa
T 011 452 5221
orders@durapaints.co.za - www.durapaints.co.za

1.5. Emergency phone number

Emergency number	: 079 494 2731 / 011 452 5221
------------------	-------------------------------

SECTION 2: Hazard identification

2.1. GHS classification of the substance/mixture and any national or regional information

Classification according to the United Nations GHS

Skin sensitisation, Category 1	H317
Specific target organ toxicity – Repeated exposure, Category 2	H373
Full text of H-statements: see section 16	
Adverse physicochemical, human health and environmental effects	: May cause damage to organs through prolonged or repeated exposure, May cause an allergic skin reaction.

2.2. GHS label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS ZA)	:  
Signal word (GHS ZA)	: Warning
Hazardous ingredients	: 2-(2-butoxyethoxy)ethanol; Benzothiazole-2-thiol; barium sulfate
Hazard statements (GHS ZA)	: H317 - May cause an allergic skin reaction H373 - May cause damage to organs (lungs, central nervous system) through prolonged or repeated exposure (Inhalation)
Precautionary statements (GHS ZA)	: P101 - If medical advice is needed, have product container or label and product safety data sheet at hand. P102 - Keep out of reach of children. P103 - Read carefully and follow all instructions. P260 - Do not breathe dusts or mists.

Dura Paints - Hydro - Direct to Metal - Orange

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

P-statements for label (GHS-ZA)	P280 - Wear eye protection, protective clothing, protective gloves. P302+P352 - IF ON SKIN: Wash with plenty of soap and water P333+P313 - If skin irritation or rash occurs: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse. P501 - Dispose of container to recycling, according to local regulations. : P101 - If medical advice is needed, have product container or label and product safety data sheet at hand.; P102 - Keep out of reach of children.; P103 - Read carefully and follow all instructions.; P260 - Do not breathe dusts or mists.; P280 - Wear eye protection, protective clothing, protective gloves.; P302+P352 - IF ON SKIN: Wash with plenty of soap and water; P333+P313 - If skin irritation or rash occurs: Get medical advice/attention; P362+P364 - Take off contaminated clothing and wash it before reuse.; P501 - Dispose of container to recycling, according to local regulations.
---------------------------------	---

2.3. Other hazards which do not result in classification or are not covered by the GHS

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to the United Nations GHS
2-(2-butoxyethoxy)ethanol	CAS-No.: 112-34-5	2.5245 – 7.524	Flam. Liq. Not classified Eye Irrit. 2, H319 STOT RE 2, H373 Aquatic Chronic Not classified
barium sulfate	CAS-No.: 7727-43-7	0.4 – 1.5	Acute Tox. Not classified (Oral) STOT RE 2, H373 Aquatic Chronic Not classified
Benzothiazole-2-thiol	CAS-No.: 149-30-4	0.02125 – 0.21375	Acute Tox. Not classified (Dermal) Skin Sens. 1, H317 STOT RE Not classified Aquatic Acute 1, H400 Aquatic Chronic 1, H410

SECTION 4: First aid measures

4.1. Description of necessary first aid measures

First-aid measures general	: Get medical advice/attention if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
Self protection of the first-aider	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effect, acute and delayed

Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.

Dura Paints - Hydro - Direct to Metal - Orange

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective actions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate non-essential personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

For containment	: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	: Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

Dura Paints - Hydro - Direct to Metal - Orange

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Keep cool. Protect from sunlight.
Packaging materials	: Always store product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

barium sulfate (7727-43-7)

South Africa - Occupational Exposure Limits (Restricted Limits)

Local name	Barium sulphate
RHCA - STEL/C	10 mg/m ³ (I: inhalable fraction, E: the value is for particulate matter containing no asbestos and ≤ 1% crystalline silica)
Regulatory reference	Government Notice No. R. 280, 2021

South Africa - Occupational Exposure Limits (Airborne Pollutants)

Local name	Barium sulphate
OEL TWA	2 mg/m ³
Regulatory reference	Government Notice No. R 904

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s)



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Viscous liquid.
Colour	: Orange
Odour	: slight
Odour threshold	: No data available
pH	: No data available
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available

Dura Paints - Hydro - Direct to Metal - Orange

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability	: Non flammable
Vapour pressure	: No data available
Vapour pressure at 50°C	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: ≈ 1.02
Relative density of saturated gas/air mixture	: No data available
Density	: No data available
Relative gas density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: > 300 – < 440 cP Source: Product TDS
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Physical state	: Liquid
Appearance	: Viscous liquid.

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10: Stability and Reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical Stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Dura Paints - Hydro - Direct to Metal - Orange

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

2-(2-butoxyethoxy)ethanol (112-34-5)	
LD50 oral rat	≥ 2410 mg/kg bodyweight Source: ECHA
LD50 dermal rabbit	≈ 2764 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), 95% CL: 2090 - 3645
Benzothiazole-2-thiol (149-30-4)	
LD50 oral rat	3800 mg/kg bodyweight Animal: rat, 95% CL: 3530 - 4100
LD50 dermal rabbit	> 7940 mg/kg bodyweight Animal: rabbit
LC50 Inhalation - Rat	> 1270 mg/l air Animal: rat
barium sulfate (7727-43-7)	
LD50 oral rat	> 5000 mg/kg bodyweight Source: ECHA
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
barium sulfate (7727-43-7)	
NOAEL (chronic, oral, animal/male, 2 years)	60 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:
NOAEL (chronic, oral, animal/female, 2 years)	75 mg/kg bodyweight Animal: rat, Animal sex: female, Remarks on results: other:
Reproductive toxicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: May cause damage to organs (lungs, central nervous system) through prolonged or repeated exposure (Inhalation).
2-(2-butoxyethoxy)ethanol (112-34-5)	
NOAEL (oral, rat, 28 days)	≥ 250 mg/kg bodyweight/day Source: ECHA
NOAEL (dermal, rat/rabbit, 28 days)	≥ 200 mg/kg bodyweight/day rat; Source: ECHA
NOAEC (inhalation, rat, gas, 28 days)	≥ 94 mg/l rat; Source: ECHA
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	< 200 mg/kg bodyweight Animal: rat, Guideline: other., Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Benzothiazole-2-thiol (149-30-4)	
LOAEL (oral, rat, 90 days)	≈ 750 mg/kg bodyweight/day Source: ECHA
NOAEL (oral, rat, 28 days)	≈ 375 mg/kg bodyweight/day Source: ECHA
barium sulfate (7727-43-7)	
NOAEL (oral, rat, 28 days)	> 61.1 – < 80.9 mg/kg bodyweight/day Source: ECHA
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified

Dura Paints - Hydro - Direct to Metal - Orange

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

2-(2-butoxyethoxy)ethanol (112-34-5)

LC50 - Fish [1]	≈ 1300 mg/l Test organisms (species): <i>Lepomis macrochirus</i>
EC50 - Crustacea [1]	≥ 100 mg/l Test organisms (species): <i>Daphnia magna</i>
EC50 96h - Algae [1]	> 100 mg/l Test organisms (species): <i>Desmodesmus subspicatus</i> (previous name: <i>Scenedesmus subspicatus</i>)
NOEC chronic crustacea	≈ 100 mg/l Source: ECHA
NOEC chronic algae	≥ 100 mg/l 4 day; Source: ECHA

Benzothiazole-2-thiol (149-30-4)

LC50 - Fish [1]	0.73 mg/l Test organisms (species): <i>Oncorhynchus mykiss</i> (previous name: <i>Salmo gairdneri</i>)
EC50 - Crustacea [1]	8.5 mg/l Test organisms (species): <i>Daphnia magna</i>
EC50 - Crustacea [2]	16.1 mg/l Test organisms (species): <i>Daphnia magna</i>
EC50 72h - Algae [1]	0.5 mg/l Test organisms (species): <i>Raphidocelis subcapitata</i> (previous names: <i>Pseudokirchneriella subcapitata</i> , <i>Selenastrum capricornutum</i>)
NOEC (chronic)	0.08 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d'
NOEC chronic fish	0.041 mg/l Test organisms (species): <i>Oncorhynchus mykiss</i> (previous name: <i>Salmo gairdneri</i>) Duration: '89 d'
NOEC chronic algae	≈ 0.06 mg/l Source: ECHA

barium sulfate (7727-43-7)

LC50 - Fish [1]	> 3.5 – < 174 mg/l Source: ECHA
EC50 - Crustacea [1]	≥ 58.8 mg/l Source: ECHA
EC50 72h - Algae [1]	> 1.15 mg/l Test organisms (species): <i>Pseudokirchneriella subcapitata</i> (previous names: <i>Raphidocelis subcapitata</i> , <i>Selenastrum capricornutum</i>)
EC50 72h - Algae [2]	> 30.07 mg/l Test organisms (species): <i>Pseudokirchneriella subcapitata</i> (previous names: <i>Raphidocelis subcapitata</i> , <i>Selenastrum capricornutum</i>)
NOEC (chronic)	≈ 58.8 mg/l Source: ECHA
NOEC chronic fish	> 1.26 – < 100 mg/l Source: ECHA
NOEC chronic algae	> 1.15 – < 100 mg/l Source: ECHA

12.2. Persistence and degradability

Dura Paints - Hydro - Direct to Metal - Orange

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

2-(2-butoxyethoxy)ethanol (112-34-5)

Persistence and degradability	
-------------------------------	--

Benzothiazole-2-thiol (149-30-4)

Persistence and degradability	
-------------------------------	--

Dura Paints - Hydro - Direct to Metal - Orange

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

barium sulfate (7727-43-7)

Persistence and degradability

12.3. Bioaccumulative potential

Dura Paints - Hydro - Direct to Metal - Orange

Bioaccumulative potential

No additional information available

2-(2-butoxyethoxy)ethanol (112-34-5)

Partition coefficient n-octanol/water (Log Pow)

≈ 1 @ 20 °C and pH7; Source: ECHA

Partition coefficient n-octanol/water (Log Kow)

≈ 1 @ 20 °C and pH7; Source: ECHA

Benzothiazole-2-thiol (149-30-4)

Partition coefficient n-octanol/water (Log Kow)

> 2.42 – < 2.86 @ pH 7; Source: ECHA

12.4. Mobility in soil

Dura Paints - Hydro - Direct to Metal - Orange

Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone

: Not classified

Other adverse effects

: No additional information available

SECTION 13: Disposal Considerations

13.1. Disposal methods

Regional waste regulation

: Disposal must be done according to official regulations.

Waste treatment methods

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations

: Disposal must be done according to official regulations.

Product/Packaging disposal recommendations

: Disposal must be done according to official regulations.

Additional information

: Do not re-use empty containers.

SECTION 14: Transport information

In accordance with SANS / UN RTDG / IMDG / IATA

SANS	UN RTDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. UN Proper Shipping Name			
Not applicable	Not applicable	Not applicable	Not applicable
Transport document description			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group, if applicable			
Not applicable	Not applicable	Not applicable	Not applicable

Dura Paints - Hydro - Direct to Metal - Orange

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

SANS	UN RTDG	IMDG	IATA
14.5. Environmental hazards			
Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available			

14.6. Special precautions for user

SANS

No data available

UN RTDG

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to IMO instructions

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

15.1.1. OCCUPATIONAL HEALTH AND SAFETY ACT, 1993

Prohibited Hazardous Chemical Agents
Not regulated

15.1.2. National Environmental Management Act, 1998

Regulation No. 51358 (Prior Informed Consent Procedure Regulations, 2024)
Not regulated

15.2. Safety, health, and environmental national regulations specific for the product

State or local regulations : This product complies with South African legal lead limit of 90ppm or less.

SECTION 16: Other information

Issue date : 29/07/2025
Revision date : 22/07/2026
Supersedes : 29/07/2025

Full text of H-statements:	
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage

Dura Paints - Hydro - Direct to Metal - Orange

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Full text of H-statements:	
H319	Causes serious eye irritation
H330	Fatal if inhaled
H331	Toxic if inhaled
H341	Suspected of causing genetic defects
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), South Africa (HCA)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.