

Prolong - Paint & Seal

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10
Issue date: 8/28/2023 Revision date: 7/27/2026 Supersedes: 8/28/2023 Version: 1.1

SECTION 1: Identification of the substance/mixture and of the supplier/undertaking

1.1. GHS product identifier

Product form	: Mixture
Trade name	: Prolong - Paint & Seal
Type of product	: Sealants
Product code	: PLPAINTSEA
Product group	: Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use	: Water-based sealant
-----------------	-----------------------

1.4. Supplier's details

Manufacturer

Dura Paints (Pty) Ltd.
5 Wakefield Road; Founders View South.
P.O. Box 303
1610 Edenvale; Johannesburg – South Africa
T 011 452 5221
orders@durapaints.co.za - www.durapaints.co.za

1.5. Emergency phone number

Emergency number	: 079 494 2731 / 011 452 5221
------------------	-------------------------------

SECTION 2: Hazard identification

2.1. GHS classification of the substance/mixture and any national or regional information

Classification according to the United Nations GHS

Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 1	H318
Carcinogenicity, Category 2	H351
Specific target organ toxicity – Repeated exposure, Category 2	H373
Hazardous to the aquatic environment – Chronic Hazard	Not classified

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects	: Suspected of causing cancer, Harmful if inhaled, When product is in liquid form, hazards related to inhalation are not present, but it contains substances that could be potential hazards if caused to become airborne due to abrasive processes.
---	--

2.2. GHS label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS ZA)



Signal word (GHS ZA)	: Danger
Hazardous ingredients	: Silicon dioxide; Aluminium oxide; Sodium oxide; Titanium dioxide
Hazard statements (GHS ZA)	: H315 - Causes skin irritation H318 - Causes serious eye damage H351 - Suspected of causing cancer (Inhalation)

Prolong - Paint & Seal

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Precautionary statements (GHS ZA)

H373 - May cause damage to organs (lungs) through prolonged or repeated exposure (Inhalation)
: P101 - If medical advice is needed, have product container or label and product safety data sheet at hand.
P102 - Keep out of reach of children.
P103 - Read carefully and follow all instructions.
P261 - Avoid breathing dust, mist.
P264 - Wash hands, forearms and face thoroughly after handling.
P280 - Wear protective clothing, protective gloves.
P302+P352 - IF ON SKIN: Wash with plenty of soap and water
P305+P354+P338 - IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P501 - Dispose of container to recycling, according to local regulations.

P-statements for label (GHS-ZA)

: P101 - If medical advice is needed, have product container or label and product safety data sheet at hand.; P102 - Keep out of reach of children.; P103 - Read carefully and follow all instructions.; P261 - Avoid breathing dust, mist.; P264 - Wash hands, forearms and face thoroughly after handling.; P280 - Wear protective clothing, protective gloves.; P302+P352 - IF ON SKIN: Wash with plenty of soap and water; P305+P354+P338 - IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.; P332+P313 - If skin irritation occurs: Get medical advice/attention; P337+P313 - If eye irritation persists: Get medical advice/attention; P501 - Dispose of container to recycling, according to local regulations.

2.3. Other hazards which do not result in classification or are not covered by the GHS

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to the United Nations GHS
Silicon dioxide	CAS-No.: 7631-86-9	13.96 – 27.92	Acute Tox. 4 (Dermal), H312 Acute Tox. Not classified (Inhalation:dust,mist) STOT RE Not classified Aquatic Acute Not classified Aquatic Chronic Not classified
Aluminium oxide	CAS-No.: 1344-28-1	3.58 – 7.16	Acute Tox. Not classified (Oral) Acute Tox. Not classified (Inhalation:dust,mist) STOT RE 1, H372 Aquatic Acute 1, H400
Sodium oxide	CAS-No.: 1313-59-3	2.2 – 4.4	Skin Corr. 1, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute Not classified Aquatic Chronic Not classified
Titanium dioxide	CAS-No.: 13463-67-7	0.51 – 1.52	Acute Tox. Not classified (Oral) Acute Tox. Not classified (Inhalation:dust,mist) Carc. 2, H351 Aquatic Chronic Not classified

Prolong - Paint & Seal

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

SECTION 4: First aid measures

4.1. Description of necessary first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms/effect, acute and delayed

No additional information available

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

5.3. Special protective actions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Avoid breathing dust/fume/gas/mist/vapours/spray.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray.
-------------------------------	---

Prolong - Paint & Seal

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Silicon dioxide (7631-86-9)	
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Silica, amorphous
OEL TWA	6 mg/m ³ inhalable particulate 3 mg/m ³ respirable particulate
Regulatory reference	Government Notice No. R 904
Aluminium oxide (1344-28-1)	
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Aluminium oxides
OEL TWA	10 mg/m ³ 5 mg/m ³
Remark	[c] The OEL for Aluminium does not include exposure to aluminium coated with mineral oil, or to fume arising from aluminium welding processes.
Regulatory reference	Government Notice No. R 904
Titanium dioxide (13463-67-7)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Titanium dioxide
RHCA - STEL/C	10 mg/m ³ 10 mg/m ³ total inhalable dust 5 mg/m ³ respirable dust
Remark	CARC (denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B)
Regulatory reference	Government Notice No. R. 280, 2021 Government Notice. R: 1179
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Titanium dioxide
OEL TWA	10 mg/m ³ inhalable particulate 5 mg/m ³ respirable particulate
Regulatory reference	Government Notice No. R 904

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection : Protective gloves
Eye protection : Safety glasses
Skin and body protection : Wear suitable protective clothing
Respiratory protection : [In case of inadequate ventilation] wear respiratory protection.

Prolong - Paint & Seal

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Personal protective equipment symbol(s)



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Paste.
Colour	: White
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability	: Non flammable
Vapour pressure	: No data available
Vapour pressure at 50°C	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Relative density of saturated gas/air mixture	: No data available
Density	: No data available
Relative gas density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Physical state	: Liquid
Appearance	: Paste.

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10: Stability and Reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

Prolong - Paint & Seal

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

10.2. Chemical Stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Silicon dioxide (7631-86-9)

LD50 oral rat	3160 mg/kg Source: TOMES; HAZARTEXT
LD50 dermal rat	≥ 2000 mg/kg bodyweight Source: ECHA
LD50 dermal rabbit	> 5000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Dust/Mist)	5.01 mg/l Source: ECHA

Aluminium oxide (1344-28-1)

LD50 oral rat	2000 – 15900 mg/kg bodyweight Source: ECHA
LC50 Inhalation - Rat	≈ 7.6 mg/l 60 min; Source: ECHA

Titanium dioxide (13463-67-7)

LD50 oral rat	> 2000 – < 25000 mg/kg bodyweight Practically nontoxic; Source: ECHA
LC50 Inhalation - Rat (Dust/Mist)	> 3.43 – < 6.82 mg/l/4h Source: ECHA

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye damage.
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Suspected of causing cancer (Inhalation).

Silicon dioxide (7631-86-9)

IARC group	3 - Not classifiable
------------	----------------------

Titanium dioxide (13463-67-7)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

Reproductive toxicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified

Sodium oxide (1313-59-3)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : May cause damage to organs (lungs) through prolonged or repeated exposure (Inhalation).

Prolong - Paint & Seal

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Silicon dioxide (7631-86-9)	
NOAEL (oral, rat, 28 days)	> 2500 mg/kg bodyweight/day Source: ECHA
NOAEC (inhalation, rat, 28 days)	> 1.3 – < 46 mg/l Source: ECHA
Aluminium oxide (1344-28-1)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.015 mg/l air Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified.

Silicon dioxide (7631-86-9)	
LC50 - Fish [1]	10000 mg/l Source: ECHA
EC50 - Crustacea [1]	> 5000 mg/l Source: ECHA
EC50 72h - Algae [1]	> 173.1 mg/l Source: ECHA
EC50 96h - Algae [1]	> 217.576 – < 217.6 mg/l Source: ECHA
LOEC (chronic)	≈ 149.2 mg/l Source: ECHA
NOEC (chronic)	> 68 – < 250 mg/l 21 days; Source: ECHA
NOEC chronic fish	> 57.001 – < 86.03 mg/l Source: ECHA
NOEC chronic algae	> 42.1 – < 42.11 mg/l Source: ECHA
Aluminium oxide (1344-28-1)	
LC50 - Fish [1]	78 – 218644.1 µg/l Source: ECHA
EC50 - Crustacea [1]	1.5 – 500 mg/l Source: ECHA
EC50 - Crustacea [2]	5.7 – 5000000 µg/l Source: ECHA
EC50 72h - Algae [1]	1.05 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (acute)	≈ 5.314 mg/l (7 days); Source: ECHA
NOEC (chronic)	4.7 – 2.31 mg/l (28 days); Source: ECHA
NOEC chronic crustacea	0.2326 – 0.4538 mg/l (42 days); Source: ECHA
NOEC chronic algae	≈ 1 g/l (6 days); Source: ECHA
Sodium oxide (1313-59-3)	
LC50 - Fish [1]	208000000 mg/l Source: QSAR
EC50 96h - Algae [1]	56800000 mg/l Source: QSAR
Titanium dioxide (13463-67-7)	
EC50 - Crustacea [1]	> 2.41 – < 103.9 mg/l Source: ECHA

Prolong - Paint & Seal

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Titanium dioxide (13463-67-7)	
EC50 - Other aquatic organisms [1]	> 100 mg/l Test organisms (species):
EC50 72h - Algae [1]	≥ 100 mg/l Source: ECHA
LOEC (acute)	≈ 160 mg/l Fish, 4 Days; Source: ECHA
LOEC (chronic)	≈ 5 mg/l Crustacea, 21 Days; Source: ECHA
NOEC (acute)	0.004 – 0.08 mg/l 28 Dday, fish; Source: Echa
NOEC (chronic)	≥ 100 mg/l 28 days; Source: ECHA
NOEC chronic fish	> 80 – < 160 mg/l 6 days; Source: ECHA

12.2. Persistence and degradability

Prolong - Paint & Seal	
Persistence and degradability	Rapidly degradable
Silicon dioxide (7631-86-9)	
Persistence and degradability	
Aluminium oxide (1344-28-1)	
Persistence and degradability	
Sodium oxide (1313-59-3)	
Persistence and degradability	
Titanium dioxide (13463-67-7)	
Persistence and degradability	

12.3. Bioaccumulative potential

Prolong - Paint & Seal	
Bioaccumulative potential	No additional information available
Silicon dioxide (7631-86-9)	
Partition coefficient n-octanol/water (Log Kow)	≈ 0.53 @ 25 °C and pH 7; Source: ECHA

12.4. Mobility in soil

Prolong - Paint & Seal	
Mobility in soil	No additional information available

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No additional information available

SECTION 13: Disposal Considerations

13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
-------------------------	---

SECTION 14: Transport information

In accordance with SANS / UN RTDG / IMDG / IATA

Prolong - Paint & Seal

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

SANS	UN RTDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. UN Proper Shipping Name			
Not applicable	Not applicable	Not applicable	Not applicable
Transport document description			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group, if applicable			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available			

14.6. Special precautions for user

SANS

No data available

UN RTDG

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to IMO instructions

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

15.1.1. OCCUPATIONAL HEALTH AND SAFETY ACT, 1993

Prohibited Hazardous Chemical Agents

Not regulated

15.1.2. National Environmental Management Act, 1998

Regulation No. 51358 (Prior Informed Consent Procedure Regulations, 2024)

Not regulated

15.2. Safety, health, and environmental national regulations specific for the product

State or local regulations : This product complies with South African legal lead limit of 90ppm or less.

Prolong - Paint & Seal

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

SECTION 16: Other information

Issue date : 28/08/2023
Revision date : 27/07/2026
Supersedes : 28/08/2023

Full text of H-statements:

H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H330	Fatal if inhaled
H331	Toxic if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), South Africa (HCA)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.