

SECTION 1: Identification of the substance/mixture and of the supplier/undertaking

1.1. GHS product identifier

Product form	: Mixture
Trade name	: Wedgewood - Decorative Tint Umber - DP17
Type of product	: Coatings
Product code	: YAQ
Product group	: Raw material

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use	: Water based colourant
-----------------	-------------------------

1.4. Supplier's details

Downstream user

Dura Paints (Pty) Ltd.
5 Wakefield Road; Founders View South.
P.O. Box 303
1610 Edenvale; Johannesburg – South Africa
T 011 452 5221
orders@durapaints.co.za - www.durapaints.co.za

1.5. Emergency phone number

Emergency number	: 079 494 2731 / 011 452 5221
------------------	-------------------------------

SECTION 2: Hazard identification

2.1. GHS classification of the substance/mixture and any national or regional information

Classification according to the United Nations GHS

Acute toxicity (inhal.), Category 4	H332
Carcinogenicity, Category 2	H351
Specific target organ toxicity – Repeated exposure, Category 2	H373

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects	: When product is in liquid form, hazards related to inhalation are not present, but it contains substances that could be potential hazards if caused to become airborne due to abrasive processes, May cause an allergic skin reaction, Suspected of causing cancer, May cause damage to organs through prolonged or repeated exposure, Harmful if inhaled.
---	--

2.2. GHS label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS ZA)



Signal word (GHS ZA)	: Warning
Hazardous ingredients	: Talc /Talc containing no asbestos fibers/; Carbon black
Hazard statements (GHS ZA)	: H332 - Harmful if inhaled H351 - Suspected of causing cancer (Inhalation) H373 - May cause damage to organs (Skin) through prolonged or repeated exposure (Dermal)

Wedgewood - Decorative Tint Umber - DP17

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Precautionary statements (GHS ZA)	: P101 - If medical advice is needed, have product container or label and product safety data sheet at hand. P102 - Keep out of reach of children. P103 - Read carefully and follow all instructions. P260 - Do not breathe dusts or mists. P280 - Wear protective gloves, protective clothing. P501 - Dispose of container to Recycling, according to local regulations.
P-statements for label (GHS-ZA)	: P101 - If medical advice is needed, have product container or label and product safety data sheet at hand.; P102 - Keep out of reach of children.; P103 - Read carefully and follow all instructions.; P260 - Do not breathe dusts or mists.; P280 - Wear protective gloves, protective clothing.; P501 - Dispose of container to Recycling, according to local regulations.

2.3. Other hazards which do not result in classification or are not covered by the GHS

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to the United Nations GHS
Talc /Talc containing no asbestos fibers/	CAS-No.: 14807-96-6	20 – 30	Acute Tox. Not classified (Oral) Acute Tox. 4 (Inhalation:dust,mist), H332 STOT RE 2, H373 Aquatic Acute Not classified Aquatic Chronic Not classified
Carbon black	CAS-No.: 1333-86-4	1 – 3	Acute Tox. 1 (Inhalation:dust,mist), H330 Carc. 2, H351 STOT RE 1, H372 Aquatic Acute Not classified Aquatic Chronic Not classified
Ethane-1,2-diol	CAS-No.: 107-21-1	1 – 3	Acute Tox. 4 (Oral), H302

SECTION 4: First aid measures

4.1. Description of necessary first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
Self protection of the first-aiders	: First-aiders should pay attention to their own protection and use the recommended personal protective equipment (see section 8).

4.2. Most important symptoms/effect, acute and delayed

Symptoms/effects after inhalation	: Harmful if inhaled.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.

Wedgewood - Decorative Tint Umber - DP17

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective actions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate non-essential personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

For containment	: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

Wedgewood - Decorative Tint Umber - DP17

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Store locked up.
Packaging materials	: Always store product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Talc /Talc containing no asbestos fibers/ (14807-96-6)	
South Africa - Occupational Exposure Limits (Maximum Limits)	
Local name	Talc (containing asbestos fibres)
RHCA - OEL	0.6 fibers/mL (measured over a continuous 10-minute period)
RHCA - STEL/C	0.1 fibers/mL
Remark	CARC (denotes carcinogenicity, which is based on GHS categorisation, including category 1A and 1B)
Regulatory reference	Government Notice No. R. 280, 2021; Government Notice No. R. 11196, 2020
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Talc (containing no asbestos fibers)
RHCA - STEL/C	4 mg/m ³ (E: the value is for particulate matter containing no asbestos and ≤ 1% crystalline silica, R: respirable fraction) 10 mg/m ³ total inhalable dust 1 mg/m ³ respirable dust
Regulatory reference	Government Notice No. R. 280, 2021 Government Notice. R: 1179
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Talc
OEL TWA	10 mg/m ³ inhalable particulate 1 mg/m ³ respirable particulate
Regulatory reference	Government Notice No. R 904
Carbon black (1333-86-4)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Carbon black
RHCA - STEL/C	6 mg/m ³ (I: inhalable fraction)
Remark	CARC (denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B)
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Carbon black
OEL TWA	4 mg/m ³
OEL STEL	7 mg/m ³
Regulatory reference	Government Notice No. R 904
Ethane-1,2-diol (107-21-1)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Ethylene glycol

Wedgewood - Decorative Tint Umber - DP17

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Ethane-1,2-diol (107-21-1)	
OEL eight hour TWA	20 mg/m ³ (H: aerosol only)
RHCA - STEL/C	50 mg/m ³ (V: vapour fraction) 100 mg/m ³ (V: vapour fraction)
Remark	SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Ethylene glycol (Ethane-1,2-diol; 1,2-Dihydroxyethane)
OEL TWA	20 mg/m ³
OEL STEL	40 mg/m ³
Regulatory reference	Government Notice No. R 904

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: [In case of inadequate ventilation] wear respiratory protection.
Personal protective equipment symbol(s)	



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: brown
Odour	: slight
Odour threshold	: No data available
pH	: > 7 – < 9 Estimated; Source: Supplier SDS
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 100 °C Estimated; Source: Supplier SDS
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability	: Non flammable
Vapour pressure	: No data available
Vapour pressure at 50°C	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: > 1.45 – < 1.65 Estimated; Source: Supplier SDS

Wedgewood - Decorative Tint Umber - DP17

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Relative density of saturated gas/air mixture	: No data available
Density	: No data available
Relative gas density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Physical state	: Liquid
Appearance	: Liquid.

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10: Stability and Reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical Stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Harmful if inhaled.

Wedgewood - Decorative Tint Umber - DP17

ATE ZA (Gases)	4500 ppmv/4h
ATE ZA (vapours)	11 mg/l/4h
ATE ZA (dust, mist)	1.5 mg/l/4h

Talc /Talc containing no asbestos fibers/ (14807-96-6)

LD50 oral rat	> 5000 mg/l Animal: rat, Animal sex: male, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
---------------	---

Wedgewood - Decorative Tint Umber - DP17

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Talc /Talc containing no asbestos fibers/ (14807-96-6)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 2.1 mg/l Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
Carbon black (1333-86-4)	
LD50 oral rat	> 2000 mg/kg bodyweight Source: ECHA
LD50 dermal rat	> 2000 mg/kg bodyweight
LC50 Inhalation - Rat	> 4.6 mg/m³ Source: ECHA
Ethane-1,2-diol (107-21-1)	
LD50 oral rat	7712 mg/kg bodyweight Animal: rat
LD50 dermal	≥ 3500 mg/kg bodyweight Test subject: Mouse; Source: ECHA
LC50 Inhalation - Rat	≈ 2.5 mg/l 6 hrs; Source: ECHA
Skin corrosion/irritation	: Not classified pH: > 7 – < 9 Estimated; Source: Supplier SDS
Serious eye damage/irritation	: Not classified pH: > 7 – < 9 Estimated; Source: Supplier SDS
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer (Inhalation).
Reproductive toxicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: May cause damage to organs (Skin) through prolonged or repeated exposure (Dermal).
Talc /Talc containing no asbestos fibers/ (14807-96-6)	
NOAEL (oral, rat, 28 days)	> 100 mg/kg bodyweight/day Source: ECHA
NOAEL (oral, rat, 90 days)	100 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Carbon black (1333-86-4)	
LOAEL (oral, rat, 90 days)	> 1000 mg/kg bodyweight/day Source: ECHA
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.0071 mg/l air Animal: rat, Animal sex: male
NOAEC (inhalation, rat, 28 days)	≈ 0.001 mg/l Source: ECHA
NOAEL (oral, rat, 90 days)	> 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.0011 mg/l air Animal: rat, Animal sex: male
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Ethane-1,2-diol (107-21-1)	
NOAEL (oral, rat, 28 days)	≥ 150 mg/kg bodyweight/day Source: ECHA
Aspiration hazard	: Not classified

Wedgewood - Decorative Tint Umber - DP17

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Talc /Talc containing no asbestos fibers/ (14807-96-6)

LC50 - Fish [1]	89581.02 mg/l Test organisms (species): other:
LC50 - Fish [2]	110000 mg/l Test organisms (species): other:
EC50 96h - Algae [1]	7202.7 mg/l Test organisms (species): other:
NOEC (chronic)	1459798 mg/l Test organisms (species): other: Duration: '30 d'
NOEC chronic fish	> 1.413 – < 5.98 g/l 30 days; Source: ECHA
NOEC chronic algae	≈ 91.81 mg/l Marine water algae; Source: ECHA

Carbon black (1333-86-4)

EC50 72h - Algae [1]	> 10000 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	> 10000 mg/l Test organisms (species):
NOEC (chronic)	≈ 3200 mg/l Source: ECHA

Ethane-1,2-diol (107-21-1)

LC50 - Fish [1]	> 72860 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
NOEC (chronic)	≥ 1000 mg/l Test organisms (species): Americamysis bahia (previous name: Mysidopsis bahia) Duration: '23 d'
NOEC chronic fish	≥ 40 mg/l Source: ECHA
NOEC chronic algae	≈ 100 mg/l 72 hrs; Source: ECHA

12.2. Persistence and degradability

Wedgewood - Decorative Tint Umber - DP17

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Talc /Talc containing no asbestos fibers/ (14807-96-6)

Persistence and degradability	
-------------------------------	--

Carbon black (1333-86-4)

Persistence and degradability	
-------------------------------	--

Ethane-1,2-diol (107-21-1)

Persistence and degradability	
-------------------------------	--

12.3. Bioaccumulative potential

Wedgewood - Decorative Tint Umber - DP17

Bioaccumulative potential	No additional information available
---------------------------	-------------------------------------

Talc /Talc containing no asbestos fibers/ (14807-96-6)

Partition coefficient n-octanol/water (Log Kow)	≈ -9.4 @ 25 °C and pH 7; Source: ECHA
---	---------------------------------------

Wedgewood - Decorative Tint Umber - DP17

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Ethane-1,2-diol (107-21-1)

Partition coefficient n-octanol/water (Log Kow) ≈ -1.36 at 25°C; Source: ECHA

12.4. Mobility in soil

Wedgewood - Decorative Tint Umber - DP17

Mobility in soil No additional information available

Carbon black (1333-86-4)

Organic Carbon Normalized Adsorption Coefficient (Log Koc) $> 589 - < 4300$ @ 20 °C and 1.3 - 3.6 % organic carbon : ECHA

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No additional information available

SECTION 13: Disposal Considerations

13.1. Disposal methods

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
Ecological waste information : The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.
Additional information : Do not re-use empty containers.

SECTION 14: Transport information

In accordance with SANS / UN RTDG / IMDG / IATA

SANS	UN RTDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. UN Proper Shipping Name			
Not applicable	Not applicable	Not applicable	Not applicable
Transport document description			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group, if applicable			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available			

Wedgewood - Decorative Tint Umber - DP17

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

14.6. Special precautions for user

SANS
No data available

UN RTDG
No data available

IMDG
No data available

IATA
No data available

14.7. Transport in bulk according to IMO instructions

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

15.1.1. OCCUPATIONAL HEALTH AND SAFETY ACT, 1993

Prohibited Hazardous Chemical Agents
Not regulated

15.1.2. National Environmental Management Act, 1998

Regulation No. 51358 (Prior Informed Consent Procedure Regulations, 2024)
Not regulated

15.2. Safety, health, and environmental national regulations specific for the product

State or local regulations : This product complies with South African legal lead limit of 90ppm or less.

SECTION 16: Other information

Issue date : 25/09/2025
Revision date : 26/07/2026
Supersedes : 29/09/2025

Full text of H-statements:	
H302	Harmful if swallowed
H330	Fatal if inhaled
H332	Harmful if inhaled
H351	Suspected of causing cancer
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure

Safety Data Sheet (SDS), South Africa (HCA)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.