

PROLONG CRACKBAND

PL019

PRODUCT CODE: Crackband Fine CBFINE(100) (300) (500)

PRODUCT DESCRIPTION: *ProLong Crackband* is a fine, 100% Polypropylene, flexible membrane, used in conjunction with water-based coatings to hide hairline plaster cracks. Widths up to 1000mm and lengths of up to 20m can be applied to entire walls without joints. Suitable for indoor and outdoor use.

INTENDED USES:

- *ProLong Crackband* is a fine flexible membrane, used in conjunction with **Wedgewood** premium coating (Opulent Matte, Opulent Sheen or Opulent Signature) to hide hairline cracks in plaster.
- *ProLong Crackband* can also be used as a cover to protect plants against frost.

FEATURES:

- *ProLong Crackband*, when applied as per specification, provides an almost invisible film that conceals hairline cracks in plaster work. Super tough and easy to use. No more chipping away and filling of cracks required. Withstands cracking and movement of the substrate. Multiple sizes are available.

PRODUCT INFORMATION:

- COMPOSITION 100% Polypropylene
- COLOUR White
- MASS 16g/m²

APPLICATION DETAILS:

- METHOD Fill and repair all large cracks and gaps with **ProLong ProFill** Multi-Purpose Filler, allow to dry, sand and dust well.
- SUBSTRATE Apply *ProLong Crackband* onto a wet coated surface so that the band sticks to the paint. (See application section below)
- APPLICATION ENVIRONMENT As per paint specification (Product MSDS/TDS)

Surface Temp	Ambient Temp	Relative Humidity
Min 10°C or 2°C above dew point	Min 10°C or 2°C above dew point	Min: 10%
Max : 40°C	Max : 40°C	Max : 85%

- Drying Time:
Touch dry 30 Min @ 25°C
Dry to handle 2 hours @ 25°C
Overcoating 2 hours @ 25°C

SURFACE PREPARATION:

Ensure that the surface is clean, dry and free of dust, grit, grime and grease. Prepare the surface as for painting.

APPLICATION:

- Fill and repair all large cracks and gaps with **ProLong Profill or Crackfill**, allow to dry, sand and dust off well.
- Apply a liberal coat of **Wedgewood** premium water-based coating (**Opulent Matte, Opulent Sheen, or Opulent Signature Coat**) to the wall.
- Apply *Crackband* onto wet, coated surface, from one point to another, ensuring there are no air bubbles, folds or wrinkles.
- Apply two further coats on top of the band ensuring that there are no air bubbles, wrinkles or folds in the painted band.
- Allow to dry.

TECHNICAL DATA SHEET

PROLONG CRACKBAND (cont).

CAUTIONS

- Avoid applying in inclement weather or if temperature is below 10°C.
- Do not exceed maximum recommended application thickness.
- Not recommended for repairing structural cracks.

STORAGE AND PACKAGING:

- Keep product sealed against contamination from dirt and moisture.
- When stored in its original unopened packaging, under the recommended storage conditions, this product does not have a defined shelf life and may be stored indefinitely without significant loss of performance.
- **ProLong Crackband** standard rolls of 100mm X 20M, 300mm x 20M and 500mm X 20M. Alternate sizes available subject to volume.

TRANSPORTATION:

This product is not classified as a dangerous good for transportation.

SHIPPING NAME: Not regulated

PACKAGING GROUP: Not regulated

HAZARD CLASS: Not regulated

S.I.N/UN NUMBER: Not regulated

SAFETY PRECAUTIONS:

- Keep out of reach of children.
- Ensure good ventilation during application and drying.
- Refer to the Safety Data Sheet (SDS) for detailed health, safety, handling, storage, and emergency information. See www.durapaints.co.za

DISCLAIMER:

- *The recommendations contained herein are given in good faith and are meant to guide the specifier or the user.*
 - *They are based on results gained from our experiences and tests and are believed to be reliable.*
 - *No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.*
 - *Technology may change necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used. See www.durapaints.co.za.*
-