

SECTION 1: Identification of the substance/mixture and of the supplier/undertaking

1.1. GHS product identifier

Product form	: Mixture
Trade name	: Dura Paints - Concrete Primer Catalyst
Type of product	: Coatings
Product code	: CONCRPRICAT
Product group	: Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use	: For use with concrete primer as per instruction
-----------------	---

1.4. Supplier's details

Manufacturer

Dura Paints (Pty) Ltd.
5 Wakefield Road; Founders View South.
P.O. Box 303
1610 Edenvale; Johannesburg – South Africa
T 011 452 5221
orders@durapaints.co.za - www.durapaints.co.za

1.5. Emergency phone number

Emergency number	: 079 494 2731 / 011 452 5221
------------------	-------------------------------

SECTION 2: Hazard identification

2.1. GHS classification of the substance/mixture and any national or regional information

Classification according to the United Nations GHS

Flammable liquids Not classified

Acute toxicity (oral), Category 1	H300
Acute toxicity (dermal), Category 5	H313
Skin corrosion/irritation, Category 1B	H314
Serious eye damage/eye irritation, Category 1	H318
Skin sensitisation, Category 1	H317
Reproductive toxicity, Category 1B	H360
Specific target organ toxicity – Repeated exposure, Category 2	H373
Hazardous to the aquatic environment – Acute Hazard, Category 2	H401
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects	: May damage fertility or the unborn child, May cause damage to organs through prolonged or repeated exposure, Fatal if swallowed, Harmful in contact with skin, Causes severe skin burns and eye damage, May cause an allergic skin reaction, Causes serious eye damage, Toxic to aquatic life, Toxic to aquatic life with long lasting effects.
---	---

Dura Paints - Concrete Primer Catalyst

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

2.2. GHS label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS ZA)

:



Signal word (GHS ZA)

: Danger

Hazardous ingredients

: Bisphenol-A; 2,2'-iminodi(ethylamine); Tetraethylenepentamine

Hazard statements (GHS ZA)

: H300 - Fatal if swallowed
H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction
H360 - May damage fertility. May damage the unborn child. (Dermal, Inhalation, Oral)
H373 - May cause damage to organs (liver, kidneys) through prolonged or repeated exposure (Dermal, Inhalation, Oral)
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS ZA)

: P101 - If medical advice is needed, have product container or label and product safety data sheet at hand.
P102 - Keep out of reach of children.
P103 - Read carefully and follow all instructions.
P261 - Avoid breathing fume, mist, spray, vapours.
P263 - Avoid contact during pregnancy and while nursing.
P273 - Avoid release to the environment.
P280 - Wear eye protection, protective clothing, protective gloves.
P271 - Use only outdoors or in a well-ventilated area.
P501 - Dispose of container to according to local regulations, recycling.
P101 - If medical advice is needed, have product container or label and product safety data sheet at hand.; P102 - Keep out of reach of children.; P103 - Read carefully and follow all instructions.; P261 - Avoid breathing fume, mist, spray, vapours.; P263 - Avoid contact during pregnancy and while nursing.; P273 - Avoid release to the environment.; P280 - Wear eye protection, protective clothing, protective gloves.; P271 - Use only outdoors or in a well-ventilated area.; P501 - Dispose of container to according to local regulations, recycling.

P-statements for label (GHS-ZA)

2.3. Other hazards which do not result in classification or are not covered by the GHS

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to the United Nations GHS
Bisphenol-A	CAS-No.: 80-05-7	< 10	Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 1B, H360 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Dura Paints - Concrete Primer Catalyst

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Name	Product identifier	%	Classification according to the United Nations GHS
2,2'-iminodi(ethylamine)	CAS-No.: 111-40-0	< 10	Flam. Liq. Not classified Acute Tox. 1 (Oral), H300 Acute Tox. 4 (Dermal), H312 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 2, H373 Aquatic Chronic Not classified
Tetraethylenepentamine	CAS-No.: 112-57-2	< 10	Flam. Liq. Not classified Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 2, H411

SECTION 4: First aid measures

4.1. Description of necessary first aid measures

First-aid measures general	: If medical advice is needed, have product container or label at hand. Get medical advice/attention if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Take off immediately all contaminated clothing. Gently wash with plenty of soap and water. If irritation persists, consult a doctor.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Do NOT induce vomiting. Give nothing to drink. Do not induce vomiting (irritation of the stomach possible). Ask for medical advice. Get immediate medical advice/attention.
Self protection of the first-aider	: First-aiders should pay attention to their own protection and use the recommended personal protective equipment (see section 8).

4.2. Most important symptoms/effect, acute and delayed

Symptoms/effects	: Harmful if inhaled. May cause drowsiness or dizziness. Harmful in contact with skin. Causes serious eye irritation. May be fatal if swallowed and enters airways.
Symptoms/effects after inhalation	: Adverse symptoms may include nausea or vomiting, headache, respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. May cause redness, dryness, and discomfort.
Symptoms/effects after eye contact	: Adverse symptoms may include pain, irritation, watering and redness. Blurred vision.
Symptoms/effects after ingestion	: Fatal if swallowed.
Symptoms/effects upon intravenous administration	: Pain, swelling, and erythema: Rapid onset at the injection site; Chemical necrotising cellulitis: Inflammatory destruction of soft tissue, often within 24 hours. Get medical attention immediately.
Chronic symptoms	: May damage fertility, May damage the unborn child.. May cause damage to liver and kidneys.
Potential adverse human health effects and symptoms	: Pre-existing skin or respiratory disorders may be aggravated by exposure to this product.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically. Pre-existing skin or respiratory disorders may be aggravated by exposure to this product.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

Dura Paints - Concrete Primer Catalyst

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective actions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Personal protection (Emergency response)	: Fire-resistant protective clothing, Use breathing equipment (SCBA), Use only explosion-proof equipment and PPE



Other information	: Dyke fire control water for later disposal. Do not allow run-off from fire-fighting to enter drains or water courses. Notify authorities if run-off does enter drains or water courses.
-------------------	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Evacuate non-essential personnel. Avoid contact with eyes, skin and clothing.
Personal Precautions, Protective Equipment and Emergency Procedures	: Use only non-sparking tools. Complete protective clothing.
Prevention Measures for Secondary Accidents	: Stop leaks if it can be done without personal risk.

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate non-essential personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

For containment	: Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up	: Absorb spillage with vermiculite or sand; Scoop into labeled hazardous waste container. Clean spill area with detergent and water — avoid solvents.
Other information	: Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Obtain special instructions before use. Do not get in eyes, on skin, or on clothing.
Hygiene measures	: Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

Dura Paints - Concrete Primer Catalyst

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Store in tightly sealed containers in a cool, dry, well-ventilated area. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Packaging materials	: Always store product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2,2'-iminodi(ethylamine) (111-40-0)

South Africa - Occupational Exposure Limits (Restricted Limits)

Local name	Diethylenetriamine [DETA]
RHCA - STEL/C	2 ppm
Remark	SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021

South Africa - Occupational Exposure Limits (Airborne Pollutants)

Local name	Diethylene triamine (2,2'-Diaminodiethylamine; 2,2'-Iminodi(ethylamine))
OEL TWA	4 mg/m ³ 1 ppm
Remark	Sk (Danger of cutaneous absorption)
Regulatory reference	Government Notice No. R 904

OEL Sources : LISAM.

BLV Sources : LISAM.

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.
Consumer exposure controls	: Avoid contact during pregnancy/while nursing.

8.3. Individual protection measures, such as personal protective equipment

Materials for protective clothing : Chemical resistant overalls

Hand protection : Protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Polyvinylchloride (PVC), Nitrile rubber (NBR)				

Eye protection : Wear security glasses which protect from splashes

Skin and body protection : Wear suitable protective clothing

Respiratory protection : [In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s)



8.4. Exposure limit values for the other components

No additional information available

Dura Paints - Concrete Primer Catalyst

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: amber
Odour	: Amine-like
Odour threshold	: No data available
pH	: No data available
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 207 °C Source: Supplier SDS
Flash point	: > 93 °C Source: Supplier SDS
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability	: Non flammable
Vapour pressure	: < 13.3 Pa at 20 deg. C; Source: Supplier SDS
Vapour pressure at 50°C	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Relative density of saturated gas/air mixture	: No data available
Density	: ≈ 976 kg/m ³ at 25 deg. C; Source: Supplier SDS
Relative gas density	: No data available
Solubility	: In water, material is partially soluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: 717.213 mm ² /s
Viscosity, dynamic	: ≈ 700 mPa·s at 25 deg. C Brookfield; Source: Supplier SDS
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available
Lower explosion limit	: ≈ 14 Vol-% Source: Supplier SDS
Upper explosion limit	: No data available
Physical state	: Liquid
Appearance	: Liquid.

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10: Stability and Reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical Stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong oxidizing agents.

Dura Paints - Concrete Primer Catalyst

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Likely routes of exposure : Dermal. Ingestion. Inhalation.

11.1. Information on toxicological effects

Acute toxicity (oral) : Fatal if swallowed.
Acute toxicity (dermal) : May be harmful in contact with skin.
Acute toxicity (inhalation) : Not classified

Dura Paints - Concrete Primer Catalyst

LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

Bisphenol-A (80-05-7)

LD50 oral rat	4100 mg/kg Source: HSDB
LD50 dermal rabbit	3000 mg/kg Source: HSDB

2,2'-iminodi(ethylamine) (111-40-0)

LD50 oral rat	≈ 1.62 mg/kg bodyweight Source: ECHA
---------------	--------------------------------------

Tetraethylenepentamine (112-57-2)

LD50 oral rat	3990 mg/kg
LD50 dermal rabbit	660 mg/kg

Skin corrosion/irritation : Causes severe skin burns.
Serious eye damage/irritation : Causes serious eye damage.
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : May damage fertility. May damage the unborn child. (Dermal, Inhalation, Oral).
Reproductive toxicity : May damage fertility. May damage the unborn child. (Dermal, Inhalation, Oral).
STOT-single exposure : Not classified

Bisphenol-A (80-05-7)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : May cause damage to organs (liver, kidneys) through prolonged or repeated exposure (Dermal, Inhalation, Oral).

2,2'-iminodi(ethylamine) (111-40-0)

LOAEL (oral, rat, 90 days)	530 – 620 mg/kg bodyweight Animal: rat, Guideline: other:
NOAEC (inhalation, rat, vapour, 28 days)	≈ 0.55 mg/l Source: ECHA
NOAEL (oral, rat, 90 days)	70 – 80 mg/kg bodyweight Animal: rat, Guideline: other:
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Dura Paints - Concrete Primer Catalyst

Viscosity, kinematic	717.213 mm²/s
----------------------	---------------

Potential adverse human health effects and symptoms : Pre-existing skin or respiratory disorders may be aggravated by exposure to this product.

Dura Paints - Concrete Primer Catalyst

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to aquatic life. Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

Bisphenol-A (80-05-7)	
LC50 - Fish [1]	7.5 mg/l Source: HSDB
EC50 - Crustacea [1]	1.1 mg/l Source: ECHA
EC50 72h - Algae [1]	2.73 mg/l Freshwater algae; Source: ECHA
NOEC (chronic)	≈ 3.146 mg/l 21 Days; Source ECHA

2,2'-iminodi(ethylamine) (111-40-0)	
LC50 - Fish [1]	0.43 g/l Test organisms (species): Poecilia reticulata
EC50 - Crustacea [1]	64.6 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	16 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	1164 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	187 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
LOEC (chronic)	11.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	5.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 10 mg/l Test organisms (species): Gasterosteus aculeatus Duration: '28 d'

12.2. Persistence and degradability

Dura Paints - Concrete Primer Catalyst	
Persistence and degradability	Not readily biodegradable.

Bisphenol-A (80-05-7)	
Persistence and degradability	

2,2'-iminodi(ethylamine) (111-40-0)	
Persistence and degradability	

Tetraethylenepentamine (112-57-2)	
Persistence and degradability	

12.3. Bioaccumulative potential

Dura Paints - Concrete Primer Catalyst	
Bioaccumulative potential	Contains components with the potential to bioaccumulate.

Bisphenol-A (80-05-7)	
Partition coefficient n-octanol/water (Log Kow)	3.32 Source: HSDB

2,2'-iminodi(ethylamine) (111-40-0)	
Partition coefficient n-octanol/water (Log Pow)	≈ -1.58 @ 20 °C & pH 7 - 12; Source: ECHA
Partition coefficient n-octanol/water (Log Kow)	≈ -1.3 Source: ICSCs

Dura Paints - Concrete Primer Catalyst

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

Tetraethylenepentamine (112-57-2)

Partition coefficient n-octanol/water (Log Kow) -3.16

12.4. Mobility in soil

Dura Paints - Concrete Primer Catalyst

Mobility in soil No additional information available

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No additional information available

SECTION 13: Disposal Considerations

13.1. Disposal methods

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
Ecological waste information : The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.
Additional information : Do not re-use empty containers.

SECTION 14: Transport information

In accordance with SANS / UN RTDG / IMDG / IATA

SANS	UN RTDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. UN Proper Shipping Name			
PAINT RELATED MATERIAL	Not applicable	PAINT RELATED MATERIAL	Paint related material
Transport document description			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	3	3
	 Not applicable	 	 
14.4. Packing group, if applicable			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes
No supplementary information available			

Dura Paints - Concrete Primer Catalyst

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

14.6. Special precautions for user

SANS

Special provisions (SANS)	: 163, 187, 223
Limited quantities (SANS)	: 5 L
Excepted quantities (SANS)	: E1
Packagings, large packagings and IBCs Packing instructions (SANS)	: P001, IBC03, LP01
Packagings, large packagings and IBCs Special packing instructions (SANS)	: PP1
Portable tank and bulk containers instructions (SANS)	: T2
Portable tank and bulk container special provisions (SANS)	: TP1, TP29

UN RTDG

No data available

IMDG

Special provisions (IMDG)	: 163, 223, 367, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

IATA

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

14.7. Transport in bulk according to IMO instructions

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

15.1.1. OCCUPATIONAL HEALTH AND SAFETY ACT, 1993

Prohibited Hazardous Chemical Agents

Not regulated

15.1.2. National Environmental Management Act, 1998

Regulation No. 51358 (Prior Informed Consent Procedure Regulations, 2024)

Not regulated

15.2. Safety, health, and environmental national regulations specific for the product

State or local regulations : This product complies with South African legal lead limit of 90ppm or less.

Dura Paints - Concrete Primer Catalyst

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10

SECTION 16: Other information

Issue date : 05/09/2023
Revision date : 23/10/2026
Supersedes : 11/02/2026

Full text of H-statements:

H300	Fatal if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H313	May be harmful in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H335	May cause respiratory irritation
H360	May damage fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), South Africa (HCA)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.