# Prolong - Profill White

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10
Issue date: 7/2/2023 Revision date: 26/10/2026 Supersedes: 26/10/2026 Version: 2.7

## SECTION 1: Identification of the substance/mixture and of the supplier/undertaking

### 1.1. GHS product identifier

| | | |
|---|---|---|
| Product form | : | Mixture |
| Trade name | : | Prolong - Profill White |
| Type of product | : | Filler |
| Product code | : | PLPROFILLW |
| Product group | : | Trade product |

### 1.2. Other means of identification

No additional information available

### 1.3. Recommended use of the chemical and restrictions on use

| | | |
|---|---|---|
| Recommended use | : | Multi-purpose ready mixed bonded interior and exterior filler |

### 1.4. Supplier's details

**Manufacturer**
Dura Paints (Pty) Ltd.
5 Wakefield Road; Founders View South.
P.O. Box 303
1610 Edenvale; Johannesburg – South Africa
T 011 452 5221
orders@durapaints.co.za - www.durapaints.co.za

### 1.5. Emergency phone number

| | | |
|---|---|---|
| Emergency number | : | 079 494 2731 / 011 452 5221 |

## SECTION 2: Hazard identification

### 2.1. GHS classification of the substance/mixture and any national or regional information

**Classification according to the United Nations GHS**

| | |
|---|---|
| Acute toxicity (dermal), Category 4 | H312 |
| Skin corrosion/irritation, Category 2 | H315 |
| Serious eye damage/eye irritation, Category 2A | H319 |
| Specific target organ toxicity – Repeated exposure, Category 2 | H373 |

Full text of H-statements: see section 16

| | | |
|---|---|---|
| Adverse physicochemical, human health and environmental effects | : | May cause damage to organs through prolonged or repeated exposure,When product is in liquid form, hazards related to inhalation are not present, but it contains substances that could be potential hazards if caused to become airborne due to abrasive processes,May cause respiratory irritation,Causes skin irritation,Causes serious eye irritation. |

### 2.2. GHS label elements, including precautionary statements

**Labelling according to the United Nations GHS**

Hazard pictograms (GHS ZA) :



| | | |
|---|---|---|
| Signal word (GHS ZA) | : | Warning |
| Hazardous ingredients | : | Silicon dioxide; Aluminium oxide; Solvent naphtha (petroleum), heavy arom. |
| Hazard statements (GHS ZA) | : | H312 - Harmful in contact with skin<br>H315+H319 - Causes skin irritation and serious eye irritation<br>H373 - May cause damage to organs (respiratory system, Skin) through prolonged or repeated exposure (Inhalation, Dermal) |

Precautionary statements (GHS ZA) : P101 - If medical advice is needed, have product container or label and product safety data sheet at hand.
P102 - Keep out of reach of children.
P103 - Read carefully and follow all instructions.
P280 - Wear eye protection, protective clothing, protective gloves.
P260 - Do not breathe dusts or mists.
P262 - Do not get in eyes, on skin, or on clothing.
P501 - Dispose of container to recycling, according to local regulations.

P-statements for label (GHS-ZA) : P101 - If medical advice is needed, have product container or label and product safety data sheet at hand.; P102 - Keep out of reach of children.; P103 - Read carefully and follow all instructions.; P280 - Wear eye protection, protective clothing, protective gloves.; P260 - Do not breathe dusts or mists.; P262 - Do not get in eyes, on skin, or on clothing.; P501 - Dispose of container to recycling, according to local regulations.

### 2.3. Other hazards which do not result in classification or are not covered by the GHS

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

| Name | Product identifier | % | Classification according to the United Nations GHS |
|---|---|---|---|
| Silicon dioxide | CAS-No.: 7631-86-9 | 51.305 – 75.193 | Acute Tox. 4 (Dermal), H312<br>Acute Tox. Not classified (Inhalation:dust,mist)<br>STOT RE Not classified<br>Aquatic Acute Not classified<br>Aquatic Chronic Not classified |
| Solvent naphtha (petroleum), heavy arom. | CAS-No.: 64742-94-5 | 0.95 – 5 | STOT RE 1, H372<br>Asp. Tox. 1, H304<br>Aquatic Chronic 2, H411 |
| Aluminium oxide | CAS-No.: 1344-28-1 | 1.79 – 2.864 | Acute Tox. Not classified (Oral)<br>Acute Tox. Not classified (Inhalation:dust,mist)<br>STOT RE 1, H372<br>Aquatic Acute 1, H400 |
| Sodium oxide | CAS-No.: 1313-59-3 | 1.1 – 1.76 | Skin Corr. 1, H314<br>Eye Dam. 1, H318<br>STOT SE 3, H335<br>Aquatic Acute Not classified<br>Aquatic Chronic Not classified |

## SECTION 4: First aid measures

### 4.1. Description of necessary first aid measures

First-aid measures general : Get medical advice/attention if you feel unwell. If medical advice is needed, have product container or label and product safety data sheet at hand.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Immediately rinse with water for a prolonged period while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth out with water. Give water to drink if victim completely conscious/alert. Do not induce vomiting because of corrosive effects. Get medical attention immediately if symptoms occur.

Self protection of the first-aider : First-aiders should pay attention to their own protection and use the recommended personal protective equipment (see section 8).

### 4.2. Most important symptoms/effect, acute and delayed

Symptoms/effects : Causes eye irritation. Causes skin irritation. May cause respiratory irritation.

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : irritation (itching, redness, blistering). May cause an allergic skin reaction.

Symptoms/effects after eye contact : Adverse symptoms may include pain, irritation, watering and redness. Blurred vision.

Symptoms/effects after ingestion : Swallowing material may cause irritation of the gastrointestinal lining, nausea, vomiting, diarrhea, and abdominal pain.

Chronic symptoms : Prolonged or repeated contact with the skin may cause dermatitis. Dust of the product, if present, may cause respiratory irritation after excessive inhalation exposure.

Potential adverse human health effects and symptoms : Causes skin and eye irritation. Harmful if swallowed. May be harmful if inhaled.

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard : No fire hazard.

Explosion hazard : No direct explosion hazard.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Special protective actions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Stop leak if safe to do so.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and materials for containment and cleaning up

For containment : Using a clean shovel, put the material in a dry container and cover without compressing it.
Methods for cleaning up : Mechanically recover the product.
Other information : Dispose of materials or solid residues at an authorized site.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Do not breathe dust, mist. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands, forearms and face thoroughly after handling. Wash contaminated clothing before reuse.
Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Packaging materials : Always store product in container of same material as original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| Silicon dioxide (7631-86-9) | |
|---|---|
| **South Africa - Occupational Exposure Limits (Airborne Pollutants)** | |
| Local name | Silica, amorphous |
| OEL TWA | 6 mg/m³ inhalable particulate<br>3 mg/m³ respirable particulate |
| Regulatory reference | Government Notice No. R 904 |

| Aluminium oxide (1344-28-1) | |
|---|---|
| **South Africa - Occupational Exposure Limits (Airborne Pollutants)** | |
| Local name | Aluminium oxides |
| OEL TWA | 10 mg/m³<br>5 mg/m³ |
| Remark | [c] The OEL for Aluminium does not include exposure to aluminium coated with mineral oil, or to fume arising from aluminium welding processes. |
| Regulatory reference | Government Notice No. R 904 |

OEL Sources : LISAM.
BLV Sources : LISAM.

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment

Materials for protective clothing : Wear protective clothing
Hand protection : Protective gloves
Eye protection : Wear security glasses which protect from splashes

| | | |
|---|---|---|
| Skin and body protection | : | Wear suitable protective clothing |
| Respiratory protection | : | In case of insufficient ventilation, wear suitable respiratory equipment |

Personal protective equipment symbol(s)



### 8.4. Exposure limit values for the other components

No additional information available

## SECTION 9: Physical and chemical properties

### 9.1. Basic physical and chemical properties

| | | |
|---|---|---|
| Physical state | : | Liquid |
| Appearance | : | Paste. |
| Colour | : | Off-white |
| Odour | : | Slight odour |
| Odour threshold | : | No data available |
| pH | : | > 8.8 – < 9.8 Source: Product TDS |
| pH solution | : | No data available |
| Relative evaporation rate (butylacetate=1) | : | No data available |
| Relative evaporation rate (ether=1) | : | No data available |
| Melting point | : | Not applicable |
| Freezing point | : | No data available |
| Boiling point | : | > 170 – < 250 °C Estimated |
| Flash point | : | > 65 – < 95 °C Estimated |
| Auto-ignition temperature | : | No data available |
| Decomposition temperature | : | No data available |
| Flammability | : | Non flammable |
| Vapour pressure | : | No data available |
| Vapour pressure at 50°C | : | No data available |
| Relative vapour density at 20°C | : | No data available |
| Relative density | : | ≈ 1.78 Standard |
| Relative density of saturated gas/air mixture | : | No data available |
| Density | : | No data available |
| Relative gas density | : | No data available |
| Solubility | : | Miscible with water. |
| Partition coefficient n-octanol/water (Log Pow) | : | No data available |
| Partition coefficient n-octanol/water (Log Kow) | : | No data available |
| Viscosity, kinematic | : | No data available |
| Viscosity, dynamic | : | > 1000 – < 10000 mPa·s Estimated |
| Explosive properties | : | Non-explosive. |
| Oxidising properties | : | Non oxidizing. |
| Explosive limits | : | No data available |
| Lower explosion limit | : | No data available |
| Upper explosion limit | : | No data available |
| Physical state | : | Liquid |
| Appearance | : | Paste. |

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10: Stability and Reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical Stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

Likely routes of exposure : Ingestion. Inhalation. Dermal.

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Harmful in contact with skin.
Acute toxicity (inhalation) : Not classified

| Prolong - Profill White | |
|---|---|
| ATE ZA (Dermal) | 1462.902 mg/kg bodyweight |

| Silicon dioxide (7631-86-9) | |
|---|---|
| LD50 oral rat | 3160 mg/kg Source: TOMES; HAZARDTEXT |
| LD50 dermal rat | ≥ 2000 mg/kg bodyweight Source: ECHA |
| LD50 dermal rabbit | > 5000 mg/kg Source: ECHA |
| LC50 Inhalation - Rat (Dust/Mist) | 5.01 mg/l Source: ECHA |

| Aluminium oxide (1344-28-1) | |
|---|---|
| LD50 oral rat | 2000 – 15900 mg/kg bodyweight Source: ECHA |
| LC50 Inhalation - Rat | ≈ 7.6 mg/l 60 min; Source: ECHA |

| Solvent naphtha (petroleum), heavy arom. (64742-94-5) | |
|---|---|
| LD50 oral rat | > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Remarks on results: other: |
| LD50 dermal rat | > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Remarks on results: other: |
| LD50 dermal rabbit | > 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Remarks on results: other: |

Skin corrosion/irritation : Causes skin irritation.
pH: > 8.8 – < 9.8 Source: Product TDS
Serious eye damage/irritation : Causes serious eye irritation.
pH: > 8.8 – < 9.8 Source: Product TDS
Respiratory or skin sensitization : Repeated exposure to dried coating dust may cause respiratory irritation.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

| Silicon dioxide (7631-86-9) | |
|---|---|
| IARC group | 3 - Not classifiable |

Reproductive toxicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified

| Sodium oxide (1313-59-3) | |
|---|---|
| STOT-single exposure | May cause respiratory irritation. |

STOT-repeated exposure : May cause damage to organs (respiratory system, Skin) through prolonged or repeated exposure (Inhalation, Dermal).

| Silicon dioxide (7631-86-9) | |
|---|---|
| NOAEL (oral, rat, 28 days) | > 2500 mg/kg bodyweight/day Source: ECHA |
| NOAEC (inhalation, rat, 28 days) | > 1.3 – < 46 mg/l Source: ECHA |

| Aluminium oxide (1344-28-1) | |
|---|---|
| LOAEC (inhalation, rat, dust/mist/fume, 90 days) | 0.015 mg/l air Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies) |
| STOT-repeated exposure | Causes damage to organs through prolonged or repeated exposure. |

| Solvent naphtha (petroleum), heavy arom. (64742-94-5) | |
|---|---|
| LOAEL (dermal, rat/rabbit, 90 days) | 50 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) |
| LOAEC (inhalation, rat, vapour, 90 days) | 4.71 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study) |
| NOAEL (oral, rat, 28 days) | ≥ 4 mg/kg bodyweight/day Source: ECHA |
| NOAEC (inhalation, rat, vapour, 90 days) | 2355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study) |
| STOT-repeated exposure | Causes damage to organs through prolonged or repeated exposure. |

Aspiration hazard : Not classified
Potential adverse human health effects and symptoms : Causes skin and eye irritation. Harmful if swallowed. May be harmful if inhaled.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short–term (acute) : Not classified
Hazardous to the aquatic environment, long–term (chronic) : Not classified

| Silicon dioxide (7631-86-9) | |
|---|---|
| LC50 - Fish [1] | 10000 mg/l Source: ECHA |
| EC50 - Crustacea [1] | > 5000 mg/l Source: ECHA |
| EC50 72h - Algae [1] | > 173.1 mg/l Source: ECHA |
| EC50 96h - Algae [1] | > 217.576 – < 217.6 mg/l Source: ECHA |
| LOEC (chronic) | ≈ 149.2 mg/l Source: ECHA |
| NOEC (chronic) | > 68 – < 250 mg/l 21 days; Source: ECHA |
| NOEC chronic fish | > 57.001 – < 86.03 mg/l Source: ECHA |
| NOEC chronic algae | > 42.1 – < 42.11 mg/l Source: ECHA |

| Aluminium oxide (1344-28-1) | |
|---|---|
| LC50 - Fish [1] | 78 – 218644.1 µg/l Source: ECHA |

| Aluminium oxide (1344-28-1) | |
|---|---|
| EC50 - Crustacea [1] | 1.5 – 500 mg/l Source: ECHA |
| EC50 - Crustacea [2] | 5.7 – 5000000 µg/l Source: ECHA |
| EC50 72h - Algae [1] | 1.05 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) |
| EC50 72h - Algae [2] | 0.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) |
| LOEC (acute) | ≈ 5.314 mg/l (7 days); Source: ECHA |
| NOEC (chronic) | 4.7 – 2.31 mg/l (28 days); Source: ECHA |
| NOEC chronic crustacea | 0.2326 – 0.4538 mg/l (42 days); Source: ECHA |
| NOEC chronic algae | ≈ 1 g/l (6 days); Source: ECHA |

| Sodium oxide (1313-59-3) | |
|---|---|
| LC50 - Fish [1] | 208000000 mg/l Source: QSAR |
| EC50 96h - Algae [1] | 56800000 mg/l Source: QSAR |

| Solvent naphtha (petroleum), heavy arom. (64742-94-5) | |
|---|---|
| LC50 - Fish [1] | > 580 – < 8410 µg/l Source: ECHA |
| EC50 - Crustacea [1] | 1.2 mg/l Test organisms (species): Daphnia magna |
| EC50 72h - Algae [1] | > 12.4 – < 18.9 mg/l Source: ECHA |

## 12.2. Persistence and degradability

| Prolong - Profill White | |
|---|---|
| Persistence and degradability | Rapidly degradable |

| Silicon dioxide (7631-86-9) | |
|---|---|
| Persistence and degradability | |

| Aluminium oxide (1344-28-1) | |
|---|---|
| Persistence and degradability | |

| Sodium oxide (1313-59-3) | |
|---|---|
| Persistence and degradability | |

| Solvent naphtha (petroleum), heavy arom. (64742-94-5) | |
|---|---|
| Persistence and degradability | |

## 12.3. Bioaccumulative potential

| Prolong - Profill White | |
|---|---|
| Bioaccumulative potential | No additional information available |

| Silicon dioxide (7631-86-9) | |
|---|---|
| Partition coefficient n-octanol/water (Log Kow) | ≈ 0.53 @ 25 °C and pH 7; Source: ECHA |

| Solvent naphtha (petroleum), heavy arom. (64742-94-5) | |
|---|---|
| Partition coefficient n-octanol/water (Log Kow) | > 2.4 – < 6.5 @ 21 - 25 °C and pH 6.2 - 7; Source: ECHA |

## 12.4. Mobility in soil

| Prolong - Profill White | |
|---|---|
| Mobility in soil | No additional information available |

### 12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No additional information available

## SECTION 13: Disposal Considerations

### 13.1. Disposal methods

Regional waste regulation : HCA Regulations under OHSA (2021). South Africa's Waste Act (Act 59 of 2008).
Waste treatment methods : Unwanted product may be brushed onto absorbent material, such as newspaper or cardboard, allowed to dry completely in a well-ventilated area, and disposed of via waste collection. Incineration at licensed facilities must occur in a hazardous waste incinerator with air pollution control systems.
Sewage disposal recommendations : Do not dispose of waste into sewer or stormwater systems.
Product/Packaging disposal recommendations : Recycle or dispose of in compliance with current legislation.
Ecological waste information : The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

## SECTION 14: Transport information

In accordance with SANS / UN RTDG / IMDG / IATA

| SANS | UN RTDG | IMDG | IATA |
|---|---|---|---|
| **14.1. UN number** | | | |
| Not regulated for transport | | | |
| **14.2. UN Proper Shipping Name** | | | |
| Not applicable | Not applicable | Not applicable | Not applicable |
| **Transport document description** | | | |
| Not applicable | Not applicable | Not applicable | Not applicable |
| **14.3. Transport hazard class(es)** | | | |
| Not applicable | Not applicable | Not applicable | Not applicable |
| Not applicable | Not applicable | Not applicable | Not applicable |
| **14.4. Packing group, if applicable** | | | |
| Not applicable | Not applicable | Not applicable | Not applicable |
| **14.5. Environmental hazards** | | | |
| Dangerous for the environment : No | Dangerous for the environment : No | Dangerous for the environment : No<br>Marine pollutant : No | Dangerous for the environment : No |
| No supplementary information available | | | |

### 14.6. Special precautions for user

**SANS**
No data available

**UN RTDG**
No data available

**IMDG**
No data available

**IATA**
No data available

### 14.7. Transport in bulk according to IMO instructions

Not applicable

## SECTION 15: Regulatory information

### 15.1. National regulations

#### 15.1.1. OCCUPATIONAL HEALTH AND SAFETY ACT, 1993

| Prohibited Hazardous Chemical Agents |
|---|
| Not regulated |

#### 15.1.2. National Environmental Management Act, 1998

| Regulation No. 51358 (Prior Informed Consent Procedure Regulations, 2024) |
|---|
| Not regulated |

### 15.2. Safety, health, and environmental national regulations specific for the product

State or local regulations : This product complies with South African legal lead limit of 90ppm or less.

## SECTION 16: Other information

Issue date : 07/02/2023
Revision date : 26/10/2026
Supersedes : 26/10/2026

| Full text of H-statements: | |
|---|---|
| H225 | Highly flammable liquid and vapour |
| H226 | Flammable liquid and vapour |
| H302 | Harmful if swallowed |
| H304 | May be fatal if swallowed and enters airways |
| H312 | Harmful in contact with skin |
| H314 | Causes severe skin burns and eye damage |
| H315 | Causes skin irritation |
| H318 | Causes serious eye damage |
| H319 | Causes serious eye irritation |
| H330 | Fatal if inhaled |
| H331 | Toxic if inhaled |
| H335 | May cause respiratory irritation |
| H340 | May cause genetic defects |
| H350 | May cause cancer |
| H351 | Suspected of causing cancer |
| H370 | Causes damage to organs |
| H372 | Causes damage to organs through prolonged or repeated exposure |
| H373 | May cause damage to organs through prolonged or repeated exposure |
| H400 | Very toxic to aquatic life |
| H402 | Harmful to aquatic life |

| Full text of H-statements: | |
|---|---|
| H411 | Toxic to aquatic life with long lasting effects |

Safety Data Sheet (SDS), South Africa (HCA)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.