Dura Paints - Hydro Finish - Transparent

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 10
Issue date: 25/11/2022 Revision date: 3/11/2026 Supersedes: 3/11/2026 Version: 1.9

SECTION 1: Identification of the substance/mixture and of the supplier/undertaking

1.1. GHS product identifier

Product form	:	Mixture
Trade name	:	Dura Paints - Hydro Finish - Transparent
Type of product	:	Coatings
Product code	:	HYDFINTRA
Product group	:	Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use	:	Water-based coating for light industrial applications

1.4. Supplier's details

Manufacturer
Dura Paints (Pty) Ltd.
5 Wakefield Road; Founders View South.
P.O. Box 303
1610 Edenvale; Johannesburg – South Africa
T 011 452 5221
orders@durapaints.co.za - www.durapaints.co.za

1.5. Emergency phone number

Emergency number	:	079 494 2731 / 011 452 5221

SECTION 2: Hazard identification

2.1. GHS classification of the substance/mixture and any national or regional information

Classification according to the United Nations GHS

Skin corrosion/irritation Not classified

Full text of H-statements: see section 16

2.2. GHS label elements, including precautionary statements

Labelling according to the United Nations GHS

Precautionary statements (GHS ZA)	:	P101 - If medical advice is needed, have product container or label and product safety data sheet at hand. P102 - Keep out of reach of children. P103 - Read carefully and follow all instructions. P280 - Wear protective gloves, protective clothing, eye protection. P501 - Dispose of container to Recycling, according to local regulations.
P-statements for label (GHS-ZA)	:	P101 - If medical advice is needed, have product container or label and product safety data sheet at hand.; P102 - Keep out of reach of children.; P103 - Read carefully and follow all instructions.; P280 - Wear protective gloves, protective clothing, eye protection.; P501 - Dispose of container to Recycling, according to local regulations.

2.3. Other hazards which do not result in classification or are not covered by the GHS

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to the United Nations GHS
Ethelyne Glycol (Regular)	CAS-No.: 107-21-1	1 – 3	Acute Tox. 4 (Oral), H302

SECTION 4: First aid measures

4.1. Description of necessary first aid measures

First-aid measures general : If medical advice is needed, have product container or label and product safety data sheet at hand.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.
Self protection of the first-aider : First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effect, acute and delayed

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact : None under normal conditions.
Symptoms/effects after eye contact : None under normal conditions.
Symptoms/effects after ingestion : None under normal conditions.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : No fire hazard.
Explosion hazard : No direct explosion hazard.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective actions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment	:	Wear recommended personal protective equipment.
Emergency procedures	:	Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment	:	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	:	Evacuate non-essential personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

For containment	:	Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up	:	Take up liquid spill into absorbent material.
Other information	:	Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	:	Ensure good ventilation of the work station. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray.
Hygiene measures	:	Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	:	Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	:	Keep in a cool, well-ventilated place away from heat.
Storage conditions	:	Store in tightly sealed containers in a cool, dry, well-ventilated area. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Packaging materials	:	Always store product in container of same material as original container.
Material used in packaging/containers	:	steel, hdpu or approved chemical drums.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethelyne Glycol (Regular) (107-21-1)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Ethylene glycol
OEL eight hour TWA	20 mg/m³ (H: aerosol only)
RHCA - STEL/C	50 mg/m³ (V: vapour fraction) 100 mg/m³ (V: vapour fraction)
Remark	SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Ethylene glycol (Ethane-1,2-diol; 1,2-Dihydroxyethane)
OEL TWA	20 mg/m³
OEL STEL	40 mg/m³
Regulatory reference	Government Notice No. R 904

OEL Sources : LISAM.

BLV Sources : LISAM.

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection : Protective gloves
Eye protection : Safety glasses
Skin and body protection : Wear suitable protective clothing
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment
Personal protective equipment symbol(s)



8.4. Exposure limit values for the other components

Ethane-1,2-diol (107-21-1)		
South Africa - Occupational Exposure Limits (Restricted Limits)		
Local name	Ethylene glycol	
OEL eight hour TWA	20 mg/m³ (H: aerosol only)	
RHCA - STEL/C	50 mg/m³ (V: vapour fraction) 100 mg/m³ (V: vapour fraction)	
Remark	SKIN (danger of cutaneous absorption)	
Regulatory reference	Government Notice No. R. 280, 2021	
South Africa - Occupational Exposure Limits (Airborne Pollutants)		
Local name	Ethylene glycol (Ethane-1,2-diol; 1,2-Dihydroxyethane)	
OEL TWA	20 mg/m³	
OEL STEL	40 mg/m³	
Regulatory reference	Government Notice No. R 904	

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid
Appearance : Viscous liquid.
Colour : Colourless,Can be tinted to various colours
Odour : characteristic,Mild odour
Odour threshold : No data available
pH : 8.8 – 9.3 Standard
pH solution : No data available
Relative evaporation rate (butylacetate=1) : No data available
Relative evaporation rate (ether=1) : No data available
Melting point : Not applicable
Freezing point : > -2 – < 0 °C Estimated
Boiling point : ≈ 100 °C Estimated ininital boiling point
Flash point : Not applicable (water-based mixture)
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability : Non flammable

Vapour pressure	:	Similair to water
Vapour pressure at 50°C	:	No data available
Relative vapour density at 20°C	:	> 1 Estimated
Relative density	:	No data available
Relative density of saturated gas/air mixture	:	> 1 – < 1.05 Standard
Density	:	No data available
Relative gas density	:	No data available
Solubility	:	Miscible with water.
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Partition coefficient n-octanol/water (Log Kow)	:	No data available
Viscosity, kinematic	:	> 1 – < 5 mm²/s Estimated
Viscosity, dynamic	:	1000 – 1300 cP Standard at 25°C
Explosive properties	:	No data available
Oxidising properties	:	No data available
Explosive limits	:	No data available
Lower explosion limit	:	No data available
Upper explosion limit	:	No data available
Physical state	:	Liquid
Appearance	:	Viscous liquid.

9.2. Data relevant with regard to physical hazard classes (supplemental)

VOC content : < 5 % Estimated

SECTION 10: Stability and Reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical Stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Ethelyne Glycol (Regular) (107-21-1)	
LD50 oral rat	6000 – 13000 mg/kg Source: Supplier SDS
LD50 dermal rat	> 22270 mg/kg bodyweight Source: Supplier SDS
LD50 dermal rabbit	> 2270 mg/kg Source: Supplier SDS
LC50 Inhalation - Rat	> 3.95 mg/l Source: Supplier SDS

Ethelyne Glycol (Regular) (107-21-1)	
LC50 Inhalation - Rat (Vapours)	> 3.95 mg/l/4h Source: Supplier SDS

Skin corrosion/irritation : Not classified.
pH: 8.8 – 9.3 Standard

Serious eye damage/irritation : Not classified
pH: 8.8 – 9.3 Standard

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Dura Paints - Hydro Finish - Transparent	
Viscosity, kinematic	> 1 – < 5 mm²/s Estimated

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short–term (acute) : Not classified

Hazardous to the aquatic environment, long–term (chronic) : Not classified

Ethelyne Glycol (Regular) (107-21-1)	
LC50 - Fish [1]	≈ 51000 mg/l Source: Supplier SDS
LC50 - Fish [2]	≈ 27540 (≤ 0) mg/l Source: Supplier SDS
EC50 - Crustacea [1]	46300 – 51100 mg/l Source: Supplier SDS
EC50 72h - Algae [1]	9500 – 13000 mg/l Source: Supplier SDS
NOEC chronic fish	≈ 15.38 g/l Source: ECHA
NOEC chronic crustacea	7.5 – 15 g/l Period: 21 days; Source: ECHA
NOEC chronic algae	≈ 100 mg/l Period: 72 hours; Source: ECHA

12.2. Persistence and degradability

Dura Paints - Hydro Finish - Transparent	
Persistence and degradability	Rapidly degradable

Ethelyne Glycol (Regular) (107-21-1)	
Persistence and degradability	

12.3. Bioaccumulative potential

Dura Paints - Hydro Finish - Transparent	
Bioaccumulative potential	No additional information available

Ethelyne Glycol (Regular) (107-21-1)	
Bioconcentration factor (BCF REACH)	< 100
Partition coefficient n-octanol/water (Log Kow)	≈ -1.36 Source: Supplier SDS

12.4. Mobility in soil

Dura Paints - Hydro Finish - Transparent	
Mobility in soil	No additional information available

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No additional information available

SECTION 13: Disposal Considerations

13.1. Disposal methods

Regional waste regulation : Disposal must be done according to official regulations. South Africa's Waste Act (Act 59 of 2008).
Waste treatment methods : Unwanted product may be brushed onto absorbent material, such as newspaper or cardboard, allowed to dry completely in a well-ventilated area, and disposed of via waste collection. Incineration at licensed facilities must occur in a hazardous waste incinerator with air pollution control systems.
Sewage disposal recommendations : Do not dispose of waste into sewer or stormwater systems.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations. Empty containers should be recycled or disposed of through an approved waste contractor.
Ecological waste information : The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

SECTION 14: Transport information

In accordance with SANS / UN RTDG / IMDG / IATA

SANS	UN RTDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. UN Proper Shipping Name			
Not applicable	Not applicable	Not applicable	Not applicable
Transport document description			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group, if applicable			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available			

14.6. Special precautions for user

SANS
No data available

UN RTDG
No data available

IMDG
No data available

IATA
No data available

14.7. Transport in bulk according to IMO instructions

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

15.1.1. OCCUPATIONAL HEALTH AND SAFETY ACT, 1993

Prohibited Hazardous Chemical Agents
Not regulated

15.1.2. National Environmental Management Act, 1998

Regulation No. 51358 (Prior Informed Consent Procedure Regulations, 2024)
Not regulated

15.2. Safety, health, and environmental national regulations specific for the product

State or local regulations : This product complies with South African legal lead limit of 90ppm or less.

SECTION 16: Other information

Issue date : 25/11/2022
Revision date : 03/11/2026
Supersedes : 03/11/2026

Full text of H-statements:	
H302	Harmful if swallowed

Safety Data Sheet (SDS), South Africa (HCA)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.