Dura Paints - Industrial Tint - Yellow 67

Safety Data Sheet

According to Regulations for Hazardous Chemical Agents, 2021 and United Nations GHS revision 9
Issue date: 13/1/2025 Revision date: 30/10/2026 Supersedes: 1/7/2026 Version: 1.4

SECTION 1: Identification of the substance/mixture and of the supplier/undertaking

1.1. GHS product identifier

Product form	:	Mixture
Trade name	:	Dura Paints - Industrial Tint - Yellow 67
Type of product	:	Coatings
Product code	:	TINTYELL67
Product group	:	Trade product

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use	:	Colourant used in light industrial coatings

1.4. Supplier's details

Manufacturer
Dura Paints (Pty) Ltd.
5 Wakefield Road; Founders View South.
P.O. Box 303
1610 Edenvale; Johannesburg – South Africa
T 011 452 5221
orders@durapaints.co.za - www.durapaints.co.za

1.5. Emergency phone number

Emergency number	:	079 494 2731 / 011 452 5221

SECTION 2: Hazard identification

2.1. GHS classification of the substance/mixture and any national or regional information

Classification according to the United Nations GHS

Flammable liquids, Category 3	H226
Skin corrosion/irritation, Category 2	H315
Germ cell mutagenicity, Category 1B	H340
Carcinogenicity, Category 1B	H350
Specific target organ toxicity – single exposure, Category 1	H370
Hazardous to the aquatic environment – Acute Hazard, Category 1	H400
Hazardous to the aquatic environment – Chronic Hazard, Category 1	H410

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects	:	Flammable liquid and vapour,May cause cancer,May cause genetic defects,Causes damage to organs,Causes skin irritation,Toxic to aquatic life with long lasting effects.

2.2. GHS label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS ZA) :



Signal word (GHS ZA)	:	Danger
Hazardous ingredients	:	Xylene; Naphtha (petroleum), heavy alkylate
Hazard statements (GHS ZA)	:	H226 - Flammable liquid and vapour H315 - Causes skin irritation

		H340 - May cause genetic defects (Dermal, Inhalation, Oral) H350 - May cause cancer (Inhalation, Dermal, Oral) H370 - Causes damage to organs (central nervous system, respiratory system, Skin) (Dermal, Inhalation, Oral) H410 - Very toxic to aquatic life with long lasting effects
Precautionary statements (GHS ZA)	:	P101 - If medical advice is needed, have product container or label and product safety data sheet at hand. P102 - Keep out of reach of children. P103 - Read carefully and follow all instructions. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 - Ground and bond container and receiving equipment. P261 - Avoid breathing fume, mist, spray, vapours. P273 - Avoid release to the environment. P280 - Wear eye protection, protective clothing, protective gloves. P271 - Use only outdoors or in a well-ventilated area. P501 - Dispose of container to according to local regulations, recycling.
P-statements for label (GHS-ZA)	:	P101 - If medical advice is needed, have product container or label and product safety data sheet at hand.; P102 - Keep out of reach of children.; P103 - Read carefully and follow all instructions.; P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.; P240 - Ground and bond container and receiving equipment.; P261 - Avoid breathing fume, mist, spray, vapours.; P273 - Avoid release to the environment.; P280 - Wear eye protection, protective clothing, protective gloves.; P271 - Use only outdoors or in a well-ventilated area.; P501 - Dispose of container to according to local regulations, recycling.

2.3. Other hazards which do not result in classification or are not covered by the GHS

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to the United Nations GHS
Cadmium zinc sulfide yellow - C.I Pigment yellow 035	CAS-No.: 8048-07-5	17.5 – 65	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Xylene	CAS-No.: 1330-20-7	20 – 30	Flam. Liq. 3, H226 Acute Tox. Not classified (Oral) Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. Not classified (Inhalation:vapour) Skin Irrit. 2, H315 STOT SE 1, H370 STOT RE Not classified Aquatic Chronic 2, H411
Cadmium sulfoselenide orange - C.I. Pigment orange 20	CAS-No.: 12656-57-4	0.35 – 13	Aquatic Chronic 2, H411
Cadmium sulfoselenide red - C.I. Pigment red 108	CAS-No.: 58339-34-7	0.35 – 13	Aquatic Chronic 2, H411
Naphtha (petroleum), heavy alkylate	CAS-No.: 64741-65-7	0.1 – 0.625	Flam. Liq. 3, H226 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304

SECTION 4: First aid measures

4.1. Description of necessary first aid measures

First-aid measures general : If medical advice is needed, have product container or label at hand. IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If breathing stops, give artificial respiration . If respiratory irritation, dizziness, nausea or unconsciousness occurs, seek immediate medical assistance. Call a poison center or a doctor if you feel unwell.

First-aid measures after skin contact : Wash contaminated clothing before reuse. If product is injected into or under the skin, or any part of the body, it should be treated as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment with in the first few hours may significantly reduce the ultimate extent of injury. Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Get immediate medical advice/attention. Do not induce vomiting/risk of damage to lungs exceeds poisoning risk. Call a poison center or a doctor if you feel unwell.

Self protection of the first-aider : First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effect, acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after inhalation : May cause drowsiness or dizziness. Adverse symptoms may include nausea or vomiting, headache, respiratory irritation. Harmful if inhaled.

Symptoms/effects after skin contact : Harmful in contact with skin. Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation. Adverse symptoms may include pain, irritation, watering and redness. Eye irritation.

Symptoms/effects after ingestion : Swallowing material may cause irritation of the gastrointestinal lining, nausea, vomiting, diarrhea, and abdominal pain. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

Symptoms/effects upon intravenous administration : Pain, swelling, and erythema: Rapid onset at the injection site; Chemical necrotising cellulitis: Inflammatory destruction of soft tissue, often within 24 hours.

Chronic symptoms : Neurological: Headaches, memory loss, fatigue;Dermal: Can lead to dermatitis, with symptoms like cracking, scaling, and inflammation; Renal/Hepatic: Liver and kidney stress.

Potential adverse human health effects and symptoms : High concentration of vapours may induce: headache, dizziness, drowsiness, nausea and vomiting and in severe cases, loss of consciousness. Toxic if swallowed.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

See section 4.1. Description of first-aid measures. Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapour.


Explosion hazard : When vapors accumulate in enclosed or poorly ventilated areas, any ignition source (e.g. static discharge, open flame, hot surfaces) can trigger an explosion. This is especially critical in spray booths, storage tanks, and confined mixing areas.

Reactivity in case of fire : Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective actions for fire-fighters

Precautionary measures fire : Evacuate area. Eliminate all ignition sources if safe to do so. Cool endangered containers with water spray or fog.

Firefighting instructions	:	Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	:	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Personal protection (Emergency response)	:	Fire-resistant protective clothing,Use breathing equipment (SCBA),Use only explosion-proof equipment and PPE
	:	

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	:	Eliminate every possible source of ignition. Ventilate spillage area. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
Personal Precautions, Protective Equipment and Emergency Procedures	:	Avoid contact with skin and eyes, avoid breathing vapours. Use only non-sparking tools. Complete protective clothing.
Prevention Measures for Secondary Accidents	:	Avoid sparks. Take precautionary measures against static discharge.

6.1.1. For non-emergency personnel

Protective equipment	:	Wear recommended personal protective equipment.
Emergency procedures	:	Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment	:	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	:	Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Ventilate area. Evacuate non-essential personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

6.3. Methods and materials for containment and cleaning up

For containment	:	Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up	:	Take up liquid spill into absorbent material. Absorb spillage with vermiculite or sand; Scoop into labeled hazardous waste container. Use non-sparking tools. Notify authorities if product enters sewers or public waters.
Other information	:	Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	:	Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe mist, spray, vapours. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
Local and general ventilation	:	Local exhaust ventilation.
Hygiene measures	:	Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	:	Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	:	Ground/bond container and receiving equipment.
Storage conditions	:	Store in tightly sealed containers in a cool, dry, well-ventilated area. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Keep away from ignition sources.
Storage area	:	Ensure electrical equipment and fittings comply with local fire prevention regulations for this class of product. Refer to national or local refulations covering safety at petroleum handling and storage areas for this product.
Incompatible products	:	Oxidizing agent. Strong acids. Strong bases.
Packaging materials	:	Always store product in container of same material as original container.
Material used in packaging/containers	:	steel, hdpu or approved chemical drums.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Xylene (1330-20-7)	
South Africa - Occupational Exposure Limits (Restricted Limits)	
Local name	Xylene, o-, m-, p- or mixed isomers
OEL eight hour TWA	300 ppm
RHCA - STEL/C	200 ppm
Remark	SKIN (danger of cutaneous absorption)
Regulatory reference	Government Notice No. R. 280, 2021
South Africa - Occupational Exposure Limits (Airborne Pollutants)	
Local name	Xylene, o-, m-, p- or mixed isomers
OEL TWA	218 mg/m³
	50 ppm
OEL STEL	435 mg/m³
	100 ppm
Remark	Sk (Danger of cutaneous absorption)
Regulatory reference	Government Notice No. R 904
South Africa - Biological limit values	
Local name	Xylenes
BEI	1.5 g/g creatinine Parameter: Methylhippuric acids - Medium: urine - Sampling time: End of shift
Regulatory reference	Government Notice No. R. 280, 2021

OEL Sources	:	LISAM.
BLV Sources	:	LISAM.

8.2. Appropriate engineering controls

Appropriate engineering controls	:	Ensure good ventilation of the work station.
Environmental exposure controls	:	Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Materials for protective clothing	:	Chemical resistant overalls
Hand protection	:	Protective gloves
Eye protection	:	Wear security glasses which protect from splashes
Skin and body protection	:	Wear suitable protective clothing
Respiratory protection	:	[In case of inadequate ventilation] wear respiratory protection.
Personal protective equipment symbol(s)		



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	:	Liquid
Appearance	:	Viscous liquid.
Colour	:	Yellow
Odour	:	Aromatic solvent like odour
Odour threshold	:	No data available
pH	:	Not applicable (solvent-borne coating)
pH solution	:	No data available
Relative evaporation rate (butylacetate=1)	:	No data available
Relative evaporation rate (ether=1)	:	No data available
Melting point	:	Not applicable
Freezing point	:	No data available
Boiling point	:	> 137 – < 145 °C Estimated
Flash point	:	> 25 – < 30 °C Estimated
Auto-ignition temperature	:	> 450 °C Estimated
Decomposition temperature	:	No data available
Flammability	:	Flammable liquid and vapour.
Vapour pressure	:	> 0.6 – < 1 kPa Estimated
Vapour pressure at 50°C	:	No data available
Relative vapour density at 20°C	:	> 3.6 Estimated
Relative density	:	> 1.05 – < 1.84 Standard - Varies by colour
Relative density of saturated gas/air mixture	:	No data available
Density	:	No data available
Relative gas density	:	No data available
Solubility	:	insoluble in water. soluble in most organic solvents.
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Partition coefficient n-octanol/water (Log Kow)	:	No data available
Viscosity, kinematic	:	< 2 mm²/s Estimated
Viscosity, dynamic	:	> 440 – < 1200 cP Standard - Varies by colour
Explosive properties	:	Vapours may form explosive mixture with air.
Oxidising properties	:	Non oxidizing.
Explosive limits	:	No data available
Lower explosion limit	:	≈ 1 Vol-% Estimated
Upper explosion limit	:	≈ 7 Vol-% Estimated
Physical state	:	Liquid
Appearance	:	Viscous liquid.

9.2. Data relevant with regard to physical hazard classes (supplemental)

VOC content	:	> 15 – < 35 % Estimated

SECTION 10: Stability and Reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical Stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Likely routes of exposure : Dermal. Inhalation. Ingestion.

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Xylene (1330-20-7)	
LD50 oral rat	> 3523 – < 6631 mg/kg bodyweight XYLENE : ECHA
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male, Remarks on results: other:
LC50 Inhalation - Rat	≥ 27.124 mg/l XYLENE : ECHA

Cadmium sulfoselenide orange - C.I. Pigment orange 20 (12656-57-4)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)

Cadmium sulfoselenide red - C.I. Pigment red 108 (58339-34-7)	
LD50 oral rat	> 2000 mg/kg Source: ECHA

Skin corrosion/irritation : Causes skin irritation.
pH: Not applicable (solvent-borne coating)
Serious eye damage/irritation : Not classified
pH: Not applicable (solvent-borne coating)
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : May cause genetic defects (Dermal, Inhalation, Oral).
Carcinogenicity : May cause cancer (Inhalation, Dermal, Oral).
Reproductive toxicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Causes damage to organs (central nervous system, respiratory system, Skin) (Dermal, Inhalation, Oral).

Xylene (1330-20-7)	
LOAEL (oral, rat)	≈ 150 mg/kg bodyweight XYLENE : ECHA
NOAEL (oral, rat)	≈ 250 mg/kg bodyweight XYLENE : ECHA
NOAEC (inhalation, rat, gas)	> 450 – < 1800 ppmv/4h XYLENE : 12H : ECHA
STOT-single exposure	Causes damage to organs (central nervous system) (Inhalation).

STOT-repeated exposure : Not classified

Xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)

Aspiration hazard : Not classified

Dura Paints - Industrial Tint - Yellow 67	
Viscosity, kinematic	< 2 mm²/s Estimated

Potential adverse human health effects and symptoms : High concentration of vapours may induce: headache, dizziness, drowsiness, nausea and vomiting and in severe cases, loss of consciousness. Toxic if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short–term (acute) : Very toxic to aquatic life.

Hazardous to the aquatic environment, long–term (chronic) : Very toxic to aquatic life with long lasting effects.

Xylene (1330-20-7)	
LC50 - Fish [1]	> 2.6 – < 9.6 mg/l Source: ECHA
EC50 - Crustacea [1]	≥ 10.389 mg/l Source: Echa
EC50 72h - Algae [1]	> 4.6 – < 4.9 mg/l XYLENE : Aquatic Algae : ECHA
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
NOEC chronic algae	≈ 0.44 mg/l XYLENE : Aquatic Algae 73H : ECHA

Cadmium zinc sulfide yellow - C.I Pigment yellow 035 (8048-07-5)	
LC50 - Fish [1]	1000 mg/l Inherited from KOSHA database
EC50 - Crustacea [1]	6.5 mg/l Source: Chat GPT
ErC50 algae	0.37 mg/l Source: ECHA

Cadmium sulfoselenide orange - C.I. Pigment orange 20 (12656-57-4)	
LC50 - Fish [1]	≥ 1 g/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 72h - Algae [1]	3.1 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
LOEC (chronic)	0.29 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Cadmium sulfoselenide red - C.I. Pigment red 108 (58339-34-7)	
LC50 - Fish [1]	> 1000 mg/l Source: ECHA
EC50 - Crustacea [1]	> 2.2 mg/l Source: ECHA
EC50 72h - Algae [1]	3.1 mg/l Source: ECHA

12.2. Persistence and degradability

Dura Paints - Industrial Tint - Yellow 67	
Persistence and degradability	Not rapidly degradable

Xylene (1330-20-7)	
Persistence and degradability	
Chemical oxygen demand (COD)	> 2.56 – < 2.91 g O_2/g substance

Naphtha (petroleum), heavy alkylate (64741-65-7)	
Persistence and degradability	

Cadmium zinc sulfide yellow - C.I Pigment yellow 035 (8048-07-5)	
Persistence and degradability	

Cadmium sulfoselenide orange - C.I. Pigment orange 20 (12656-57-4)	
Persistence and degradability	

Cadmium sulfoselenide red - C.I. Pigment red 108 (58339-34-7)	
Persistence and degradability	

12.3. Bioaccumulative potential

Dura Paints - Industrial Tint - Yellow 67	
Bioaccumulative potential	No additional information available

Xylene (1330-20-7)	
Partition coefficient n-octanol/water (Log Pow)	> 3.155 – < 3.16 XYLENE @ 20 °C : ECHA
Partition coefficient n-octanol/water (Log Kow)	> 3.12 – < 3.2 XYLENE @ 20 °C and pH 7: ECHA

12.4. Mobility in soil

Dura Paints - Industrial Tint - Yellow 67	
Mobility in soil	No additional information available

Xylene (1330-20-7)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	≈ 537 XYLENE: @ 20 °C : ECHA

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No additional information available


SECTION 13: Disposal Considerations

13.1. Disposal methods

Regional waste regulation : HCA Regulations under OHSA (2021). South Africa's Waste Act (Act 59 of 2008).
Waste treatment methods : Unwanted product may be brushed onto absorbent material, such as newspaper or cardboard, allowed to dry completely in a well-ventilated area, and disposed of via waste collection. Incineration at licensed facilities must occur in a hazardous waste incinerator with air pollution control systems.
Sewage disposal recommendations : Do not dispose of waste into sewer or stormwater systems.
Product/Packaging disposal recommendations : Recycle or dispose of in compliance with current legislation.
Ecological waste information : The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with SANS / UN RTDG / IMDG / IATA

SANS	UN RTDG	IMDG	IATA
14.1. UN number			
1263	1263	1263	1263
14.2. UN Proper Shipping Name			
PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	Paint
Transport document description			
Not applicable	UN 1263 PAINT RELATED MATERIAL, 3, III	UN 1263 PAINT RELATED MATERIAL, 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1263 Paint, 3, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)			
3	3	3	3
	 Not applicable		
14.4. Packing group, if applicable			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes
No supplementary information available			

14.6. Special precautions for user

SANS

Special provisions (SANS) : 163, 187, 223
Limited quantities (SANS) : 5 L
Excepted quantities (SANS) : E1
Packagings, large packagings and IBCs Packing instructions (SANS) : P001, IBC03, LP01
Packagings, large packagings and IBCs Special packing instructions (SANS) : PP1
Portable tank and bulk containers instructions (SANS) : T2
Portable tank and bulk container special provisions (SANS) : TP1, TP29

UN RTDG

Special provisions (UN RTDG) : 163, 223, 367
Limited quantities (UN RTDG) : 5L
Excepted quantities (UN RTDG) : E1
Packing instruction (UN RTDG) : P001, IBC03, LP01
Special packing provisions (UN RTDG) : PP1
Portable tank and bulk container special instructions (UN RTDG) : T2
Portable tank and bulk container special provisions (UN RTDG) : TP1, TP29

IMDG

Special provisions (IMDG)	:	163, 223, 367, 955
Limited quantities (IMDG)	:	5 L
Excepted quantities (IMDG)	:	E1
Packing instructions (IMDG)	:	P001, LP01
Special packing provisions (IMDG)	:	PP1
IBC packing instructions (IMDG)	:	IBC03
Tank instructions (IMDG)	:	T2
Tank special provisions (IMDG)	:	TP1, TP29
EmS-No. (Fire)	:	F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	:	S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG)	:	A
Properties and observations (IMDG)	:	Miscibility with water depends upon the composition.

IATA

PCA Excepted quantities (IATA)	:	E1
PCA Limited quantities (IATA)	:	Y344
PCA limited quantity max net quantity (IATA)	:	10L
PCA packing instructions (IATA)	:	355
PCA max net quantity (IATA)	:	60L
CAO packing instructions (IATA)	:	366
CAO max net quantity (IATA)	:	220L
Special provisions (IATA)	:	A3, A72, A192
ERG code (IATA)	:	3L

14.7. Transport in bulk according to IMO instructions

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

15.1.1. OCCUPATIONAL HEALTH AND SAFETY ACT, 1993

Prohibited Hazardous Chemical Agents
Not regulated

15.1.2. National Environmental Management Act, 1998

Regulation No. 51358 (Prior Informed Consent Procedure Regulations, 2024)
Not regulated

15.2. Safety, health, and environmental national regulations specific for the product

State or local regulations : This product complies with South African legal lead limit of 90ppm or less.

SECTION 16: Other information

Issue date	:	13/01/2025
Revision date	:	30/10/2026
Supersedes	:	01/07/2026

Full text of H-statements:	
H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H332	Harmful if inhaled

Full text of H-statements:	
H340	May cause genetic defects
H350	May cause cancer
H370	Causes damage to organs
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), South Africa (HCA)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.