



Feel it ...

DATA SHEET INTANACO STUCCO

LIFESTYLE INTANACO STUCCO is a pigmented white cement, fine plaster. It has been designed and formulated to give the effect of traditional Italian plasters (Intanaco). LIFESTYLE INTANACO STUCCO is designed for interior walls and is also ideal for use in high moisture areas as kitchens and bathrooms. When used in showers, it should be sealed with lifestyle matt sealer and then with Twin Pack Polyurethane sealer. Acrylic sealers will blanch (whiten) when exposed to hot water.

METHOD OF APPLICATION

- a. Surface Inspection and Preparation:
 1. Check for patches, fillers and cracks etc.
 2. Apply Slurrycote as per Slurrycote data sheet and allow drying for 24 hours. If the wall is painted. (failure to do so will show up these marks when the stucco dries).
 3. If the surface is extremely smooth (high sheen or dents off shutter concrete) apply Slurrycote as per data sheet and allow drying for 24 hours.
 4. Use the same treatment for plastered surfaces with chase or patch marks.
 - b. First coat: Mixing
 1. Mix 12ℓ clean drinking water with 30kg LIFESTYLE STUCCO powder in a steel mixing container using a mechanical stirrer (DO NOT use plastic container as pieces of ground plastic will cause scratch marks in the final trowel surface). Adjust viscosity to a thick paint of consistency.
 2. Allow (gel) to stand for 15 minutes.
 3. Re-mix
 4. Apply to porous surface with a block brush (pre-dampen porous surfaces to reduce suction)
 5. Allow first coat to dry for 24 hours.
- NB 6.** LIFESTYLE INTANACO STUCCO plaster is designed to be applied onto raw plaster or wood floated surfaces.
- c. Second Coat: mixing
 1. Mix 12ℓ clean drinking water with 30kg LIFESTYLE STUCCO powder in a steel mixing container using a mechanical stirrer
 2. Allow to gel for 15 minutes
 3. Dampen wall with clean water before applying second coat
 4. Now re-mix and adjust viscosity if necessary with clean water.
 - d. Application
 1. Trowel the entire surface using a uniform action.
 2. Allow to stiffen and steel trowel to a glass like finish – DO NOT throw excessive amounts of water when finishing as these run marks will show up when the final sealer is applied.
 3. Allow drying for 24 hours.
 4. Now sand off trowel marks with 220 grit water paper to remove unwanted trowel marks.
 5. Wipe off with a damp cloth and apply two coats of Lifestyle Matt sealer to enhance watability.
 6. Allow 6 hours between coats.

Packaging: 30kg durable polypropylene bag
Colours: 9 Awesome colours
Coverage: 15-20m² per 30kg bag
Shelf Life: 6 months, must be stored in dry cool conditions and ensure that bag is sealed
Cleaning Tools: Clean tap water

HEALTH AND SAFETY

This product contains fine cement and aggregates. Avoid inhalation. Contact with product may cause irritation to sensitive skin. Wear suitable protective clothing, eye/face protection. In case of insufficient ventilation, wear suitable respiratory protection.

DO NOT TAKE INTERNALLY
KEEP OUT OF REACH OF CHILDREN
THIS PRODUCT IS NONFLAMMABLE

DISCLAIMER NOTICE

The information given in this information sheet is based on controlled laboratory tests and many years of experience. It is given in good faith but not guarantee of any performance characteristic is given or implied. Lifestyle Colours can not be held liable for any consequential damage whatsoever nature that may rise from the use of Lifestyle Colours product. Paint technology is continually being developed and Lifestyle Colours reserves the right to update product specifications without prior notice. Contact Lifestyle Colours for details.

TECHNICAL: 083 446 6754
Email: info@lifestylecolours.co.za
Website: www.lifestylecolours.co.za