TECHNICAL DATA SHEET

DURA INDUSTRIAL 2K/POLYURETHANE THINNERS (DI021)

DESCRIPTION:

- **2K / POLYURETHANE THINNERS** is a diluent for the 2k and Heavy duty polyurethane (HDPU) coatings.
- **2K / POLYURETHANE THINNERS** can also be used to clean equipment.

FEATURES:

• APPEARANCE	Water like liquid
• S G @ 25°C (g/ml)	0.80
• VISCOSITY @ 25°C (sec)	10 – 12
• FLASH POINT (°C)	< 5
• FLAMMABILITY	Flammable

STORAGE STABILITY:

- Store in a separate safety storage cabinet or room.
- Keep container tightly closed and sealed until ready for use.
- Keep in a well ventilated place.
- Storage containers should be grounded and bonded.
- Store in a cool area away from all ignition sources.

PRODUCT PACKAGING:

- 5 LT
- 25 LT

COLOURS:

- Colourless

ISO 9001:2008 REGISTERED FIRM
5 Wakefield Road, Founders View South, Edenvale (opposite Modderfontein golf Course) | P.O. Box 303, Edenvale, 1610, South Africa
Tel: 011 452-5221 | Fax: 011 452-2313 | orders@durapaints.co.za | www.durapaints.co.za | Director M Lloyd

DURA PAINTS Futuretint Lifestyle Colours ProLong Quality Products Go Line 30 marking systems WEDGEWOOD PAINTS
Dura Paints (PTY) ltd. - CK 2012/184075/07

SAFETY PRECAUTIONS:

- Keep out of reach of children.
- Keep container in well ventilated place.
- Keep away from food, drink and animal feeding stuffs
- Keep away from sources of ignition - No smoking
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Wear eye/face protection.
- Use only in well ventilated areas
- This material and its container must be disposed of as hazardous waste.
- If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.
- Refer to the Material safety data sheet (MSDS) of **2K / POLYURETHANE THINNERS.**

DISCLAIMER:

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user.
They are based on results gained from our experiences and tests and are believed to be reliable.
No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.
Technology may change with time necessitating changes to this Technical Data Sheet (TDS)/MSDS. It is the responsibility of the user to ensure that the latest TDS is being used. See www.durapaints.co.za for the latest version.

ISO 9001:2008 REGISTERED FIRM
5 Wakefield Road, Founders View South, Edenvale (opposite Modderfontein golf Course) | P.O. Box 303, Edenvale, 1610, South Africa
Tel: 011 452-5221 | Fax: 011 452-2313 | orders@durapaints.co.za | www.durapaints.co.za | Director M Lloyd
DURA PAINTS Futuretint Lifestyle Colours ProLong Quality Products Go Line 30 marking systems WEDGEWOOD PAINT
Dura Paints (PTY) ltd. - CK 2012/184075/07