

WEDGEWOOD OPULENT TEXTURE COAT

WD 012

PRODUCT CODE:	White/Pastel (Wedgewood Plastic Containers)	: optexw (05) (20)
	Deep (Wedgewood Plastic Containers)	: optexde (05) (20)
	Transparent (Wedgewood Plastic Containers)	: optextr (05) (20)

PRODUCT DESCRIPTION: **Opulent Texture Coat** is a premium long lasting coating with a fine textured finish. It is ideal for direct application to exterior plastered surfaces where hair line cracks require hiding. **Opulent Texture Coat** is water-based, non- flammable and lead free.

INTENDED USES: Suitable for previously primed or painted areas such as cement plaster, gypsum plaster , concrete, fibre cement, ceiling boards and unglazed brick, provided that appropriate preparation is carried out.

FEATURES: Suitable for interior and exterior use (Tip. Due to its rough feel/texture consider using **Opulent Ripple Coat** on interior walls). Hides imperfections and hairline cracks. Low odour. Excellent coverage and hiding. This product comes with a 5 year quality guarantee. (Subject to Terms and Conditions)

PRODUCT INFORMATION:	<ul style="list-style-type: none"> • APPEARANCE Textured matt finish. • COLOUR White, can be tinted • SOLIDS% 55% by mass (Varies by colour/base) 40% by volume (Varies by colour/base) • S G @ 25°C 1.38 (Varies by colour/base) • RECOMMENDED DFT/PER COAT MIN : 35µm MAX: 45µm • PRACTICAL SPREADING RATE 4 to 6 m². (dependant on substrate and application thickness (DFT)) • VISCOSITY @ 25°C (WHITE) 115 to 120 KU (varies by colour/base.)
-----------------------------	--

APPLICATION DETAILS:

- MIXING Stir thoroughly with a flat paddle until homogeneous
- METHOD Lambs wool roller or brush.
- THINNING Not recommended.
- CLEANING Water
- SUBSTRATE Cement plaster, concrete, fibre-cement, ceiling boards, gypsum plaster.
- APPLICATION ENVIRONMENT

Surface Temp	Ambient Temp	Relative Humidity
Min 10°C or 2°C above dew point	Min 10°C or 2°C above dew point	Min: 10%
Max : 40°C	Max : 40°C	Max : 85%

- DRYING TIME

Touch dry	60 Min @ 25°C
Dry to handle	2 hours @ 25°C
Overcoating	4 hours @ 25°

STORAGE AND PACKAGING:

- Store away from direct sun, heat and severe cold. Do not exceed 50°C.
- Keep containers tightly closed.
- Packaging 5lt & 20lt
- Shelf life. 12 months from date of manufacture when correctly stored and unopened.

WEDGEWOOD OPULENT TEXTURE COAT (contd.)

TRANSPORTATION:

SHIPPING NAME:	Not classified
PACKAGING GROUP:	Not classified
HAZARD CLASS:	4-H-C
S.I.N/UN NUMBER:	Not classified dangerous for transport

SURFACE PREPARATION:

Ensure all surfaces are dry, less than 12% moisture content, and free from dirt, dust, chalking, oil, grease and any other contamination before painting.

Unpainted Substrate:

Cement plaster, concrete, ceiling boards, fibre cement, gypsum board.

- Prime with one coat **Wedgewood Opulent 2 in 1** water based primer/topcoat.
- Apply two or three coats **Wedgewood Opulent Texture Coat**, depending on colour.

Previously painted substrate

- Remove all loose and flaking paint by scrapping, sanding or hydro blasting - allow to dry. Clean with **ProLong ProSoap or ProLong ProSoap Liquid** to remove all contaminants. Rinse off **ProLong ProSoap/ProSoap Liquid** with water.
- Apply two or three coats **Wedgewood Opulent Texture Coat**, depending on colour.
- If the surface is chalky and cannot be thoroughly cleaned, apply one coat of **Opulent Bonding Liquid**, allow to dry overnight, then apply two or three coats **Wedgewood Opulent Texture Coat**, depending on colour.
- Fill defects with ProLong **Crackfill** or **ProLong Profill**, as part of the preparation.
- Mould/Algae. Remove by scrubbing with a solution of 4:1 Water/Bleach or Water/Chlorine. Saturate affected areas and allow to stand for a minimum of 4 hours. Rinse off thoroughly with clean water and allow to dry before painting.

APPLICATION:

Apply two (three coats for some low hiding colours) un-thinned to prepared surfaces so as to achieve complete obliteration.

Using a lambs wool roller apply using a combination of overlapping vertical, horizontal and diagonal strokes. Do not over apply (spread) the product.

Note: Brushing may give an uneven finish.

CAUTIONS:

- Avoid painting during inclement weather or if temperature is below 10°C.
- For optimum performance a practical recommended spreading rate of 4 m² / l should not be exceeded.
- Do not over spread the product.
- It is very important to purchase sufficient paint to complete the project. Different batches may result in slight variations in colour that are beyond the control of the manufacturer.

WEDGEWOOD OPULENT TEXTURE COAT (contd.)

SAFETY PRECAUTIONS:

- Keep out of reach of children.
 - Ensure good ventilation during application and drying.
 - In case of skin contact, wash with soap and water or a recognized skin cleaner. Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist. If ingested give plenty of water / milk. Do not induce vomiting. Seek medical attention.
 - Refer to Material Safety Data Sheet for complete information. See www.durapaints.co.za.
-

DISCLAIMER:

- *The recommendations contained herein are given in good faith and are meant to guide the specifier or the user.*
- *They are based on results gained from our experiences and tests and are believed to be reliable.*
- *No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.*
- *Technology may change necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used. See www.durapaints.co.za.*